

## GENERAL PRODUCT



# DEWAXIT<sup>TM</sup>

## Low Foam, Ammonia Free, Floor Wax Stripper

### FEATURES/BENEFITS

#### Features

Highly concentrated  
Excellent detergency  
Safe on most floors  
Powerful and fast stripping  
Low foam

#### Benefits

Low chemical consumption  
Also cleans walls, woodwork  
and floors  
Minimum labor required  
Effective in automated floor  
scrubbers

*Dewaxit* is available in 6 gallon pails,  
55 gallon drums and bulk deliveries

### Description

*Dewaxit* is a low foam, heavy duty, non-ammoniated floor stripper that removes old wax films and metal cross-linked polymeric finishes from floor surfaces.

*Dewaxit* will not harm floor surfaces such as asphalt, rubber, linoleum or vinyl when used as directed.

*Dewaxit* is also an excellent daily maintenance cleaner for floors, walls, shelves, woodwork, and is an outstanding product for ultrasonic cleaning.

### Typical Use Directions for Floor Stripping (also see product label)

Stripping	Water Temperature	Dwell Time		
		<u>Dewaxit Concentration</u>	<u>Concentration</u>	<u>Minutes</u>
		Non-metallic	Metal-Complex	
Light to Med.	Warm to Hot	1:16	1:8	5 - 10
Heavy Duty	Warm to Hot	1:4	1:4	5 - 10
Automatic	Hot	1:16	1:8	5 typical

#### Manual Stripping:

Mix *Dewaxit* with water, apply solution to floor and allow to dwell. Pick up loosened wax with Wet-vac or mop. Rinse thoroughly with water.

#### Automatic Stripping:

Mix *Dewaxit* with water and completely wet floor. Brushes and/or stripping pads should be at full pressure. After dwell, make second pass with pads on floating pressure. Squeegee down and vacuum on, solution valve off.

#### Daily Maintenance:

Mix 1 part *Dewaxit* to 64 parts water. This solution will not strip floor wax.

**IMPORTANT:** Before using DEWAXIT, always be sure to read and follow precautions and directions for use appearing on the product container label and MSDS. (Mar04)