



GRAFIKLEEN® LVR96

Roller & Blanket Wash

FEATURES/BENEFITS

Features

No SARA Title III ingredients

High flash point (over 140°F)

Low odor

One product cleans blankets,
rollers & pipe rollers

Benefits

Reduced reporting

Safer for employees to use

Removes ink and lint in one
application

Pleasant to work with

Reduced solvent consumption

VOC reductions when mixed
with water

Cost reductions

Excellent cleaning efficiency

Grafikleen LVR96 is available in 6 gallon pails, 55 gallon drums, totes and bulk deliveries.

Description

VOC (method 24) 96%, 6.62 lbs/gl, 795 gms/l

Grafikleen LVR96 is the first step of West/Penetone's four-step conversion to low VOC press washes. *Grafikleen LVR96* is designed to familiarize press operators with slower evaporating solvents, the introduction of water into the cleaning process and working with solvents with higher flash points.

Directions for Use

Blankets (Hand Wipe Applications): Start by working with the product in its concentrated form. When press operators become comfortable with the product, try using it at 1:1 dilution with water. The advantage of using water is its ability to remove both paper lint and ink in one application, as well as reducing VOCs.

Using The Product In Its Concentrated Form: Apply *Grafikleen LVR96* in its concentrated form just as you would any other traditional blanket wash. On sheet-fed presses, a lightly water dampened rag should be used to dry the blanket. For web presses, the blanket can be dried using the same process, or the web can be used to take the solvent off the blanket.

Using The Product With Water: Dilute *Grafikleen LVR96* 1:1 with water and apply via a rag that is not dripping wet. On web presses you may want to disengage the web during cleaning. Dry the blanket with a lightly water dampened rag.

Rollers: Apply *Grafikleen LVR96* either diluted 1:1 with water or concentrated. Clean one side of the roller train at a time. Allow the press to idle for a short period of time, then engage the wash-up blades. Reapply *Grafikleen LVR96*, then rinse the roller train with water.

Pipe Rollers: Use *Grafikleen LVR96* in its concentrated form. Apply the wash to the web and spin the roller backwards by hand.

IMPORTANT: Before using *Grafikleen LVR96*, always be sure to read and follow precautions and directions for use appearing on the product container label and MSDS. (Apr05)