



PENMUL™ R950

Heavy Duty Solvent Emulsion Degreaser

FEATURES/BENEFITS

Features

- High flashpoint (150° TCC)
- Water rinseable
- Effective at room temperature
- Effective on asphaltic deposits
- Safe on all metals
- Works fast
- Free of chlorinates

Benefits

- Safer than flammable products
- Versatile and multipurpose
- No heat required
- Increased productivity

Penmul R950 is available in 6 gallon pails, 55 gallon drums, totes and bulk deliveries.

Description

Penmul R950 is a colorless mixture of solvent and emulsifiers intended for use in difficult industrial cleaning applications. *Penmul R950* is especially effective in loosening and dissolving asphaltic and heavy petroleum based soils and sludge accumulations.

Penmul R950 is typically used to clean and desludge oil storage tanks, engine blocks and where asphalt is mixed, applied or pumped.

Penmul R950 has a flashpoint above 140°F, rendering it non-hazardous for disposal.

Directions For Use:

Penmul R950 can be applied by brush or coarse spray, in a tank operation, or in a parts washing machine. When used in a tank, agitation should be provided for best results. *Penmul R950* may be used concentrated or diluted with water, mineral spirits, kerosene or fuel oil.

Application & Procedure Using *Penmul R950* Concentrated:

Automotive: Spray or brush on the undergear of trucks, buses, tractors, and road building equipment for removing asphalt, tar and pitch. Allow to set for a few minutes, then hose or wipe off.

Parts Washing: Soak until oils and grease are removed. Rinse with water or mineral spirits.

NOTE: *Penmul R950* may attack asphaltic flooring and some plastics. Pre-test on these surfaces before using. Do not use on painted surfaces.

IMPORTANT: Before using *PENMUL R950*, always be sure to read and follow precautions and directions for use appearing on the product container label and MSDS. (Sep06)