GENERAL PRODUCT



NAVITONETM

Low Odor Solvent Emulsion Degreaser

FEATURES/BENEFITS

Features

Safe on all metals

Heat not required

Removes the heaviest deposits

Works fast

Water rinsable

Increased viscosity

No flash point to boiling (212°F)

Benefits

Versatility

Saves energy

Reduces labor in cleaning

Clings to vertical surfaces

Navitone is available in 6 gallon pails, 55 gallon drums, totes and bulk deliveries.

Description

Navitone is a unique cleaning product containing solvents, detergents and emulsifiers, and is formulated for use in the heaviest cleaning applications.

Navitone should be used in industrial environments such as steel mills, paper mills, asphalt application, refineries and power plants to effectively remove greases, tars and resins from production equipment, floors, castings, cellars and tools.

Typical Use Directions (also see product label)

Manual Operations: Dilute concentrate with water at 1:4 to 1:10. Wipe on, wipe off. Wear neoprene gloves.

Pressure Spray Methods: Dilute concentrate with water at 1:20. Use a coarse spray at long distance. Do not fine mist this product.

Tank Immersion: Mix concentrate with water at 1:4 to 1:10, depending on the degree of soil to be removed.

For extremely heavily soiled surfaces, use *Navitone* concentrated or diluted 1:1 with mineral spirits. When applied concentrated or mixed 1:1, the product is somewhat viscous and is ideally suited for cleaning upright surfaces. *Navitone* will cling to the surface until rinsed off.

NOTE: The product may attack certain flooring and plastics; pre-test on these surfaces before using.

IMPORTANT: Before using NAVITONE, always be sure to read and follow precautions and directions for use appearing on the product container label and MSDS. (Sep06)

