### GENERAL PRODUCT



# CITRIKLEEN® HD

## **Heavy-Duty Solvent Degreaser**

#### FEATURES/BENEFITS

#### **Features**

Biodegradable (after soil release)

No petroleum or chlorinated solvents

High flash point - 155°F (COC)

Effectively removes carbon

Multiple uses

Safer than conventional solvents

Water dilutable

Cleans a wide variety or soils

#### **Benefits**

Cost effective

Safer for employees to use

Pleasant to work with

Effective as many petroleum

and chlorinated solvents

Eliminates need for multiple

solvents

U.S. Patent 4.511.488

Canada Patent 1,222,425

Citrikleen HD is available in 6 gallon pails, 55 gallon drums, totes and bulk deliveries.

#### **Description**

Citrikleen HD is a patented blend of a natural hydrocarbon solvent (nonpetroleum), carbon removers and surfactants. It is specifically formulated to dislodge and reduce carbonaceous soils, gelled oils and grease masses into easily rinsed particles to leave a clean surface. Requiring no heat, Citrikleen HD has a pleasing odor and high efficiency. Permitted to stand overnight, oils, greases and carbonaceous particles will rise to the top of the tank and may be skimmed off.

#### **Directions for Use**

Citrikleen HD may be used concentrated at ambient temperatures in immersion tanks, or at various dilution rates with water, depending on soil conditions.

Soils	Water Dilution	Immersion Time
Grease & Carbon Light	1:4 to 1:20	30 minutes
Moderate	1:2 to 1:10	2 to 4 hours
Heavy	1:1 to 1:2	Overnight or longer
Solidified Grease	1:1 to 1:2	1 to 4 hours, depending on severity of soil. Some agitation may be required.
Gelled Oils	1:1 to 1:5	30 to 90 minutes. Mild agitation will reduce tank time.
Specialty Lubes	1:1 to 1:12 with	4 hours to overnight
<b>Properties</b>	mild agitation	
Physical Form		
Odor citrus-pine		
pH (as received) $11.0 \pm 0.5$ Specific Gravity $0.95$		
Weight Per Gallon (liter)		
Flash Point (C.O.C.)		
Fire Point (C.O.C.)		
Stability		
Solubility In Water excellent Rinsability With Water excellent		
Biodegradable		
Metal Safety test on nonferrous alloys, zinc and cadmium-plated substrates before use		

IMPORTANT: Before using CITRIKLEEN HD, always be sure to read and follow warnings and directions for use appearing on the product container label, MSDS and applicable current technical manual. (Feb04)

YOUR CLEANING SOLUTIONS RESOURCE.

Penetone Corporation • 700 Gotham Parkway • Carlstadt, New Jersey 07072 • (800) 631-1652 West Penetone, Inc. • 10900 Secant Street • Ville d'Anjou, QC H1J 1S5 • (514) 355-4660