



PENPOWER™ 150H

Non-Caustic Heavy Duty Cleaner

FEATURES/BENEFITS

Features

Effective at low concentrations
Safe on all metals
Hard water tolerant
Excellent rinsability
Caustic free

Benefits

Economical to use
One product for all metals
Less hazardous to use than
caustic products
Bright soil-free surface after
rinsing

Penpower 150H is available in 175
and 450 lb. drums.

Description

Penpower 150H is a dustless, free flowing, tan powder, that dissolves quickly in water.

Penpower 150H contains emulsifying, penetrating, and grease dissolving ingredients, and is ideal for a wide variety of applications. Some applications are: removing machinery oils and buffing compounds prior to electroplating, steam cleaning of transportation equipment, hot tank cleaning of engine blocks, and concrete deck and general floor cleaning.

Typical Use Directions (also see product label)

Hot Tank Cleaning and Degreasing: *Penpower 150H* is recommended for use at 6 to 10 ounces per gallon of water between temperatures of 180°F to boiling. Immersion time is dependent on type and degree of soil to be removed.

Steam Cleaning: For use in steam cleaning operation, use *Penpower 150H* at 2 to 4 ounces per gallon of water.

High Pressure Washing: Use *Penpower 150H* at 1/2 to 1 ounce per gallon of water for heavy-duty transportation equipment washing.

Manual Cleaning: *Penpower 150H* is generally used at 2 to 4 ounces per gallon of hot water. For heavy soil build-up, 3 to 6 ounces per gallon is recommended.

IMPORTANT: Before using *PENPOWER 150H*, always be sure to read and follow precautions and directions for use appearing on the product container label and MSDS. (Sep06)

