



MATERIAL SAFETY DATA SHEET

Penetone® Corporation, 700 Gotham Parkway, Carlstadt, NJ 07072

PEN-CRETE™

Page: 1 of 4
Date: February 17, 2004
MSDS No.: 2480-402K

SECTION 1 PRODUCT IDENTIFICATION & EMERGENCY INFORMATION

PRODUCT NAME: PEN-CRETE
GENERAL USE: Concrete treatment
PRODUCT DESCRIPTION: Concrete treatment
GENERIC INGREDIENTS: Acrylic emulsion in water

EMERGENCY TELEPHONE NUMBERS: **PENETONE 201-567-3000**
CHEMTREC 800-424-9300

SECTION 2 HAZARDOUS INGREDIENT SECTION

This product is nonhazardous as defined in 29 CFR 1910.1200.

OSHA HAZARDOUS INGREDIENTS

	CAS#	EXPOSURE LIMITS 8 hrs. TWA (mg/m ³)		Supplier
		OSHA PEL	ACGIH TLV	
Dibutyl phthalate	84-74-2	5	5	---

SECTION 3 HEALTH INFORMATION & PROTECTION

EMERGENCY OVERVIEW:

Off-white emulsion with sweet odor.
Can be irritating to skin and eyes.

POTENTIAL HEALTH EFFECTS:

EYE CONTACT:

Irritating to the eyes on contact only.

SKIN CONTACT:

Frequent or prolonged contact may irritate or dry the skin and cause dermatitis. Skin contact may aggravate an existing dermatitis condition.

INHALATION:

Inhalation of spray mist may cause irritation to the respiratory tract.

INGESTION:

Ingestion may cause irritation to the digestive tract and diarrhea.

CHRONIC:

Ingestion of high doses of dibutyl phthalate has caused birth defects in lab animals. Ingestion of high doses of dibutyl phthalate has also caused kidney, liver, and blood damage in lab animals, and testicular and other reproductive organ effects in male rats.

FIRST AID MEASURES:

EYE CONTACT:

Flush eyes with large amounts of water. See physician immediately.

SKIN CONTACT:

Flush skin with large amounts of water. Remove contaminated clothing and launder before reuse. If skin irritation develops or persists, consult physician.

INHALATION:

Remove person to fresh air. Administer oxygen or artificial respiration as needed. Call a physician immediately.

INGESTION:

If swallowed, give plenty of water or milk. Call a physician immediately.

WORKPLACE EXPOSURE CONTROLS:

PERSONAL PROTECTION:

Safety glasses are recommended for all workplace conditions. Rubber gloves are recommended. Other protective gear, including splash proof goggles or face shield, rubber boots, apron, gauntlets, or rain gear should be worn depending on how the product is used.

VENTILATION:

None needed under normal use conditions. If the product is being sprayed, a dust mask or particle respirator is recommended.

SECTION 4 FIRE & EXPLOSION HAZARDS

FLASH POINT: None to boiling point (TCC, COC)

FLAMMABLE LIMITS: Not applicable

AUTOIGNITION TEMPERATURE: Not determined

GENERAL HAZARD:

This is a water based product and presents no unusual hazards in a fire.

FIRE FIGHTING:

Cool containers with water.

HAZARDOUS COMBUSTION PRODUCTS:

Smoke, fumes, and oxides of carbon when taken to dryness.

SECTION 5 SPILL CONTROL MEASURES

LAND SPILL:

For small spills, use absorbent material such as towels or absorbent powders. Put all material into proper waste disposal container with lid tightly covered. For larger spills, dike spill, recover free liquid, and use absorbent material to dry area. Rinse area with water. Put all material into appropriate waste containers.

WATER SPILL:

Product is water based and water dilutable. Surfactants used in this product are biodegradable. Localized high concentration of product may cause fish kills, but no persistent or long term effects will result. Dibutyl phthalate is listed in the Clean Water Act. Check with local environmental regulatory agencies for reporting requirements.

SECTION 6 HANDLING & STORAGE

STORAGE TEMPERATURE, °F: ambient. DO NOT STORE ABOVE 120° F. KEEP FROM FREEZING.

GENERAL: Do not store near oxidizers.

SECTION 7 TYPICAL PHYSICAL & CHEMICAL PROPERTIES

BOILING POINT, °F:

about 212

EVAPORATION RATE, Acetone = 1:

equal to water

SOLUBILITY IN WATER:

soluble

SPECIFIC GRAVITY at 75°F:

1.01

ODOR AND APPEARANCE:

off-white emulsion with sweet odor

VAPOR PRESSURE, mm Hg at 20°C:

equal to water

VAPOR DENSITY (Air = 1):

equal to water

WT% ORGANIC VOLATILES:

about 5

pH:

7-8

SECTION 8 REACTIVITY DATA

GENERAL:

This product is stable and hazardous polymerization will not occur.

INCOMPATIBLE MATERIALS AND CONDITIONS TO AVOID:

Oxidizers.

SECTION 9 REGULATORY INFORMATION

DEPARTMENT OF TRANSPORTATION (DOT):

PROPER SHIPPING NAME:

NONHAZARDOUS (nonregulated) MATERIAL

HAZARD CLASS: none

IDENTIFICATION NUMBER: none

PACKING GROUP: none

LABEL: not required

FLASH POINT: None-to-boil

pH: 7-8

TSCA: The ingredients in this product are listed on the TSCA inventory.

CERCLA:

This product contains the following reportable CERCLA material:

Dibutyl phthalate CAS# 84-74-2 RQ = 10 lbs

Releases exceeding the RQ must be reported to the National Response Center, 800-424-8802, and may be subject to state and local reporting.

RCRA HAZARD CLASS:

U069 Dibutyl phthalate

SARA TITLE III:**311/312 HAZARD CATEGORIES:**

Acute health, Chronic health

313 REPORTABLE INGREDIENTS:Dibutyl phthalate CAS# 894-74-2 1 wt%
Diethylene glycol butyl ether CAS# 112-34-5 5 wt%**CLEAN WATER ACT:**

Dibutyl phthalate is listed in the Clean Water Act as a hazardous substance and priority pollutant.

CALIFORNIA PROPOSITION 65 INFORMATION:

This product does not contain any chemicals recognized by the state of California to cause cancer and/or birth defects or reproductive harm.

SCAQMD INFORMATION:Is there a photochemically reactive material present? No
What is the % by volume of photochemically reactive material? 0
What is the VOC content? about 50 g/l
What is the vapor pressure of VOC's? less than 0.1 mm Hg 20°C

SECTION 10 NOTES

HAZARD RATING SYSTEMS:

	HMIS	NFPA
HEALTH	1	1
FLAMMABILITY	0	0
REACTIVITY	0	0

KEY
4 = Severe
3 = Serious
2 = Moderate
1 = Slight
0 = Minimal**REVISION SUMMARY:**

Change in header

SUPERSEDES ISSUE DATE:

January 19, 1998

FOR ADDITIONAL PRODUCT INFORMATION, CONTACT YOUR SALES ENGINEER
FOR ADDITIONAL HEALTH/SAFETY INFORMATION, CALL 201-567-3000

THE INFORMATION PRESENTED HEREIN HAS BEEN COMPILED FROM SOURCES CONSIDERED TO BE DEPENDABLE AND ACCURATE TO THE BEST OF PENETONE'S KNOWLEDGE. THE INFORMATION RELATES TO THIS SPECIFIC MATERIAL. IT MAY NOT BE VALID FOR THIS MATERIAL IF USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY ONESELF AS TO THE SUITABILITY AND COMPLETENESS OF THIS INFORMATION FOR HIS OWN PARTICULAR USE.