

GENERAL PRODUCT



PEN-CRETE™

Aqueous Concrete Coating

FEATURES/BENEFITS

Use Inside or Out
Dries, Cures Rapidly
Protects Hard Surfaces
Satin-Gloss Finish
Slip Resistant
Easy to Apply
No Solvent Odor or Flash Point
Minimal Floor Preparation
Prevents Abrasion & Marking
Nonyellowing

Pen-Crete is available in 55 gallon drums and 5 gallon pails. Inquire about availability in other packages.

2480a.bul.wpd

(Mar05)

Description

Pen-Crete is a water-based thermoplastic dispersion, recommended for interior and exterior nonresilient surfaces such as concrete, exposed aggregate, brick, masonry floors and walls.

Coverage:

Horizontal Surfaces: 500 - 800 square feet per gallon.

Vertical Surfaces: 1500 - 2500 square feet per gallon.

Typical Use Directions (also see product label)

Remove all grease, oil and other foreign material by scrubbing with a heavy-duty concrete cleaner and wire brush. Rinse thoroughly with clean water and allow to dry. On permanent coatings, it is recommended that they be abraded with a 100 mesh screen back disk. Put down a test patch if there is any question of adhesion. Extremely dense or hardened concrete may require acid etching prior to coating.

For best results, apply with a lamb's wool applicator or a low pressure sprayer (recommended 40 psi) such as a Hudson Power Sprayer.

Allow one to two hours dry time, depending on conditions before applying second coat. A third coat is recommended to insure protection and higher gloss. The final coat should dry 6-8 hours before subjecting to heavy traffic.

IMPORTANT: Before using *Pen-Crete*, always be sure to read and follow warnings and directions for use appearing on the product container label and MSDS.

Penetone Corporation • 700 Gotham Parkway • Carlstadt, NJ 07072 • (800) 631-1652
West Penetone, Inc. • 10900 Secant St. • Ville d'Anjou, QC H1J 1S5 • (514) 355-4660



YOUR CLEANING SOLUTIONS RESOURCE.