

GENERAL PRODUCT



BARRIER COATING™

Anti-Graffiti Coating for Non-Porous Surfaces

FEATURES/BENEFITS

Easy to apply

Safe on most non-porous surfaces

Covers up to 400 sq. ft./gallon

Dries to a hard transparent film

Easy graffiti removal

Barrier Coating is available in 55 gallon drums and 6 gallon pails. Inquire about availability in other packages.
2590A.bul.wpd (Mar04)

Description

Barrier Coating is a liquid coating which when applied to non-porous surfaces, such as those found on transportation equipment, leaves a hard, transparent film that acts as a barrier between the surface and graffiti. Graffiti is then easily removed with *Dewaxit*.

Typical Use Directions (also see product label)

Use as received. Apply to surfaces with a paint brush roller. Each gallon will cover approximately 250-400 square feet. Product will dry in one to three hours.

Typical Surfaces

Barrier Coating may be used on non-porous plastic, stone, wood, metal, and glass.

Typical Properties

Appearance: White to slightly tan emulsion

Odor: Slightly ammoniacal

Specific Gravity: 1.0

pH: 9 - 10

IMPORTANT: Before using *Barrier Coating*, always be sure to read and follow warnings and directions for use appearing on the product container label and MSDS.

Penetone Corporation • 700 Gotham Parkway • Carlstadt, NJ 07072 • (800) 631-1652
West Penetone, Inc. • 10900 Secant St. • Ville d'Anjou, QC H1J 1S5 • (514) 355-4660



YOUR CLEANING SOLUTIONS RESOURCE.