

GENERAL PRODUCT



PENPOWER[®] 225L

Aluminum Safe Alkaline Cleaner and Degreaser

FEATURES/BENEFITS

Controlled foam
Safe on soft metals as well as cast iron and steel
Effective at low concentrations
Excellent Rinsing
Long solution life
Defoamers not normally needed
One product for all applications
Very economical
Less frequent recharges
Excellent pre-paint cleaner

PENPOWER 225L is available in 450 and 200 lb. drums.
3150a.bul.wpd (Feb04)

Description

PENPOWER 225L is a powerful powdered alkaline detergent formulated to provide heavy duty degreasing an high pressure cabinet type power spray washers.

PENPOWER 225L will quickly remove heavy oils and greases, buffing compounds, drawing lubes and rust preventative compounds.

PENPOWER 225L is also effective in hot tank applications to degrease engine and transmission parts.

Typical Use Directions (also see product label)

High Pressure Recirculation Systems:

Use ½ to 2 ounces per gallon at 160° to 180° F.

Hot Tanks:

Use at 6 to 10 ounces per gallon at 140° F to boiling.
Immersion time is 5 to 60 minutes.

Manual and Floor Cleaning:

Use at 1 to 6 ounces per gallon. Mop and rinse.

IMPORTANT: Before using Penpower 225L, always be sure to read and follow warnings and directions for use appearing on the product container label and MSDS.

Penetone Corporation • 700 Gotham Parkway • Carlstadt, NJ 07072 • (800) 631-1652
West Penetone, Inc. • 10900 Secant St. • Ville d'Anjou, QC H1J 1S5 • (514) 355-4660



YOUR CLEANING SOLUTIONS RESOURCE.