



CITRIKLEEN[®] HD THIXOTROPIC

Water-Based, Biodegradable Natural Gel Solvent

FEATURES/BENEFITS

Features

- Clings to vertical surfaces
- Cleans heavy greases and oils
- Moderate carbon removal
- Pleasant odor
- Water rinsable
- Aerospace approved per
McDonnell-Douglas CSD-1,
Type I and Type II

Benefits

- Does not need reapplication
caused by drip-off
- Easy to clean recessed areas
- Removes moist soils found in
the industrial environment

U.S. Patent 4,511,488
Canada Patent 1,222,425

Citrikleen HD Thixotropic is available in 6 gallon pails, 55 gallon drums and bins.

Description

Citrikleen HD Thixotropic is a patented blend of natural hydrocarbons that performs the function of several cleaners and degreasers. *Citrikleen HD Thixotropic* is used as an exterior aircraft cleaner, flap and wheel well cleaner, engine parts cleaner and hydraulic parts cleaner. *Citrikleen HD Thixotropic* will stick to surfaces, allowing the cleaner to penetrate the deposit rather than run off onto the ground. The increased dwell time will allow the cleaner to work while the product is being applied to other areas. *Citrikleen HD Thixotropic* is *Citrikleen HD* containing a thickening agent. It has all the corrosion resistance properties of *Citrikleen HD*.

Directions for Use

Spray on undiluted, allow 5-45 minute dwell, brush if needed, then high pressure water rinse. *Citrikleen HD Thixotropic* may be used at ambient temperature in immersion tanks, or at various dilution rates with water, depending on soil conditions.

Do not heat above 125°F.

<i>Use or Application</i>	<i>Water Dilution</i>	<i>Method</i>
Grease & Carbon		
Light	Mix 9:1	Spray or brush
Moderate	Mix 2:1	on, rinse once
Heavy	Use straight	

IMPORTANT: Before using CITRIKLEEN HD THIXOTROPIC, always be sure to read and follow warnings and directions for use appearing on the product container label, MSDS and applicable current technical manual. (Dec05)