GENERAL PRODUCT



PENSOLVTM L945

High Performance Solvent Cleaner

FEATURES/BENEFITS

Features

145°FTCC flash point

Superior cleaning compared to mineral spirits

Safer for user than most solvent cleaners

Pleasant odor

Safe on all metals

Low vapor pressure

Free of chlorinates

Benefits

Environmentally improved

Fast cleaning to improve productivity

User friendly compared to kerosene and mineral spirits

Pensolv L945 is available in 24 x 13 oz. aerosol and pump spray, 6 gallon pails, 55 gallon drums, totes and bulk deliveries.

Description

Pensolv L945 is a solvent blend that is formulated to have a closed cup flash point above 140°F, but provides the same excellent cleaning performance as a solvent with a much lower flash point. The pleasant odor and low vapor pressure of **Pensolv L945** make it an ideal plant-wide cleaning solvent. **Pensolv L945** will quickly clean oils, greases, many adhesives, flux and fingerprints. Dry time is 15-25 minutes.

Directions For Use

By Immersion: Immerse parts for several minutes, agitate as needed, remove parts and drain solvent back into tank. Air dry.

By Spray: Spray on, brush as needed, rinse with Pensolv L945.

Caution: Electrical equipment should be off or not operating when cleaning. Do not restart equipment until thoroughly dry. Test on plastics and elastomers.

IMPORTANT: Before using PENSOLV L945, always be sure to read and follow warnings and directions for use appearing on the product container label and MSDS. (Mar04)

