



PENMUL L599

Biodegradable Solvent Emulsion Degreaser

FEATURES/BENEFITS

Features

- Biodegradable
- Effective when used cold
- Caustic free
- Fast rinsing
- Spray on/rinse off
- Little to no odor

Benefits

- Environmentally friendly
- Clings to vertical surfaces
- Steam and heat not required
- Safer than most heavy duty degreasers
- Fast and cost effective heavy degreasing

Penmul L599 is available in 6 gallon pails, 55 gallon drums, totes and bulk deliveries.

Description

Penmul L599 is a heavy duty degreaser formulated to meet today's needs of tough industrial cleaning along with improved safety and environmental friendliness.

Penmul L599 works in place of caustic and/or objectionable solvent containing cleaning formulations, without performance compromise.

Penmul L599 effectively cleans grease, hydraulic fluids and gear oils from production machinery, mill cellars, walls and floors.

Penmul L599 has a viscosity of typically thirty to forty centipoise and will dwell on vertical surfaces, degreasing rather than running off. (it can be thickened even further by adding 10% water).

Penmul L599 is typically used in steel mills, refineries, railroad shops and similar industrial environments.

Typical Use Directions (also see product label)

Heavy Equipment, Oil Cellars and Rolling Mills: Spray concentrate onto soiled surface, allow five to thirty minutes dwell and rinse with a fire hose or high pressure water. Cover sensitive components and electric control boxes.

Floor Cleaning: Mix two to eight ounces of *Penmul L599* to one gallon of hot or cold water. Mop and rinse.

High Pressure Cleaning: Siphon into water at a ratio of one to five percent. Use hot or cold water.

Tank Immersion: Use concentrated to four parts water. Heat to 160°F for most effective cleaning.

IMPORTANT: Before using *PENMUL L599*, always be sure to read and follow precautions and directions for use appearing on the product container label and MSDS. (Sep06)