



# PENSOLV™ L1055

## Multi-Purpose Solvent Cleaner

### FEATURES/BENEFITS

#### Features

Very low odor  
High flash point-155°F (TCC)  
Free of chlorinates  
TLV 300 PPM  
Low vapor pressure  
High dielectric voltage  
Excellent cleaning  
Residue free after drying

#### Benefits

Workshop is odor free  
Non-hazardous flashpoint  
Safer for the user than most solvent cleaners  
Safe for use on electric motors after source of electricity is disconnected

*Pensolv L1055* is available in 6 gallon pails, 55 gallon drums, totes and bulk deliveries

### Description

PENSOLV™ L1055 Solvent Cleaner was formulated as a more user friendly replacement for kerosene and mineral spirits. It can be used in large quantities without generating excessive odors.

The high flashpoint and excellent solvency make *Pensolv L1055* the ideal cleaning solvent for maintenance parts. It can be applied manually in a conventional parts washer or enclosed spray cabinet.

### Directions for Use

By Immersion - immerse and agitate parts for five to ten minutes in ambient temperature solvent. Allow to air dry or blow dry to accelerate. Brush if needed.

Spray Booth - Spray by non-atomizing coarse spray at fifteen to fifty PSI onto parts. Cleaning chamber should be sealed. Blow surface dry or allow to air dry.

### Typical Uses

- Wipe down of precision equipment
- Calender stack residue removed
- Degrease roller bearings
- Plastic mold cleaning
- Parts washing

**IMPORTANT:** Before using PENSOLV L1055, always be sure to read and follow precautions and directions for use appearing on the product container label and MSDS. (0295)