## GENERAL PRODUCT



# PL-998<sup>TM</sup>

## **Acid Metal Cleaner/Treatment**

#### FEATURES/BENEFITS

#### **Features**

Excellent detergency

Non-fuming acid

Removes heat scale

Highly concentrated

#### **Benefits**

Effective on tough soils

Safer to use

Lower use cost

**PL-998** is available in 15 and 30 gallon drums.

#### **Description**

**PL-998** is a versatile acid based cleaner possessing heavy duty detergent properties and powerful acid metal conditioners. **PL-998** is used in both production and maintenance applications.

#### **Some Typical Production Uses:**

- · Cleaning and phosphatizing of steel prior to painting
- · Stainless steel vat cleaning in food processing plant

#### **Some Typical Maintenance Uses:**

- · Descaling of heat exchangers and air pre-heaters
- · Heavy duty cleaning of tile and grout in a shower room
- · Derusting of tools, nuts, bolts and hardware
- · Aluminum etching and brightening

### Typical Use Directions (also see product label)

**Prepaint Steel Conditioning and Cleaning:** Mix *PL-998* at 5%-20% by volume, heat to 150°F. Immersion time will vary with condition of metal. Consult PENETONE for recommendations.

**Descaling and Derusting:** Mix *PL-998* at 10%-20% by volume. Heating to 150°F will accelerate cleaning. Application time will vary. Test to determine.

**Tile and Grout:** Foam apply at 10%-15% by volume. Use hot water. Allow 1-3 minutes dwell, rinse before dry. Apply from bottom up, rinse from top down.

IMPORTANT: Before using PL-998, always be sure to read and follow precautions and directions for use appearing on the product container label and MSDS. (Jul04)

