



# MATERIAL SAFETY DATA SHEET

Penetone® Corporation, 700 Gotham Parkway, Carlstadt, NJ 07072

OLD SALT™

Page: 1 of 4

Date Prepared: February 27, 2004

MSDS No.: 6830-402S

## SECTION 1 PRODUCT IDENTIFICATION & EMERGENCY INFORMATION

**PRODUCT NAME:** OLD SALT

**GENERAL USE:** Degreaser

**PRODUCT DESCRIPTION:** Solvent emulsion

**GENERIC INGREDIENTS:** Water, aliphatic hydrocarbons, surfactants, builders

**EMERGENCY TELEPHONE NUMBERS:** PENETONE 201-567-3000

CHEMTREC 800-424-9300

## SECTION 2 HAZARDOUS INGREDIENT SECTION

This product is hazardous as defined in 29 CFR 1910.1200.

**OSHA HAZARD: HEALTH**

### OSHA HAZARDOUS INGREDIENTS

	CAS#	EXPOSURE LIMITS 8 hrs. TWA (ppm)		Supplier
		OSHA PEL	ACGIH TLV	
Aliphatic hydrocarbons	64742-47-8	not established	not established	200

## SECTION 3 HEALTH INFORMATION & PROTECTION

### EMERGENCY OVERVIEW:

Clear, amber liquid with pine odor.

Can be irritating to eyes, skin, and respiratory tract.

### POTENTIAL HEALTH EFFECTS:

#### EYE CONTACT:

Slightly irritating but does not injure eye tissue. High vapor concentrations may be irritating.

#### SKIN CONTACT:

Frequent or prolonged contact may irritate or dry the skin or cause dermatitis. Skin contact may aggravate an existing dermatitis condition.

#### INHALATION:

High vapor/aerosol concentrations (greater than the TLV) are irritating to the respiratory tract, may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects.

#### INGESTION:

Small amounts of this liquid may be drawn into the lungs by either swallowing or vomiting. This may cause severe and delayed health effects such as inflammation of the lungs and infection of the bronchi. Ingestion may cause irritation of the digestive tract and diarrhea.

## FIRST AID MEASURES:

### EYE CONTACT:

Flush eyes with large amounts of water. See physician immediately.

### SKIN CONTACT:

Flush skin with large amounts of water. Use soap if available. Remove contaminated clothing and launder before reuse. If skin irritation develops or persists, consult physician.

### INHALATION:

Remove person to fresh air. Administer oxygen or artificial respiration as needed. Call a physician immediately.

### INGESTION:

If swallowed, DO NOT INDUCE VOMITING. Use a stomach pump. Call a physician immediately.

## WORKPLACE EXPOSURE CONTROLS:

### PERSONAL PROTECTION:

Safety glasses are recommended for all workplace conditions. Solvent resistant gloves are recommended where prolonged skin exposure is expected. Other protective gear, including splash proof goggles or face shield, rubber boots, aprons, gauntlets, or rain gear should be worn depending on how the product is used.

### VENTILATION:

None needed under normal use conditions. For enclosed areas, or where large amounts of the product are being used, the use of fans or other mechanical ventilation is recommended. An organic vapor mask should be used if the TLV is exceeded and a particle mask if the product is sprayed. DO NOT MIST THIS PRODUCT. Use coarse spray only.

---

## SECTION 4 FIRE & EXPLOSION HAZARDS

---

**FLASH POINT:** None to 200°F TCC

**FLAMMABLE LIMITS:** not determined

**AUTOIGNITION TEMPERATURE:** not determined

### GENERAL HAZARD:

Can form combustible mixtures above 200°F.

Containers can rupture and explode under fire conditions due to pressure and vapor buildup.

### FIRE FIGHTING:

Either allow fire to burn out under controlled conditions or extinguish with water, foam, or dry chemical.

Cool exposed containers with water spray.

### HAZARDOUS COMBUSTION PRODUCTS:

Smoke, fumes, and oxides of carbon and sulfur.

---

## SECTION 5 SPILL CONTROL MEASURES

---

### LAND SPILL:

Eliminate sources of ignition. For small spills, use absorbent material such as towels or absorbent powders. Put all material into proper waste disposal container with lid tightly covered. **Solvent soaked materials may spontaneously combust.** For larger spills, dike spill, recover free liquid, and use absorbent material to dry area. Rinse area with water. Put all material into appropriate waste containers.

### WATER SPILL:

Remove product from water surface by skimming or with suitable absorbents. This product contains surfactants which will cause it to disperse in water. Localized high concentrations of this product may cause fish kills, but no persistent or long term effects will result. Check with local environmental regulatory agencies for reporting requirements.

---

## SECTION 6 HANDLING & STORAGE

---

**STORAGE TEMPERATURE, °F:** ambient. DO NOT STORE ABOVE 120 Deg. F. KEEP FROM FREEZING.

**GENERAL:** Keep away from heat sources, open flames, and other ignition sources. Do not store near strong oxidants.

---

## SECTION 7 TYPICAL PHYSICAL & CHEMICAL PROPERTIES

---

**BOILING POINT, °F:**

about 212

**EVAPORATION RATE, n-butyl acetate = 1:**

less than 0.05

**SOLUBILITY IN WATER:**

emulsifies

**SPECIFIC GRAVITY at 75°F:**

0.895

**ODOR AND APPEARANCE:**

clear amber liquid with pine odor

**VAPOR PRESSURE, mm Hg at 20°C:**

equal to water

**VAPOR DENSITY (Air = 1):**

greater than 1

**WT% ORGANIC VOLATILES:**

about 45

**pH:**

13

---

## SECTION 8 REACTIVITY DATA

---

**GENERAL:**

This product is stable and hazardous polymerization will not occur.

**INCOMPATIBLE MATERIALS AND CONDITIONS TO AVOID:**

Strong oxidizing agents.

---

## SECTION 9 REGULATORY INFORMATION

---

**DEPARTMENT OF TRANSPORTATION (DOT):**

**PROPER SHIPPING NAME:**

NONREGULATED (nonhazardous) MATERIAL

**HAZARD CLASS:** none

**IDENTIFICATION NUMBER:** none

**PACKING GROUP:** none

**LABEL:** not required

**FLASH POINT:** none to 200°F TCC

**pH:** 13

**TSCA:** The ingredients in this product are listed on the TSCA inventory.

**CERCLA:**

This product contains no reportable CERCLA materials. Contact local authorities to determine if there may be other local reporting requirements.

**RCRA HAZARD CLASS:**

Nonhazardous waste

**SARA TITLE III:****311/312 HAZARD CATEGORIES:**

Acute health

**313 REPORTABLE INGREDIENTS:**

None

**NEW JERSEY RIGHT-TO-KNOW INFORMATION:**

This product contains water (CAS# 7732-18-5), aliphatic hydrocarbons (CAS# 64742-47-8), alkylphenol ethoxylate (CAS# 9016-45-9), sodium dodecylbenzene sulfonate (CAS# 25155-30-0), and pine oil (CAS# 8002-09-3).

**CALIFORNIA PROPOSITION 65 INFORMATION:**

This product does not contain any chemicals recognized by the state of California to cause cancer and/or birth defects or reproductive harm.

**SCAQMD INFORMATION:**

Is there a photochemically reactive material present? No

What is the % by volume of photochemically reactive material? 0

What is the VOC content? 390 g/l

What is the vapor pressure of VOC's? 0.03 mm Hg @ 20°C

---

**SECTION 10 NOTES**

---

**HAZARD RATING SYSTEMS:**

	HMIS	NFPA
HEALTH	1	1
FLAMMABILITY	1	1
REACTIVITY	0	0

KEY  
4 = Severe  
3 = Serious  
2 = Moderate  
1 = Slight  
0 = Minimal

**REVISION SUMMARY:**

Change in header

**SUPERSEDES ISSUE DATE:**

October 7, 1993

FOR ADDITIONAL PRODUCT INFORMATION, CONTACT YOUR SALES ENGINEER  
FOR ADDITIONAL HEALTH/SAFETY INFORMATION, CALL 201-567-3000

THE INFORMATION PRESENTED HEREIN HAS BEEN COMPILED FROM SOURCES CONSIDERED TO BE DEPENDABLE AND ACCURATE TO THE BEST OF PENETONE'S KNOWLEDGE. THE INFORMATION RELATES TO THIS SPECIFIC MATERIAL. IT MAY NOT BE VALID FOR THIS MATERIAL IF USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY ONESELF AS TO THE SUITABILITY AND COMPLETENESS OF THIS INFORMATION FOR HIS OWN PARTICULAR USE.