

PENAIR® M-5571

Solvent Emulsion Cleaner Aromatic Solvent General Use Exterior Aircraft Cleaner

Exhaust Stain and Carbon Remover - Safe On All Aircraft Metals

Qualified Under MIL-PRF-85570 Type I

WARNING: COMBUSTIBLE MIXTURE

CONTAINS DIPROPYLENE GLYCOL METHYL ETHER (CAS# 34590-94-8) AND AROMATIC HYDROCARBONS (CAS# 64742-94-5). FLASH POINT 147° F (TCC). VAPOR HARMFUL. IRRITATING TO SKIN AND EYES. HARMFUL IF SWALLOWED. KEEP OUT OF REACH OF CHILDREN. Keep away from heat, sparks, and open flames. Avoid breathing of vapors and spray mist. Adequate ventilation, including open doors and windows, exhaust fans and air movements must be provided. Avoid contact with skin, eyes, and clothing. When using, wear safety glasses or splash-proof goggles and solvent resistant gloves. Other equipment including face shield and apron are recommended if the product is sprayed. Use coarse spray only. DO NOT FOG. If spraying, wear a particle mask. Launder contaminated clothing before reuse. Overexposure can cause headaches, drowsiness, or nausea.

FIRST AID: In case of contact with skin and eyes, immediately flush affected areas with large amounts of water for 15 minutes. For eyes, consult physician immediately. For skin, consult physician if irritation develops or persists. In case of excessive inhalation, remove to fresh air. Give artificial respiration if needed. Call a physician immediately. If ingested, drink plenty of milk and/or water. DO NOT INDUCE VOMITING. Call a physician immediately.

FIRE PROCEDURE: Extinguish with foam, dry chemical, or CO₂.

STORAGE AND HANDLING: Keep container closed when not in use. Store away from heat, sparks or open flame, and at temperatures below 120°F. If *Penair M-5571* should freeze, thaw and mix before using. Store only in original container. Do not cut, weld or reuse empty container. Dispose of container and contents only in accordance with local, state, and Federal EPA regulations.

Use product within two years of purchase date. To reorder, call 800-631-1652 or 800-421-6211.

DIRECTIONS FOR USE:

For Most General Cleaning Operations: Apply PENAIR M-5571 by coarse spray, foam (see NAVAIR 01-1A-509, Section 2), mop, sponge, cloth or brush After allowing a short dwell time, scrub by brush or otherwise and thoroughly rinse with fresh water to ensure removal of stubborn deposits.

For Light Soils: Mix 1 part Penair M-5571 in 14 parts water.

For Moderate Soils: Mix 1 part Penair M-5571 in 9 parts water.

For Heavy Soils: Mix 1 part Penair M-5571 in 4 parts water.

For Regular Cleaning of Exhaust Track Areas, Wheel and Tire Wells: Dilute 1:2 with water. Apply to surface liberally, preferably with a high pressure sprayer. After a dwell time of 1 to 2 minutes, agitate with mop head or soft bristled brush where necessary, then hose or pressure rinse thoroughly with large volumes of water.

For Extremely Heavily Soiled Surfaces: Use *Penair M-5571* concentrated or diluted 1:1 with water.

IMPORTANT: Always follow the instructions contained in the appropriate service/technical manuals prior to cleaning.

NEW JERSEY RIGHT-TO-KNOW INFORMATION: This product contains water (CAS# 7732-18-5), alkyl phenol ethoxylate (CAS# 9016-45-9), dipropylene glycol monomethyl ether (CAS# 34590-94-8), aromatic hydrocarbons (CAS# 64742-94-5), and diethylene glycol (CAS# 111-46-6).

CALIFORNIA PROPOSITION 65 INFORMATION: This product does not contain chemicals recognized by the state of California to cause cancer and/or birth defects or reproductive harm.

(9904.lbl) (Nov05)