



**TPC SOLVENT™ AEROSOL**

Page: 1 of 7  
Date Prepared: January 29, 2016  
MSDS No.: 1884Aero

**SECTION 1: IDENTIFICATION**

**Product name:** TPC SOLVENT AEROSOL

**Recommended use:** General purpose bench top aerosol solvent degreaser

**Physical Description:** Clear water white liquid with mild odor

**Generic Ingredients:** Hydrocarbon solvent & propellant

**Distributed by:**

Penetone Corporation  
700 Gotham Parkway  
Carlstadt, NJ 07072  
800-631-1652 or 201-567-3000

**Business Contact:**

Customer Service  
800-631-1652 x2602 or 2272  
Product Safety  
800-631-1652 x2211 or 2257

**Manufacturer:**

ExxonMobil Chemical Company  
13501 Katy Freeway  
Houston, TX 77079-1398  
Product Name: Exxon OMS

**Emergency Phone Numbers:**    **PENETONE 201-567-3000**    **CHEMTREC 800-424-9300**

**SECTION 2: HAZARDS IDENTIFICATION**

**GHS CLASSIFICATION:**

<p><b>Health:</b> Aspiration hazard: 1 Specific target organ toxicity - single exposure: 3</p>	<p><b>Physical:</b> Flammable aerosol: 1 Compressed gas</p>
--	---

**DANGER!**

Extremely Flammable Aerosol.  
Contains Gas Under Pressure; May Explode if Heated.  
May Be Fatal If Swallowed and Enters Airways.  
May Cause Drowsiness or Dizziness.



<b>Precautionary Statements:</b>	
<p><u>Prevention:</u> Keep away from heat/sparks/open flames/hot surfaces.--No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing fumes, vapors or mists if inhalable mists occur during use. Use only outdoors or in a well-ventilated area.</p> <p><u>Response:</u> <i>If inhaled:</i> Remove person to fresh air and keep comfortable for breathing. Call a poison center, doctor, emergency room or 911 if you feel unwell.</p>	<p><i>If swallowed:</i> Immediately call a poison center, doctor, emergency room, or 911. Do NOT induce vomiting.</p> <p><u>Storage:</u> Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store locked up. Store in a well ventilated place.</p> <p><u>Disposal:</u> Dispose of contents/container in accordance with local, regional, and national regulations (see Sections 13 and 15 of SDS for disposal and reporting requirements).</p>

**SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS**

Chemical Name	CAS#	Concentration Wt% (1)
Aliphatic petroleum naphtha	64742-48-9	>90
Carbon dioxide	124-38-9	<10

(1) Exact percentages being withheld under trade secret provision of OSHA HCS 1910.1200(l)



---

**TPC SOLVENT™ AEROSOL**

Page: 2 of 7  
Date Prepared: January 29, 2016  
MSDS No.: 1884Aero

---

---

**SECTION 4: FIRST-AID MEASURES**

---

**General Description of Symptoms & First-Aid Measures**

Most likely work-place exposure routes will be *skin contact* or *inhalation*.

For *skin contact*, typically no immediate effects will be observed. Slight reddening or minor irritation could develop some time after exposure if product is not washed off.

*Inhalation* exposure may produce varied effects, particularly if exposure occurs above the recommended workplace exposure limits (see SECTION 8). Typical symptoms would include headaches, dizziness, and drowsiness. In extreme cases, unconsciousness and other central nervous effects may occur.

**Eyes**

Rinse cautiously with water for several minutes. If contact lenses present, remove them if easy to do. Continue rinsing for several minutes. If eye irritation develops: Get medical advice or attention. Penetone recommends that after any eye exposure and initial treatment a physician be seen immediately..

**Ingestion**

If swallowed: Immediately call a poison center, doctor, physician or other competent medical authority. Product presents an aspiration hazard. **DO NOT INDUCE VOMITING.**

**Inhalation**

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center, doctor, physician or other competent medical authority if you feel unwell.

**Skin**

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. A mild soap may be used to wash skin. Wash contaminated clothing before reuse.

**Special Treatment / Other**

None

---

**SECTION 5: FIRE FIGHTING MEASURES**

---

**Flammable Properties**

**Classification:** 3

**Flash Point:** 130°F TCC, 145°F COC

**Autoignition Temperature:** about 660°F

**Lower Flammable Limit:** 0.6 **Upper Flammable Limit:** 6

**Specific Hazards**

Flammable aerosol. Aerosol cans are under pressure. Exposure to temperatures above 120°F can cause bursting of cans. Containers can rupture and explode under fire conditions due to pressure and vapor buildup.

**Extinguishing Media**

**Suitable:** SMALL FIRE: Use dry chemical, carbon dioxide (CO<sub>2</sub>), water spray or regular foam. LARGE FIRE: water spray, water fog, or foam.

**Unsuitable:** Do not use solid water stream as this may spread fire.

**Protection & Precautions for Firefighters**

**Protective Equipment & Clothing:** Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters protective clothing will only provide limited protection.

**Fire Fighting Guidance:** Mist/spray can burn at temperatures below flash point. Cool containers with flooding quantities of water until well after fire is out. Move containers from fire area if you can do it safely. Dike fire control



---

**TPC SOLVENT™ AEROSOL**

Page: 3 of 7  
Date Prepared: January 29, 2016  
MSDS No.: 1884Aero

---

water for later disposal; do not scatter material. Containers can expand and explode under fire conditions due to vapor buildup. Always stay away from containers engulfed in fire.

**Hazardous Combustion Products:** Smoke, fumes, and oxides of carbon.

---

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

---

**Land Spill**

Eliminate sources of ignition. Do not touch or walk through spilled material. Stop leak if you can do it safely. For large spills, dike and pump into properly labeled containers for reclamation or disposal. For small spill, soak up with absorbent material and place in properly labeled containers for disposal.

**Water Spill**

Remove product from water surface by skimming or with suitable absorbents. Put into properly labeled containers for reclamation or disposal. If allowed by local environmental regulatory agencies, you may use a suitable dispersant. Check with local environmental regulatory agencies for reporting requirements.

See **SECTION 8 for EXPOSURE CONTROLS and PERSONAL PROTECTION.**

---

**SECTION 7: HANDLING & STORAGE**

---

**Handling**

Do not handle near heat, sparks, or flame. Avoid contact with oxidizing agents. Use only with adequate ventilation/personal protection (SEE section 8). Avoid contact with eyes, skin and clothing. After handling, always wash hands thoroughly with soap and water. Avoid personal contact with any residue. Dispose of empty containers with care. Empty containers can contain flammable residue and explosive vapors. **Do not cut, weld, or reuse empty container.**

**Storage**

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Do not store near heat, sparks, open flame, or other ignition sources. Do not store near strong oxidizing agents. Do not store in direct sunlight. Avoid storing above 120°F (49°C).

---

**SECTION 8: EXPOSURE CONTROLS and PERSONAL PROTECTION**

---

**Engineering Controls**

Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits.

**Personal Protection**

Inhalation A respiratory protection program that meets OSHA's 29 CFR 1910.134 or ANSI Z88.2 requirements must be followed whenever workplace conditions warrant respirator use. Use of an organic vapor mask or respirator is recommended.

Skin Wear chemical resistant gloves such as: rubber, nitrile, neoprene, or latex when skin contact is possible. Protective clothing including gloves, apron, sleeves, boots, head and face protection should be worn depending on how the product is used. PPE should be cleaned thoroughly after each use.

Eyes Penetone recommends always wearing safety glasses as a minimum in any workplace. Conditions may warrant the use of chemical goggles and possibly a face shield. Consult your standard operating procedure or safety professional for advice. Use protective eye and face devices that comply with ANSI Z87.1-1987.

**Additional Remarks**

Selection of appropriate personal protective equipment should be based on an evaluation of the performance



---

**TPC SOLVENT™ AEROSOL**

Page: 4 of 7  
Date Prepared: January 29, 2016  
MSDS No.: 1884Aero

---

characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use.

**Occupational Exposure Limits**

<u>Component Name</u>	<u>Source</u>	<u>Value</u>	<u>Type</u>	<u>Notation</u>
Aliphatic petroleum naphtha	ACGIH	1200 mg/m <sup>3</sup>	TWA	Appendix H
	NIOSH	350 mg/m <sup>3</sup>	TWA	
Carbon dioxide		1800 mg/m <sup>3</sup>	C	15 minutes
	OSHA Z1	500 ppm	TWA	
	ACGIH	5,000 ppm	TWA	
		30,000 ppm	STEL	
	NIOSH	5,000 ppm	TWA	
		30,000 ppm	STEL	
	OSHA	5,000 ppm	TWA	

---

**SECTION 9: PHYSICAL & CHEMICAL PROPERTIES**

---

**Appearance:** clear water white liquid  
**Odor:** mild hydrocarbon  
**Odor Threshold:** not determined  
**pH:** not applicable  
**Melting Point / Freezing:** -80°F (pour point)  
**Boiling Point / Boiling Point Range:** 340-380°F  
**Flash Point:** 130°F TCC, 145°F COC  
**Evaporation Rate:** 0.1 (n-butyl acetate =1)  
**Flammability:** not applicable  
**Lower Flammable Limit:** 0.6  
**Upper Flammable Limit:** 6  
**Explosive Properties:** not applicable to the contents  
**Vapor Pressure:** <1 mm Hg at room temperature  
**Relative Vapor Density:** 5  
**Relative Density:** 0.76  
**Solubility (Water):** insoluble  
**Partition Coefficient (K<sub>ow</sub>):** not determined  
**Auto-ignition temperature:** 660°F  
**Decomposition temperature:** not available  
**Viscosity:** 2 cSt

---

**SECTION 10: STABILITY & REACTIVITY**

---

**Reactivity**  
Not reactive.

**Chemical Stability**  
Stable under normal conditions.

**Hazardous Reactions**  
No hazardous reactions or under normal storage conditions. Hazardous polymerization will not occur.

**Conditions to Avoid**  
Product is a flammable aerosol. Do not store near sources of heat, sparks, open flame, or other ignition sources.



---

**TPC SOLVENT™ AEROSOL**

Page: 5 of 7  
Date Prepared: January 29, 2016  
MSDS No.: 1884Aero

---

**Incompatible Materials**

Strong oxidizing agents.

**Hazardous Decomposition Products**

Carbon monoxide and dioxide.

---

**SECTION 11: TOXICOLOGICAL INFORMATION**

---

**Product Summary**

Product is essentially non-toxic. May cause mild, short lasting discomfort to the eye. Prolonged or repeated exposure may dry the skin leading to discomfort and dermatitis. Vapor/aerosol concentrations above recommended exposure levels are irritating to the eyes and respiratory tract, and may cause headaches, dizziness, drowsiness, unconsciousness and other central nervous system effects.

*NOTE: Values in this section refer only to the solvent.*

**Acute Toxicity:**

**Dermal:** LD50 > 2,000 mg/kg rat; LD50 > 5,000 mg/kg rabbit

**Inhalation:** LC50 > 5,000 mg/m<sup>3</sup> (vapor) 8 hrs rat

**Oral:** LC50 > greater than near-saturated vapor concentration 1hr rat

**Skin Corrosion/Irritation**

Mildly irritating to skin with prolonged exposure. Prolonged exposure may dry the skin leading to discomfort and dermatitis. Not considered irritating based on test data for structurally similar materials.

**Serious Eye Damage/Irritation**

May cause mild, short-lasting discomfort. Not considered irritating based on test data for structurally similar materials.

**Sensitization - Respiratory or Skin**

Not expected to be a respiratory or skin sensitizer. Based on test data for structurally similar materials.

**Germ Cell Mutagenicity**

Not expected to be a germ cell mutagen. Based on test data for structurally similar materials.

**Carcinogenicity**

Not expected to cause cancer. Based on test data for structurally similar materials.

**Reproductive Toxicity**

Not expected to be a reproductive toxicant. Based on test data for structurally similar materials.

**Specific Target Organ Effects - Single Exposure**

Not expected to cause organ damage from a single exposure.

**Specific Target Organ Effects - Repeated or Prolonged Exposure**

Not expected to cause organ damage from prolonged or repeated exposure. Based on test data for structurally similar materials.

**Aspiration Hazard**

Based upon available data and comparison to similar materials, if swallowed, may pose a lung aspiration hazard during vomiting. Lung aspiration may result in chemical pneumonitis, pulmonary edema, and damage to lung tissue or death.



---

**TPC SOLVENT™ AEROSOL**

Page: 6 of 7  
Date Prepared: January 29, 2016  
MSDS No.: 1884Aero

---

---

**SECTION 12: ECOLOGICAL INFORMATION**

---

**Product Summary**

Product is essentially insoluble in water in water. Product expected to be not toxic at the limit of its water solubility.

*NOTE: Values in this section refer only to the solvent.*

**Ecotoxicity**

Acute toxicities, LC0, EL0, NOECR > 1000 mg/l.

**Persistence and Degradability**

Expected to be readily biodegradable. Transformation due to hydrolysis and photolysis not expected to be significant. Expected to degrade rapidly in air.

**Bioaccumulative Potential**

Due to biodegradability, expected to have low bioaccumulative potential.

**Mobility in soil**

Expected to adsorb onto soil

**Other Adverse Effects**

None known

---

**SECTION 13: DISPOSAL CONSIDERATIONS**

---

Product is a D001 Ignitable Hazardous Waste under RCRA definitions. Dispose of contents/container in accordance with all applicable federal, state, and local regulations.

**Note:** Contaminated product, soil, water, container residues and spill cleanup materials may be hazardous wastes. Appropriate hazardous waste designation is the responsibility of the user.

---

**SECTION 14: TRANSPORT INFORMATION**

---

**ID No.:** UN1950  
**Proper Shipping Name:** AEROSOLS  
**Hazard Class:** 2.1  
**Packing Group:** not applicable  
**Marine Pollutant:** No  
**RQ:** No  
**Special Precautions:** none

---

**SECTION 15: REGULATORY INFORMATION**

---

**TSCA**

The ingredients in this product are listed on the TSCA inventory.

**RCRA HAZARD CLASS**

D001 - Ignitable hazardous waste

**SARA 311/312 REPORTABLE HAZARD CATEGORIES:** Immediate (Acute) Health Fire



**TPC SOLVENT™ AEROSOL**

Page: 7 of 7  
Date Prepared: January 29, 2016  
MSDS No.: 1884Aero

**REPORTING REQUIREMENTS** (all quantities in pounds)

Component	CAS / 313 Code	Section 302 (EHS) TPQ	Section 304 EHS RQ	CERCLA RQ	Section 313	CAA 112(r) TQ	CWA / OPA
Aliphatic petroleum naphtha	64742-48-9			(1)			(2)
<p>(1) This material is not subject to any special reporting under the requirements of CERCLA. CERCLA petroleum exclusion applies for this product. Contact local authorities to determine if other reporting requirements apply.</p> <p>(2) This product is classified as an oil under Section 311 of the CWA (40 CFR 110) and the OPA of 1990. Discharge or spills which produce a visible sheen on either surface water, or in waterways/sewers which lead to surface water, must be reported to the National Response Center at 800-424-8802.</p>							

**NEW JERSEY RIGHT-TO-KNOW INFORMATION**

This product contains aliphatic petroleum naphtha (CAS# 64742-48-9) and carbon dioxide (CAS# 124-38-9)

**CALIFORNIA PROPOSITION 65 INFORMATION**

This product does not contain any chemicals recognized by the state of California to cause cancer and/or birth defects or reproductive harm.

**SCAQMD INFORMATION**

Is there a photochemically reactive material present? No  
 What is the % by volume of photochemically reactive material? 0  
 What is the VOC content? 760 g/l  
 What is the vapor pressure of VOC's? <1 mm Hg at room temperature

**SECTION 16: OTHER INFORMATION**

**REVISION SUMMARY**

Change in Section 1

**SUPERSEDES ISSUE DATE**

March 17, 2015

**HAZARD RATING SYSTEMS:**

	<u>HMIS</u>	<u>NFPA</u>
HEALTH	1	1
FLAMMABILITY	2	2
REACTIVITY	0	0
	B	

**KEY**  
 4 = Severe  
 3 = Serious  
 2 = Moderate  
 1 = Slight  
 0 = Minimal

FOR ADDITIONAL PRODUCT INFORMATION, CONTACT YOUR SALES ENGINEER  
 FOR ADDITIONAL HEALTH/SAFETY INFORMATION, CALL 201-567-3000

THE INFORMATION PRESENTED HEREIN HAS BEEN COMPILED FROM SOURCES CONSIDERED TO BE DEPENDABLE AND ACCURATE TO THE BEST OF PENETONE'S KNOWLEDGE. THE INFORMATION RELATES TO THIS SPECIFIC MATERIAL. IT MAY NOT BE VALID FOR THIS MATERIAL IF USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY ONESELF AS TO THE SUITABILITY AND COMPLETENESS OF THIS INFORMATION FOR HIS OWN PARTICULAR USE.