



**NV-80®**

Page: 1 of 8  
 Date Prepared: March 15, 2015  
 MSDS No.: 2840

**SECTION 1: IDENTIFICATION**

**Product name:** NV-80

**Recommended use:** Degreaser

**Physical Description:** Clear amber liquid with aromatic odor

**Generic Ingredients:** Water, aromatic hydrocarbons, surfactants, coupling agents, inorganic builder

**Manufacturer:**

Penetone Corporation  
 700 Gotham Parkway  
 Carlstadt, NJ 07072  
 800-631-1652 or 201-567-3000

**Business Contact:**

Customer Service  
 800-631-1652 x2602 or 2272  
 Product Safety  
 800-631-1652 x2211 or 2257

**Emergency Phone Numbers:**    **PENETONE 201-567-3000**    **CHEMTREC 800-424-9300**

**SECTION 2: HAZARDS IDENTIFICATION**

**GHS CLASSIFICATION:**

<p><b>Health:</b>          Skin corrosion: 1C          Eye damage: 1          Specific target organ toxicity - single exposure: 3</p>	<p>Aspiration hazard: 1</p> <p><b>Physical:</b>          not classified</p>
---	---

**DANGER!**

Causes Severe Skin Burns and Eye Damage.  
 May Cause Drowsiness or Dizziness.  
 May Be Fatal If Swallowed and Enters Airways.



<b>Precautionary Statements:</b>	
<p><u>Prevention:</u>          Avoid breathing fumes or vapors. Do not breath mists if inhalable mists occur during use. Use only outdoors or in a well-ventilated area.          Wear protective gloves, eye protection, and face protection. Wash hands and exposed skin thoroughly after handling.          Keep container tightly closed. Keep away from heat/sparks/open flames/hot surfaces. No smoking.</p> <p><u>Response:</u>  <i>If in eyes:</i> Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.  <i>If on skin (or hair):</i> Take off immediately all contaminated clothing. Rinse skin with water or shower. A mild soap may be used. Wash</p>	<p>contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.  <i>If inhaled:</i> Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center, doctor, emergency room or 911 if you feel unwell.  <i>If swallowed:</i> Rinse mouth. Do NOT induce vomiting. Immediately call a poison center, doctor, emergency room, or 911.</p> <p><u>Storage:</u>          Store locked up. Store in a well-ventilated place. Keep cool. Keep container tightly closed.</p> <p><u>Disposal:</u>          Dispose of contents/container in accordance with local, regional, and national regulations (see Sections 13 and 15 of SDS for disposal and reporting requirements).</p>

**SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS**

Chemical Name	CAS#	Concentration Wt% (1)
Water	7732-18-5	50-75
Aromatic petroleum naphtha	64742-94-5	25-50



**NV-80®**

Page: 2 of 8  
Date Prepared: March 15, 2015  
MSDS No.: 2840

Potassium fatty acid soap	61790-44-1	1-10
1-Butoxyethanol	111-76-2	1-10
Ethoxylated nonylphenol	127087-87-0	1-10
Sodium silicate	1344-09-8	<1

(1) Exact percentages being withheld under trade secret provision of OSHA HCS 1910.1200(i)

## SECTION 4: FIRST-AID MEASURES

### General Description of Symptoms & First-Aid Measures

Most likely work-place exposure routes will be *skin contact* or *inhalation*.

For *skin contact*, typically no immediate effects will be observed. Reddening, irritation, or a burning sensation could develop some time after exposure if product is not quickly washed off.

*Inhalation* exposure may produce varied effects depending on whether vapor or mist/spray is inhaled (see SECTION 8 for recommended workplace exposure limits). For vapor, typical symptoms would include headaches, dizziness, and drowsiness. In extreme cases, unconsciousness and other central nervous effects may occur. For mist/spray, typical symptoms could include coughing, sneezing, and a tingling or burning sensation in the nose, throat, and lungs.

### Eyes

If in eyes: Rinse cautiously with water for several minutes. If contact lenses present, remove them if easy to do. Continue rinsing for several minutes. Immediately call a poison center, doctor, physician or other competent medical authority for medical advice. Penetone recommends that after any eye exposure and initial treatment a physician be seen immediately.

### Ingestion

If swallowed: Rinse mouth. Immediately call a poison center, doctor, physician or other competent medical authority. Product presents an aspiration hazard. DO NOT INDUCE VOMITING.

### Inhalation

If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center, doctor, physician or other competent medical authority for medical advice.

### Skin

If on skin: Take off immediately all contaminated clothing. Rinse skin with water or shower. A mild soap may be used. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice or attention.

### Special Treatment / Other

None

## SECTION 5: FIRE FIGHTING MEASURES

### Flammable Properties

**Classification:** not classified

**Flash Point:** none to boil

**Autoignition Temperature:** not determined

**Lower Flammable Limit:** not determined **Upper Flammable Limit:** not determined

### Specific Hazards

Contains combustible solvent. Although no flash point up to 200°F, combustible vapors may be given off above this temperature. The product is water based and water dilutable and will self extinguish with addition of water.

### Extinguishing Media

**Suitable:** SMALL FIRE: Use dry chemical, carbon dioxide (CO<sub>2</sub>), water spray or regular foam. LARGE FIRE: water



**NV-80®**

Page: 3 of 8  
Date Prepared: March 15, 2015  
MSDS No.: 2840

spray, water fog, or foam.

**Unsuitable:** Do not use solid water stream as this may spread fire.

**Protection & Precautions for Firefighters**

**Protective Equipment & Clothing:** Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters protective clothing will only provide limited protection.

**Fire Fighting Guidance:** Cool containers with flooding quantities of water until well after fire is out. Move containers from fire area if you can do it safely. Dike fire control water for later disposal; do not scatter material. Containers can expand and explode under fire conditions due to vapor buildup. Always stay away from containers engulfed in fire.

**Hazardous Combustion Products:** Smoke, fumes, and oxides of carbon, particularly when taken to dryness.

---

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

**Land Spill**

Eliminate sources of ignition. Do not touch or walk through spilled material. Stop leak if you can do it safely. For large spills, dike and pump into properly labeled containers for reclamation or disposal. For small spill, soak up with absorbent material and place in properly labeled containers for disposal.

**Water Spill**

Product forms emulsion with water which may make cleanup difficult. Avoid agitation to minimize emulsion formation. Remove product from water surface by skimming or with suitable absorbents. Put into properly labeled containers for reclamation or disposal. If allowed by local environmental regulatory agencies, you may use a suitable dispersant. Check with local environmental regulatory agencies for reporting requirements.

See **SECTION 8 for EXPOSURE CONTROLS and PERSONAL PROTECTION.**

---

**SECTION 7: HANDLING & STORAGE**

**Handling**

Do not handle near heat, sparks, or flame. Avoid contact with oxidizing agents. Use only with adequate ventilation/personal protection (SEE section 8). Avoid contact with eyes, skin and clothing. After handling, always wash hands thoroughly with soap and water. Avoid personal contact with any residue. Dispose of empty containers with care. Empty containers can contain flammable residue and explosive vapors. **Do not cut, weld, or reuse empty container.**

**Storage**

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Do not store near heat, sparks, open flame, or other ignition sources. Do not store near strong oxidizing agents. Do not store in direct sunlight. Avoid storing above 120°F (49°C).

---

**SECTION 8: EXPOSURE CONTROLS and PERSONAL PROTECTION**

**Engineering Controls**

Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits.

**Personal Protection**

**Inhalation** A respiratory protection program that meets OSHA's 29 CFR 1910.134 or ANSI Z88.2 requirements must be followed whenever workplace conditions warrant respirator use. Use of an organic vapor mask or respirator is recommended.



**NV-80®**

Page: 4 of 8  
Date Prepared: March 15, 2015  
MSDS No.: 2840

**Skin** Wear chemical resistant gloves such as: rubber, nitrile, neoprene, or latex when skin contact is possible. Protective clothing including gloves, apron, sleeves, boots, head and face protection should be worn depending on how the product is used. PPE should be cleaned thoroughly after each use.

**Eyes** Penetone recommends always wearing safety glasses as a minimum in any workplace. Conditions may warrant the use of chemical goggles and possibly a face shield. Consult your standard operating procedure or safety professional for advice. Use protective eye and face devices that comply with ANSI Z87.1-1987.

**Additional Remarks**

Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use.

**Occupational Exposure Limits**

<u>Component Name</u>	<u>Source</u>	<u>Value</u>	<u>Type</u>	<u>Notation</u>
Aromatic petroleum naphtha	ACGIH	100 mg/m <sup>3</sup>	TWA	Appendix H
	NIOSH	350 mg/m <sup>3</sup>	TWA	
		1800 mg/m <sup>3</sup>	Ceiling	
1-Butoxyethanol	ACGIH	20 ppm	TWA	15 minutes
	NIOSH	5 ppm	TWA	A3; BEI
		OSHA	50 ppm	TWA

**SECTION 9: PHYSICAL & CHEMICAL PROPERTIES**

**Appearance:** clear amber liquid  
**Odor:** aromatic  
**Odor Threshold:** not determined  
**pH:** 12-13  
**Melting Point / Freezing:** about 30°F  
**Boiling Point / Boiling Point Range:** about 212°F  
**Flash Point:** none to boil  
**Evaporation Rate:** equal to water  
**Flammability:** not applicable  
**Lower Flammable Limit:** not determined  
**Upper Flammable Limit:** not determined  
**Explosive Properties:** not applicable  
**Vapor Pressure:** equal to water  
**Relative Vapor Density:** equal to water  
**Relative Density:** 1.04  
**Solubility (Water):** forms emulsion (stable for one to 12 hours)  
**Partition Coefficient (K<sub>ow</sub>):** not determined  
**Auto-ignition temperature:** not determined  
**Decomposition temperature:** not determined  
**Viscosity:** 10 to 30 centipoise at room temperature

**SECTION 10: STABILITY & REACTIVITY**

**Reactivity**  
Not reactive.



**NV-80®**

Page: 5 of 8  
Date Prepared: March 15, 2015  
MSDS No.: 2840

**Chemical Stability**

Stable.

**Hazardous Reactions**

None known.

**Conditions to Avoid**

Contains combustible liquid. Do not store near sources of heat, sparks, open flame, or other ignition sources.

**Incompatible Materials**

Strong oxidizing agents. Strong acids.

**Hazardous Decomposition Products**

Smoke, fumes, and oxides of carbon, particularly when taken to dryness.

---

**SECTION 11: TOXICOLOGICAL INFORMATION**

---

**Product Summary**

Product is corrosive to skin, eyes, and other tissues, including oral and gastrointestinal. Mists can be corrosive to the eyes and respiratory tract. Ingestion may result in severe damage to the mouth, tongue, throat, and esophagus. Vapor/aerosol concentrations above recommended exposure levels may be irritating to the eyes and respiratory tract, and may cause headaches, dizziness, drowsiness, unconsciousness and other central nervous system effects.

**Acute Toxicity:**

**Dermal:** Rabbits, LD50 > 3,000 mg/kg (estimated using additivity formula)

**Inhalation:** no data available

**Oral:** Rats, LD50 > 3,000 mg/kg (estimated using additivity formula)

**Skin Corrosion/Irritation**

Based upon component data and product pH, product as a whole may be corrosive to the skin.

**Serious Eye Damage/Irritation**

Based upon component data and product pH, product as a whole may be corrosive to the eyes and potentially cause serious eye damage.

**Sensitization - Respiratory or Skin**

Based upon component data, not expected to be a skin sensitizer.

**Germ Cell Mutagenicity**

Based upon component data, not expected to cause germ cell mutagenicity.

**Carcinogenicity**

Ethylene glycol monobutyl ether is listed by ACGIH as Group A3: Confirmed animal carcinogen with unknown relevance to humans. Available evidence does not suggest that the agent is likely to cause cancer in humans except under uncommon or unlikely routes or levels of exposure.

**Reproductive Toxicity**

No data available.

The nonionic surfactant used in this product has produced effects in the fetus only at levels that were toxic to the parent animals.

Ethylene glycol monobutyl ether has been toxic to the fetus lab animals at doses toxic to the mother. Effects on reproduction have been seen only at doses that produced significant toxicity to the parent animal.

**Specific Target Organ Effects - Single Exposure**

No data available.



## SAFETY DATA SHEET

Penetone® Corporation, 700 Gotham Parkway, Carlstadt, NJ 07072

NV-80®

Page: 6 of 8  
Date Prepared: March 15, 2015  
MSDS No.: 2840

### Specific Target Organ Effects - Repeated or Prolonged Exposure

No data available.

The aromatic hydrocarbon caused kidney effects in male rats which are not considered relevant to humans.

Repeated exposure to ethylene glycol monobutyl ether has caused hemolysis and secondary effects on the kidney and liver in lab animals. Small but statistically significant increases in tumors were observed in mice but not rats. These effects are not believed to be relevant to humans.

In three month study, rats fed 200, 600, and 1800 ppm sodium silicate, changes were reported in the blood chemistry of some animals, but no specific organ effects were observed. In a 4 week 2.4g/kg/day oral feeding study, kidney effects were seen in dogs but no observed effects seen in rats. 600 and 1200 ppm sodium silicate in drinking water of rats decreased number of births and survival to weaning. Frequent ingestion over extended periods of time of gram quantities of sodium silicate are associated with kidney stone formation and other siliceous urinary calculi in humans.

### Aspiration Hazard

Based upon available data and comparison to similar materials, if swallowed, may pose a lung aspiration hazard during vomiting. Lung aspiration may result in chemical pneumonitis, pulmonary edema, and damage to lung tissue or death.

## SECTION 12: ECOLOGICAL INFORMATION

### Product Summary

Product is expected to be toxic to fish, aquatic invertebrates, algae, and microorganisms. (Acute aquatic toxicity category 2 by European Union classification.)

### Ecotoxicity

LC/EC/IC 1-10 mg/l (estimated using additivity formula)

### Persistence and Degradability

Product components range in biodegradability from not readily to readily biodegradable..

### Bioaccumulative Potential

No data available for the product. Aromatic solvent used in this product has the potential to bioaccumulate.

### Mobility in soil

No data available for the product. Product is a complex mixture. Components will partition into water and soil phases depending on inherent solubility of component in water.

### Other Adverse Effects

None known

## SECTION 13: DISPOSAL CONSIDERATIONS

Product is a D002 Corrosive Hazardous Waste under RCRA definitions. Dispose of contents/container in accordance with all applicable federal, state, and local regulations.

**Note:** Contaminated product, soil, water, container residues and spill cleanup materials may be hazardous wastes. Appropriate hazardous waste designation is the responsibility of the user.



**NV-80®**

Page: 7 of 8  
Date Prepared: March 15, 2015  
MSDS No.: 2840

**SECTION 14: TRANSPORT INFORMATION**

**ID No.:** UN3266  
**Proper Shipping Name:** CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S., (contains sodium silicate)  
**Hazard Class:** 8  
**Packing Group:** III  
**Label:** CORROSIVE  
**Marine Pollutant:** No  
**RQ:** No  
**Special Precautions:** none

**SECTION 15: REGULATORY INFORMATION**

**TSCA**  
The ingredients in this product are listed on the TSCA inventory.

**RCRA HAZARD CLASS**  
D002 - Corrosive hazardous waste

**SARA 311/312 REPORTABLE HAZARD CATEGORIES:** Immediate (Acute) Health Fire

**REPORTING REQUIREMENTS** (all quantities in pounds)

Component	CAS / 313 Code	Section 302 (EHS) TPQ	Section 304 EHS RQ	CERCLA RQ	Section 313	CAA 112(r) TQ	CWA / OPA
1-Butoxyethanol	N230 Glycol ethers			(1)	313		
(1) This material is not subject to any special reporting under the requirements of CERCLA. CERCLA petroleum exclusion applies for this product. Contact local authorities to determine if other reporting requirements apply.							

**NEW JERSEY RIGHT-TO-KNOW INFORMATION**

This product contains water (CAS# 7732-18-5), aromatic petroleum naphtha (CAS# 64741-67-9), potassium fatty acid soap (CAS# 61790-44-1), 1-butoxyethanol (CAS# 111-76-2), ethoxylated nonylphenol (CAS# 127087-87-0), and sodium silicate (CAS# 1344-09-8).

**CALIFORNIA PROPOSITION 65 INFORMATION**

This product does not contain any chemicals recognized by the state of California to cause cancer and/or birth defects or reproductive harm.

**SCAQMD INFORMATION**

Is there a photochemically reactive material present? Yes  
 What is the % by volume of photochemically reactive material? About 30  
 What is the VOC content? About 320 g/l  
 What is the vapor pressure of VOC's? Less than 1 mm Hg @ 20°C



**NV-80®**

Page: 8 of 8  
Date Prepared: March 15, 2015  
MSDS No.: 2840

---

**SECTION 16: OTHER INFORMATION**

---

**REVISION SUMMARY**

New GHS format

**SUPERSEDES ISSUE DATE**

October 5, 2010

**HAZARD RATING SYSTEMS:**

	<u>HMIS</u>	<u>NFPA</u>
HEALTH	2	2
FLAMMABILITY	1	1
REACTIVITY	0	0
	B	

**KEY**  
4 = Severe  
3 = Serious  
2 = Moderate  
1 = Slight  
0 = Minimal

FOR ADDITIONAL PRODUCT INFORMATION, CONTACT YOUR SALES ENGINEER  
FOR ADDITIONAL HEALTH/SAFETY INFORMATION, CALL 201-567-3000

THE INFORMATION PRESENTED HEREIN HAS BEEN COMPILED FROM SOURCES CONSIDERED TO BE DEPENDABLE AND ACCURATE TO THE BEST OF PENETONE'S KNOWLEDGE. THE INFORMATION RELATES TO THIS SPECIFIC MATERIAL. IT MAY NOT BE VALID FOR THIS MATERIAL IF USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY ONESELF AS TO THE SUITABILITY AND COMPLETENESS OF THIS INFORMATION FOR HIS OWN PARTICULAR USE.