

Penetone® Corporation, 700 Gotham Parkway, Carlstadt, NJ 07072

OLD SALT™

Page: 1 of 7

Date Prepared: September 14, 2016

MSDS No.: 6830

SECTION 1: IDENTIFICATION

Product name: OLD SALT

Recommended use: Cleaning, degreasing

Physcial Description: Clear amber liquid with pine odor

Generic Ingredients: Water, aliphatic hydrocarbons, surfactants, builders Manufacturer: **Business Contact:** Penetone Corporation **Customer Service**

700 Gotham Parkway 800-631-1652 x2602 or 2272

Carlstadt, NJ 07072 Product Safety

800-631-1652 x2211 or 2257 800-631-1652 or 201-567-3000

Emergency Phone Numbers: PENETONE 201-567-3000 CHEMTREC 800-424-9300

SECTION 2: HAZARDS IDENTIFICATION

GHS CLASSIFICATION:

Health: Aspiration hazard: 1

Skin corrosion: 1C Eye damage: 1

Physical: Specific target organ toxicity - single exposure: 3 Not classified

DANGER!

Causes Severe Skin Burns and Eye Damage. May Be Fatal If Swallowed and Enters Airways. May Cause Drowsiness or Dizziness.







Precautionary Statements:

Prevention:

Avoid breathing fumes or vapors. Do not breath mists if inhalable mists occur during use. Use only outdoors or in a well-ventilated area.

Wear protective gloves, eye protection, and face protection. Wash hands and exposed skin thoroughly after handling.

Response:

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center, doctor, emergency room, or 911.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. A mild soap may be used. Wash contaminated clothing before reuse.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center, doctor, emergency room or 911 if you feel unwell.

If swallowed: Rinse mouth. Do NOT induce vomiting. Immediately call a poison center, doctor, emergency room, or 911.

Storage:

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

Disposal:

Dispose of contents/container in accordance with local, regional, and national regulations (see Sections 13 and 15 of SDS for disposal and reporting requirements).

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Concentration Wt% (1)
Aliphatic petroleum naphtha	64742-47-8	40-60
Water	7732-18-5	25-40
Ethoxylated nonylphenol	127087-87-0	1-10
Potassium dodecylbenzene sulfonate	27177-77-1	1-10



Penetone® Corporation, 700 Gotham Parkway, Carlstadt, NJ 07072

OLD SALTTM Page: 2 of 7

Date Prepared: September 14, 2016

MSDS No.: 6830

 Pine oil
 8002-09-3
 1-10

 Potassium soap
 61790-44-1
 1-10

 Potassium silicate
 1312-67-1
 <1</td>

 Trisodium hydroxyethylethylene diamine triacetate
 139-89-9
 <1</td>

(1) Exact percentages being withheld under trade secret provision of OHSA HCS 1910.1200(i)

SECTION 4: FIRST-AID MEASURES

General Description of Symptoms & First-Aid Measures

Most likely work-place exposure routes will be skin contact or inhalation.

For *skin contact*, typically no immediate effects will be observed. Reddening, irritation, or a burning sensation could develop some time after exposure if product is not quickly washed off.

Inhalation exposure may produce varied effects depending on whether vapor or mist/spray is inhaled (see SECTION 8 for recommended workplace exposure limits). For vapor, typical symptoms would include headaches, dizziness, and drowsiness. In extreme cases, unconsciousness and other central nervous effects may occur. For mist/spray, typical symptoms could include coughing, sneezing, and a tingling or burning sensation in the nose, throat, and lungs.

Eyes

If in eyes: Rinse cautiously with water for several minutes. If contact lenses present, remove them if easy to do. Continue rinsing for several minutes. Immediately call a poison center, doctor, physician or other competent medical authority for medical advice. Penetone recommends that after any eye exposure and initial treatment a physician be seen immediately.

Ingestion

If swallowed: Rinse mouth. Immediately call a poison center, doctor, physician or other competent medical authority. Product presents an aspiration hazard. DO NOT INDUCE VOMITING.

Inhalation

If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center, doctor, physician or other competent medical authority for medical advice.

Skin

If on skin: Take off immediately all contaminated clothing. Rinse skin with water or shower. A mild soap may be used. Wash contaminated clothing before reuse. Immediately call a poison center, doctor, physician or other competent medical authority for medical advice. If skin irritation or rash occurs: Get medical advice or attention.

Special Treatment / Other

None

SECTION 5: FIRE FIGHTING MEASURES

Flammable Properties

Classification: not classified Flash Point: none to boil

Autoignition Temperature: not determined

Lower Flammable Limit: not determined Upper Flammable Limit: not determined

Specific Hazards

Contains combustible solvent. Although no flash point up to 200°F, combustible vapors may be given off above this temperature. The product is water based and water dilutable and will self extinguish with addition of water.



Penetone® Corporation, 700 Gotham Parkway, Carlstadt, NJ 07072

OLD SALT™

Page: 3 of 7

Date Prepared: September 14, 2016

MSDS No.: 6830

Extinguishing Media

Suitable: SMALL FIRE: Use dry chemical, carbon dioxide (CO₂), water spray or regular foam. LARGE FIRE: water spray, water fog, or foam.

Unsuitable: Do not use solid water stream as this may spread fire.

Protection & Precautions for Firefighters

Protective Equipment & Clothing: Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters protective clothing will only provide limited protection.

Fire Fighting Guidance: Cool containers with flooding quantities of water until well after fire is out. Move containers from fire area if you can do it safely. Dike fire control water for later disposal; do not scatter material. Containers can expand and explode under fire conditions due to vapor buildup. Always stay away from containers engulfed in fire.

Hazardous Combustion Products: Smoke, fumes, and oxides of carbon, nitrogen, and sulfur when taken to dryness.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Land Spill

Do not touch or walk through spilled material. Stop leak if you can do it safely. For large spills, dike and pump into properly labeled containers for reclamation or disposal. For small spill, soak up with absorbent material and place in properly labeled containers for disposal.

Water Spill

Product forms emulsion with water which may make cleanup difficult. Avoid agitation to minimize emulsion formation. This product has a pH >12 and will raise the pH of surface waters. If possible, remove product from water surface by skimming or with suitable absorbents. Put into properly labeled containers for reclamation or disposal. If allowed by local environmental regulatory agencies, you may use a suitable dispersant. Check with local environmental regulatory agencies for reporting requirements.

See SECTION 8 for EXPOSURE CONTROLS and PERSONAL PROTECTION.

SECTION 7: HANDLING & STORAGE

Handling

Do not handle near heat, sparks, or flame. Avoid contact with oxidizing agents. Use only with adequate ventilation/personal protection (SEE section 8). Avoid contact with eyes, skin and clothing. After handling, always wash hands thoroughly with soap and water. Avoid personal contact with any residue. Dispose of empty containers with care. Empty containers can contain flammable residue and explosive vapors. *Do not cut, weld, or reuse empty container.*

Storage

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Do not store near heat, sparks, open flame, or other ignition sources. Do not store near strong oxidizing agents. Do not store in direct sunlight. Avoid storing above 120°F (49°C).

SECTION 8: EXPOSURE CONTROLS and PERSONAL PROTECTION

Engineering Controls

Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits.



Penetone® Corporation, 700 Gotham Parkway, Carlstadt, NJ 07072

OLD SALT™

Page: 4 of 7

Date Prepared: September 14, 2016

MSDS No.: 6830

Personal Protection

<u>Inhalation</u> A respiratory protection program that meets OSHA's 29 CFR 1910.134 or ANSI Z88.2 requirements must be followed whenever workplace conditions warrant respirator use. Use of an organic vapor mask or respirator is recommended.

<u>Skin</u> Wear chemical resistant gloves such as: rubber, nitrile, neoprene, or latex when skin contact is possible. Protective clothing including gloves, apron, sleeves, boots, head and face protection should be worn depending on how the product is used. PPE should be cleaned thoroughly after each use.

<u>Eyes</u> Penetone recommends always wearing safety glasses as a minimum in any workplace. Conditions may warrant the use of chemical goggles and possibly a face shield. Consult your standard operating procedure or safety professional for advice. Use protective eye and face devices that comply with ANSI Z87.1-1987.

Additional Remarks

Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use.

Occupational Exposure Limits

Component Name	Source	Value	Type	Notation
Aliphatic petroleum naphtha	ACGIH	1200 mg/m ³	TWA	Appendix H
	NIOSH	350 mg/m ³	TWA	
		1800 mg/m ³	С	15 minutes
	OSHA Z1	500 ppm	TWA	

SECTION 9: PHYSICAL & CHEMICAL PROPERTIES

Appearance: clear amber liquid

Odor: pine

Odor Threshold: not determined

pH: 12-13

Melting Point / Freezing: about 30°F

Boiling Point / Boiling Point Range: about 212°F

Flash Point: none to 200°F TCC Evaporation Rate: equal to water Flammability: not applicable

Lower Flammable Limit: not determined Upper Flammable Limit: not determined Explosive Properties: not applicable

Vapor Pressure: equal to water, about 17 mm Hg @ 20°C

Relative Vapor Density: not determined

Relative Density: 0.90

Solubility (Water): forms emulsion

Partition Coefficient (K_{ow}): not determined Auto-ignition temperature: not determined Decomposition temperature: not determined Viscosity: 20 to 50 cp at room temperature



Penetone® Corporation, 700 Gotham Parkway, Carlstadt, NJ 07072

OLD SALT™

Page: 5 of 7

Date Prepared: September 14, 2016

MSDS No.: 6830

SECTION 10: STABILITY & REACTIVITY

Reactivity

Not reactive.

Chemical Stability

Stable.

Hazardous Reactions

None known.

Conditions to Avoid

Contains combustible liquid. Do not store near sources of heat, sparks, open flame, or other ignition sources.

Incompatible Materials

Strong oxidizing agents. Strong acids

Hazardous Decomposition Products

Smoke, fumes, and oxides of carbon, nitrogen, and sulfur when taken to dryness.

SECTION 11: TOXICOLOGICAL INFORMATION

Product Summary

Product is corrosive to skin, eyes, and other tissue. Mists can be corrosive to the eyes and respiratory tract. Vapor concentrations above recommended exposure levels may cause headaches, dizziness, drowsiness, unconsciousness and other central nervous system effects.

Acute Toxicity:

Dermal: Rabbits, LD50 > 2,500 mg/kg (estimated using additivity formula)

Inhalation: no data available

Oral: Rats, LD50 >4,000 mg/kg (estimated using additivity formula)

Skin Corrosion/Irritation

No data available. Based upon tests of a similar product, product is considered corrosive to the skin.

Serious Eye Damage/Irritation

No data available. Based upon component data, product is considered corrosive to the eyes.

Sensitization - Respiratory or Skin

No data available. Based upon component data, product not expected to be a skin sensitizer.

Germ Cell Mutagenicity

No data available. Based upon component data, product not expected to exhibit germ cell mutagenicity.

Carcinogenicity

Reproductive Toxicicty

No data available.

The nonionic surfactant used in this product has produced effects in the fetus only at levels that were toxic to the parent animals.

Specific Target Organ Effects - Single Exposure

No data available



Penetone® Corporation, 700 Gotham Parkway, Carlstadt, NJ 07072

OLD SALT™

Page: 6 of 7

Date Prepared: September 14, 2016

MSDS No.: 6830

Specific Target Organ Effects - Repeated or Prolonged Exposure

No data available.

The nonionic surfactant used in this product exhibited kidney and liver effects in lab animals at high feeding levels over extended periods of time.

Aspiration Hazard

Based upon available data and comparison to similar materials, if swallowed, may pose a lung aspiration hazard during vomiting. Lung aspiration may result in chemical pneumonitis, pulmonary edema, and damage to lung tissue or death.

SECTION 12: ECOLOGICAL INFORMATION

Product Summary

Based upon product component information, product can be considered mildly toxic to aquatic organisms with LC50s generally in the range of 10-50 mg/l. (Acute aquatic toxicity category 2 by European Union classification).

Ecotoxicity

LC/EC/IC 10-50 mg/l (estimated using additivity formula)

Persistence and Degradability

Product components range in biodegradability from not readily to readily biodegradable. Similar products have had biodegradabilities greater than 80% by DOC (EPA 796.3100).

Bioaccumulative Potential

Product not expected to bioaccumulate due to its degradability.

Mobility in soil

Product is a complex mixture. Components will partition into water and soil phases depending on inherent solubility of component in water.

Other Adverse Effects

None known

SECTION 13: DISPOSAL CONSIDERATIONS

Product is a D002 Corrosive Hazardous Waste under RCRA definitions. Dispose of contents/container in accordance with all applicable federal, state, and local regulations.

<u>Note:</u> Contaminated product, soil, water, container residues and spill cleanup materials may be hazardous wastes. Appropriate hazardous waste designation is the responsibility of the user.

SECTION 14: TRANSPORT INFORMATION

ID No.: UN3266

Proper Shipping Name: CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S., (contains potassium silicate)

Hazard Class: 8
Packing Group: |||

Label: CORROSIVE

Marine Pollutant: No RQ: No Special Precautions: none



Penetone® Corporation, 700 Gotham Parkway, Carlstadt, NJ 07072

OLD SALT™

Page: 7 of 7

Date Prepared: September 14, 2016

MSDS No.: 6830

SECTION 15: REGULATORY INFORMATION

TSCA

The ingredients in this product are listed on the TSCA inventory.

RCRA HAZARD CLASS

D002 - Corrosive hazardous waste

SARA 311/312 REPORTABLE HAZARD CATEGORIES: Immediate (Acute) Health

REPORTING REQUIREMENTS (all quantities in pounds)

Component	CAS / 313 Code	Section 302 (EHS) TPQ	Section 304 EHS RQ	CERCLA RQ	Section 313	CAA 112(r) TQ	CWA / OPA
no components subject to reporting							

NEW JERSEY RIGHT-TO-KNOW INFORMATION

This product contains aliphatic petroleum naphtha (CAS 64742-47-8), water (CAS 7732-18-5), ethoxylated nonylphenol (CAS 127087-87-0), potassium dodecylbenzene sulfonate (CAS 27177-77-1), and pine oil (CAS 8002-09-3).

CALIFORNIA PROPOSITION 65 INFORMATION

This product does not contain any chemicals recognized by the state of California to cause cancer and/or birth defects or reproductive harm.

SCAQMD INFORMATION

Is there a photochemically reactive material present? No What is the % by volume of photochemically reactive material? 0 What is the VOC content? 450 g/l What is the vapor pressure of VOC's? 0.03 mm Hg @ 20°C

SECTION 16: OTHER INFORMATION

REVISION SUMMARY New GHS format			SUPERSEDES ISSUE DATE February 27, 2004
HAZARD RATING SYSTEM HEALTH FLAMMABILITY REACTIVITY	MS: HMIS 2 1 0 B	NFPA 2 1 0	KEY 4 = Severe 3 = Serious 2 = Moderate 1 = Slight
			0 = Minimal

FOR ADDITIONAL PRODUCT INFORMATION, CONTACT YOUR SALES ENGINEER FOR ADDITIONAL HEALTH/SAFETY INFORMATION, CALL 201-567-3000

THE INFORMATION PRESENTED HEREIN HAS BEEN COMPILED FROM SOURCES CONSIDERED TO BE DEPENDABLE AND ACCURATE TO THE BEST OF PENETONE'S KNOWLEDGE. THE INFORMATION RELATES TO THIS SPECIFIC MATERIAL. IT MAY NOT BE VALID FOR THIS MATERIAL IF USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY ONESELF AS TO THE SUITABILITY AND COMPLETENESS OF THIS INFORMATION FOR HIS OWN PARTICULAR USE.