

GENERAL USE



Brawn is a thickened liquid product, formulated to strip paint, remove graffiti and clean heavy cooked on carbon and cooking greases from fryers, cooking utensils, fryer hoods, grease traps and waste receptacles.

Brawn is thickened and will stay where it is applied, being highly effective on vertical surfaces.

Brawn is USDA listed under category A1 (general cleaning compounds for all surfaces).

Brawn is also an effective organic coating stripper.

FEATURES AND BENEFITS

- Thickened to cling on surfaces
- Minimal scrubbing
- Less product usage
- Easily rinses
- Highly effective
- Stays where applied to stop re-application
- Labor cost saving
- Reduces chemical cost

DIRECTIONS FOR USE

Use procedures

Food Industry

Before using **Brawn**, food products and packaging materials must be removed from the room or carefully protected from contamination. **Brawn** can be applied by brushing, roll coating, flooding, or by coarse spray onto the surface to be cleaned. Allow **Brawn** to dwell from five minutes to overnight. Brushing will accelerate the cleaning process and re-application may be necessary for thick deposits. All surfaces must be thoroughly rinsed with potable water.

Coating Removal

Test coating to assure **Brawn** is effective. **Brawn** will remove many, but not all coating. Apply to surface by brush, roller, or coarse spray. Allow to dwell until coating is loosened, brush to accelerate removal and water rinse.

Metal Safety

Brawn should not be used on soft metals such as aluminum, tin, galvanized or zinc. When used as directed, **Brawn** is safe for use on brass, bronze, chromium, copper, iron, steel and stainless steel.

BRAWN

HEAVY-DUTY DECARBONIZER, STRIPPER AND GRAFFITI REMOVER

PHYSICAL PROPERTIES

Appearance	Viscous brown/amber liquid
Odor	Mild solvent
pH	>13
Freezing Point	About 25°F
Boiling Point	About 220°F
Flash Point (TCC)	Above 200°F
Relative Density	1.24
Auto-Ignition Temperature	Not determined
Water Solubility	Complete
Viscosity	About 30 poise

INCOMPATIBILITY

Strong acids. Soft metals or alloys.

WAREHOUSING PRECAUTIONS

Store locked up. Store in corrosive resistant container. Plastic is recommended. Keep container tightly closed when not in use.

Do not store in direct sunlight.
Avoid storing above 120°F (49°C).

APPROVALS

USDA A1

AVAILABLE SIZES

4 X 1 gallon Case

5 gallon Pail

55 gallon Drum

FIRST AID MEASURES

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center, doctor, physician or other competent medical authority for medical advice. Penetone recommends that after any eye exposure a physician be seen immediately.

If swallowed: Rinse mouth. DO NOT INDUCE VOMITING. Immediately call a poison center, doctor, physician or other competent medical authority for medical advice.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a local Poison Control

Center, physician, or other competent medical authority for medical advice.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. A mild soap may be used to wash skin. Wash contaminated clothing before reuse. Immediately call a local Poison Control Center, doctor, physician or other competent medical authority for medical advice.

PERSONAL PROTECTION Security equipment



WHMIS



IMPORTANT: Before using **BRAWN**, always be sure to read and follow precautions and directions for use appearing on the product container label and on the safety data sheet (S.D.S).



CARLSTADT

700 Gotham Parkway
Carlstadt, NJ 07072
Tel.: 201-567-3000
Toll free: 1-800-631-1652

MONTREAL

10,900 Secant Street
Anjou, QC H1J 1S5
Tel.: 514-355-4660
Toll free: 1-800-361-8927

EDMONTON

11411-160 Street
Edmonton, Alberta T5M 3T7
Tel.: 780-454-3919
Toll free: 1-866-454-3919

United States
www.penetone.com

Canada
www.westpenetone.com