

DEWAXIT

LOW FOAM, AMMONIA FREE, FLOOR WAX STRIPPER

GENERAL USE



Dewaxit is a low foam, heavy duty, non-ammoniated floor stripper that removes old wax films and metal cross-linked polymeric finishes from floor surfaces.

Dewaxit will not harm floor surfaces such as asphalt, rubber, linoleum or vinyl when used as directed.

Dewaxit is also an excellent daily maintenance cleaner for floors, walls, shelves, woodwork, and is an outstanding product for ultra-sonic cleaning.

FEATURES AND BENEFITS

- Highly concentrated
- Excellent detergency
- Safe on most floors
- Powerful and fast stripping
- Low foam
- Low chemical consumption
- Also cleans walls, woodworkand floors
- Minimum labor required
- Effective in automated floor scrubbers

DIRECTIONS FOR USE

Use procedure

Apply solution to the floor to be treated.

Concentration

For Light to Medium Duty Floor Stripping:

Mix 1 part **Dewaxit** to 16 parts warm water for stripping no-metal complexed finished.

Mix 1 part **Dewaxit** to 8 parts warm water for stripping metal-complexed finished.

For Heavy-Duty Stripping:

Dilute 1 part **Dewaxit** to 4 parts water and follow procedures outlined above.

For Automatic Stripping:

Mix 1 part **Dewaxit** to 16 parts of hot water for stripping non-metal complexed finished.

Mix 1 part **Dewaxit** to 8 parts of hot water for stripping metal complexed finished.

Dwell time / Operation time

5 to 10 minutes.

Mechanical action

Use stiff brush or floor machine to agitate the loosened wax. Pick up lifted, loosened wax with a mop or preferably a wet vacuum.

Rinsing

Rinse the floor thoroughly with clear water. Although one rinsing normally suffices, type, coarse spray approximately one gallon of solution over each 100 square feet two rinses are recommended to ensure removal of all old waxes and soil before polishing applications.

DEWAXIT

LOW FOAM, AMMONIA FREE, FLOOR WAX STRIPPER

PHYSICAL PROPERTIES

Annogranco	Clear blue liquid
Appearance	Clear blue liquid
Odor	Mild amine
рН	>12.5
Freezing Point	About 32°F
Boiling Point	About 212°F
Flash Point (TCC)	Not applicable
Relative Density	1.08
Auto-Ignition Temperature	Not applicable
Water Solubility	Soluble
Viscosity	Less than 5 CP at room temperature

INCOMPATIBILITY

Strong acids.

WAREHOUSING PRECAUTIONS

Store locked up. Keep container tightly closed when not in use. Do not store near strong acids. Do not store in direct sunlight. Avoid storing above 120°F (49°C).

AVAILABLE SIZES

5 gallon Pail

55 gallon Drum

FIRST AID MEASURES

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing, Immediately call a local Poison Control Center, doctor, physician or other competent medical authority for medical advice. Penetone recommends that after any eye exposure a physician be seen immediately. If swallowed: Rinse mouth. DO NOT INDUCE VOMITING. Immediately call a poison center, doctor, physician or other competent medical authority for medical advice.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a local Poison Control Center, physician, or other competent medical authority for medical advice.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. A mild soap may be used to wash skin. Wash contaminated clothing before reuse. Immediately call a local Poison Control Center, doctor, physician or other competent medical authority for medical advice.

IMPORTANT: Before using DEWAXIT, always be sure to read and follow precautions and directions for use appearing on the product container label and on the safety data sheet (S.D.S).

PERSONAL PROTECTION Security equipment WHMIS



CLIFTON

125 Kingsland Avenue Clifton, NI 07014 Tel.: 201-567-3000 Toll free: 1-800-631-1652 Toll free: 1-800-361-8927

MONTREAL

10,900 Secant Street Anjou, QC H1J 1S5 Tel.: 514-355-4660

FDMONTON

11411-160 Street Edmonton, Alberta T5M 3T7 Tel.: 780-454-3919 Toll free: 1-866-454-3919

United States www.penetone.com

www.westpenetone.com