

GENERAL USE



Dewaxit is a low foam, heavy duty, non-ammoniated floor stripper that removes old wax films and metal cross-linked polymeric finishes from floor surfaces.

Dewaxit will not harm floor surfaces such as asphalt, rubber, linoleum or vinyl when used as directed.

Dewaxit is also an excellent daily maintenance cleaner for floors, walls, shelves, woodwork, and is an outstanding product for ultra-sonic cleaning.

FEATURES AND BENEFITS

- Highly concentrated
- Excellent detergency
- Safe on most floors
- Powerful and fast stripping
- Low foam
- Low chemical consumption
- Also cleans walls, woodwork and floors
- Minimum labor required
- Effective in automated floor scrubbers

DIRECTIONS FOR USE

Use procedure	Apply solution to the floor to be treated.
Concentration	<p>For Light to Medium Duty Floor Stripping: Mix 1 part Dewaxit to 16 parts warm water for stripping no-metal complexed finished. Mix 1 part Dewaxit to 8 parts warm water for stripping metal-complexed finished.</p> <p>For Heavy-Duty Stripping: Dilute 1 part Dewaxit to 4 parts water and follow procedures outlined above.</p> <p>For Automatic Stripping: Mix 1 part Dewaxit to 16 parts of hot water for stripping non-metal complexed finished. Mix 1 part Dewaxit to 8 parts of hot water for stripping metal complexed finished.</p>
Dwell time / Operation time	5 to 10 minutes.
Mechanical action	Use stiff brush or floor machine to agitate the loosened wax. Pick up lifted, loosened wax with a mop or preferably a wet vacuum.
Rinsing	Rinse the floor thoroughly with clear water. Although one rinsing normally suffices, type, coarse spray approximately one gallon of solution over each 100 square feet two rinses are recommended to ensure removal of all old waxes and soil before polishing applications.

DEWAXIT

LOW FOAM, AMMONIA FREE, FLOOR WAX STRIPPER

PHYSICAL PROPERTIES

Appearance	Clear blue liquid
Odor	Mild amine
pH	>12.5
Freezing Point	About 32°F
Boiling Point	About 212°F
Flash Point (TCC)	Not applicable
Relative Density	1.08
Auto-Ignition Temperature	Not applicable
Water Solubility	Soluble
Viscosity	Less than 5 CP at room temperature

INCOMPATIBILITY

Strong acids.

WAREHOUSING PRECAUTIONS

Store locked up. Keep container tightly closed when not in use.
Do not store near strong acids.
Do not store in direct sunlight.
Avoid storing above 120°F (49°C).

AVAILABLE SIZES

5 gallon Pail

55 gallon Drum

FIRST AID MEASURES

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a local Poison Control Center, doctor, physician or other competent medical authority for medical advice. Penetone recommends that after any eye exposure a physician be seen immediately.

If swallowed: Rinse mouth. DO NOT INDUCE VOMITING. Immediately call a poison center, doctor, physician or other competent medical authority for medical advice.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a local Poison Control Center, physician, or other competent medical authority for medical advice.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. A mild soap may be used to wash skin. Wash contaminated clothing before reuse. Immediately call a local Poison Control Center, doctor, physician or other competent medical authority for medical advice.

PERSONAL PROTECTION Security equipment



WHMIS



IMPORTANT: Before using **DEWAXIT**, always be sure to read and follow precautions and directions for use appearing on the product container label and on the safety data sheet (S.D.S).



CARLSTADT

700 Gotham Parkway
Carlstadt, NJ 07072
Tel.: 201-567-3000
Toll free: 1-800-631-1652

MONTREAL

10,900 Secant Street
Anjou, QC H1J 1S5
Tel.: 514-355-4660
Toll free : 1-800-361-8927

EDMONTON

11411-160 Street
Edmonton, Alberta T5M 3T7
Tel.: 780-454-3919
Toll free: 1-866-454-3919

United States
www.penetone.com

Canada
www.westpenetone.com