

GENERAL USE



Navitone is a unique cleaning product containing solvents, detergents and emulsifiers, and is formulated for use in the heaviest cleaning applications.

Navitone should be used in industrial environments such as steel mills, paper mills, asphalt application, refineries and power plants to effectively remove greases, tars and resins from production equipment, floors, castings, cellars and tools.

FEATURES AND BENEFITS

- Safe on all metals
- Heat not required
- Removes the heaviest deposits
- Works fast
- Water rinsable
- Increased viscosity
- No flash point to boiling (212°F)
- Saves energy
- Reduces labor in cleaning
- Clings to vertical surfaces

DIRECTIONS FOR USE

Use procedures

Manual operations

Dilute concentrate with water at 1:4 to 1:10. Wipe on, wipe off. Wear neoprene gloves.

Pressure spray

Dilute concentrate with water at 1:20. Use a coarse spray at long distance. Do not fine mist this product.

Tank immersion

Mix concentrate with water at 1:4 to 1:10 depending on the degree of soil to be removed.

*For extremely heavily soiled surfaces, use **Navitone** concentrated or diluted 1:1 with mineral spirits. When applied concentrated or mixed 1:1, the product is somewhat viscous and is ideally suited for cleaning upright surfaces. **Navitone** will cling to the surface until rinsed off.*

Note

The product may attack certain flooring and plastics; pre-test on these surfaces before using.

NAVITONE

LOW ODOR SOLVENT EMULSION DEGREASER

PHYSICAL PROPERTIES

Appearance	Clear amber liquid
Odor	Aromatic
pH	12
Freezing Point	About 30°F
Boiling Point	About 212°F
Flash Point (TCC)	None to boil
Relative Density	1.00
Auto-Ignition Temperature	Not determined
Water Solubility	Emulsifies
Viscosity	10 to 30 CP at room temperature

INCOMPATIBILITY

Strong oxidizing agents. Strong acids.

WAREHOUSING PRECAUTIONS

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Do not store near heat, sparks, open flame, or other ignition sources. Do not store in direct sunlight. Avoid storing above 12°F (49°C).

AVAILABLE SIZES

5 gallon Pail

55 gallon Drum

FIRST AID MEASURES

If in eyes: Rinse cautiously with water for several minutes. If contact lenses present, remove them if easy to do. Continue rinsing for several minutes. Immediately call a poison center, doctor, physician or other competent medical authority for medical advice. Penetone recommends that after any eye exposure and initial treatment a physician be seen immediately.

If swallowed: Rinse mouth. Immediately call a poison center, doctor, physician or other competent medical authority. Product presents an aspiration hazard. **DO NOT INDUCE VOMITING.**

If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center, doctor, physician or other competent medical authority for medical advice.

If on skin: Take off immediately all contaminated clothing. Rinse skin with water or shower. A mild soap may be used. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice or attention.

PERSONAL PROTECTION Security equipment



WHMIS



IMPORTANT: Before using **NAVITONE**, always be sure to read and follow precautions and directions for use appearing on the product container label and on the safety data sheet (S.D.S).



CARLSTADT

700 Gotham Parkway
Carlstadt, NJ 07072
Tel.: 201-567-3000
Toll free: 1-800-631-1652

MONTREAL

10,900 Secant Street
Anjou, QC H1J 1S5
Tel.: 514-355-4660
Toll free : 1-800-361-8927

EDMONTON

11411-160 Street
Edmonton, Alberta T5M 3T7
Tel.: 780-454-3919
Toll free: 1-866-454-3919

United States
www.penetone.com

Canada
www.westpenetone.com