

TRANSPORTATION INDUSTRY



Penmul L745 is an asphalt cleaner containing solvents and naturally derived ingredients that gives performance equivalent to or better than diesel fuel. This product is water rinsable and water dilutable. **Penmul L745** is non hazardous, and has a pleasant odor.

FEATURES AND BENEFITS

- No chlorinated solvents
- Water rinsable and dilutable
- High flash point
- Non hazardous
- Pleasant odor
- Safer for user
- User friendly

Use procedures

Penmul L745 can be applied by brush or coarse spray, in a dip tank operation, or in a parts washing machine. When used in a dip tank, agitation should be provided for best results.

Concentration

Penmul L745 may be used concentrated or diluted with water.

Automotive Use

Spray or brush on the undergear of trucks, buses, tractors, road building equipment for removing asphalt, tar and pitch. Allow to set for a few minutes, then hose or wipe off.

Parts Washing

Soak until oils and grease are removed. Rinse with water.

Note

This product may craze or soften certain plastics and may affect certain paints. Pretest on part to be cleaned before use.

PENMUL L745

HIGH POWERED DEGREASER, ASPHALT REMOVER

PHYSICAL PROPERTIES

Appearance	Clear to pale amber liquid
Odor	Mild citrus
pH	not applicable, 7-9 for 10% dilution
Freezing Point	Not determined, pour point about -34°C
Boiling Point	Initial 212°F
Flash Point	145°F TCC
Relative Density	0.80
Auto-Ignition Temperature	Not determined
Water Solubility	Emulsifies
Viscosity	Less than 5 CP at room temperature

INCOMPATIBILITY

Strong oxidizing agents.

WAREHOUSING PRECAUTIONS

Store in a well-ventilated place. Keep container tightly closed. Open slowly in order to control possible pressure release. Keep cool. Store locked up. Do not store near heat, sparks, open flame, or other ignition sources. Do not store in direct sunlight. Avoid storing above 120°F (49°C).

APPROVALS

North Carolina DOT approved

AVAILABLE SIZES

5 gallon Pail

55 gallon Drum

FIRST AID MEASURES

If in eyes: Rinse cautiously with water for several minutes. If contact lenses present, remove them if easy to do. Continue rinsing for several minutes. If eye irritation persists: Get medical advice or attention. Penetone recommends that after any eye exposure and initial treatment a physician be seen immediately.

If swallowed: Immediately call a poison center, doctor, physician or other competent medical authority. Product presents an aspiration hazard. **DO NOT INDUCE VOMITING.**

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center, doctor, physician or other competent medical authority if you feel unwell.

If on skin (or hair): Wash with plenty of water or a mild soap. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice or attention.

PERSONAL PROTECTION Security equipment



WHMIS



IMPORTANT: Before using **PENMUL L745**, always be sure to read and follow precautions and directions for use appearing on the product container label and on the safety data sheet (S.D.S).



CLIFTON

125 Kingsland Avenue
Clifton, NJ 07014
Tel.: 201-567-3000
Toll free: 1-800-631-1652

MONTREAL

10,900 Secant Street
Anjou, QC H1J 1S5
Tel.: 514-355-4660
Toll free: 1-800-361-8927

EDMONTON

11411-160 Street
Edmonton, Alberta T5M 3T7
Tel.: 780-454-3919
Toll free: 1-866-454-3919

United States

www.penetone.com

Canada

www.westpenetone.com