

GENERAL USE



Penmul R950 is a mixture of solvent and emulsifiers intended for use in difficult industrial cleaning applications. **Penmul R950** is especially effective in loosening and dissolving asphaltic and heavy petroleum based soils and sludge accumulations.

Penmul R950 is typically used to clean and desludge oil storage tanks, engine blocks and where asphalt is mixed, applied or pumped.

Penmul R950 has a flashpoint above 140°F, rendering it non-hazardous for disposal.

FEATURES AND BENEFITS

- Water rinseable
- Effective at room temperature
- Effective on asphaltic deposits
- Safe on all metals
- Works fast
- Free of chlorinates
- Safer than flammable products
- Versatile and multipurpose
- No heat required
- Increased productivity

DIRECTIONS FOR USE

Use procedures

Penmul R950 can be applied by brush or coarse spray, in a tank operation, or in a parts washing machine. When used in a tank, agitation should be provided for best results.

Penmul R950 may be used concentrated or diluted with water, mineral spirits, kerosene or fuel oil.

Application & Procedure Using Penmul R950 Concentrated:

Automotive

Spray or brush on the undergear of trucks, buses, tractors, and road building equipment for removing asphalt, tar and pitch. Allow to set for a few minutes, then hose or wipe off.

Parts Washing

Soak until oils and grease are removed. Rinse with water or mineral spirits.

Note

Penmul R950 may attack asphaltic flooring and some plastics. Pre-test on these surfaces before using. Do not use on painted surfaces.

PENMUL R950

HEAVY DUTY SOLVENT EMULSION DEGREASER

PHYSICAL PROPERTIES

Appearance	Clear liquid
Odor	Aromatic
pH	Not applicable
Freezing Point	Less than 20°F
Boiling Point	350-410°F
Flash Point	150°F TCC
Relative Density	0.90
Auto-Ignition Temperature	Not determined
Water Solubility	Emulsifies
Viscosity	Less than 5 CP at room temperature

INCOMPATIBILITY

Strong oxidizing agents.

WAREHOUSING PRECAUTIONS

Store in a well-ventilated place. Keep container tightly closed. Open slowly in order to control possible pressure release. Keep cool. Store locked up. Do not store near heat, sparks, open flame, or other ignition sources. Do not store in direct sunlight. Avoid storing above 120°F (49°C).

AVAILABLE SIZES

5 gallon Pail

55 gallon Drum

FIRST AID MEASURES

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists or develops: Get medical advice or attention. Penetone recommends that after any eye exposure a physician be seen immediately.

If swallowed: Immediately call a poison center, doctor, physician or other competent medical authority. Rinse mouth. Product presents an aspiration hazard. DO NOT INDUCE VOMITING.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center, doctor, physician or other competent medical authority if you feel unwell.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. A mild soap may be used to wash skin. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice or attention.

PERSONAL PROTECTION Security equipment



WHMIS



IMPORTANT: Before using **PENMUL R950**, always be sure to read and follow precautions and directions for use appearing on the product container label and on the safety data sheet (S.D.S).



CARLSTADT

700 Gotham Parkway
Carlstadt, NJ 07072
Tel.: 201-567-3000
Toll free: 1-800-631-1652

MONTREAL

10,900 Secant Street
Anjou, QC H1J 1S5
Tel.: 514-355-4660
Toll free: 1-800-361-8927

EDMONTON

11411-160 Street
Edmonton, Alberta T5M 3T7
Tel.: 780-454-3919
Toll free: 1-866-454-3919

United States
www.penetone.com

Canada
www.westpenetone.com