

GENERAL USE



Powermate is an economical, effective liquid detergent specially formulated to meet the exacting standards of industrial use. Greases, oils, dry oil films and caked-on soils are quickly removed with a water diluted solution of **Powermate**. Rinse with clear water and the surface dries without streaking or hazing.

Powermate is excellent for cleaning motor housings, forklifts, conveyor rollers, stands, cranes, hoists, pump cellars and other areas.

FEATURES AND BENEFITS

- Biodegradable
- No hazardous SARA TITLE III Section 313 reportables
- Versatile
- Economical
- No fire or flash point
- Free Rinsing
- Cost effective
- Reduces hazardous reporting
- Leaves no film or residue after rinsing

DIRECTIONS FOR USE

Use procedures

Floors 2 oz. per gallon of water applied by mop and rinsed with clear water.

Oil Soaked Floors 6 oz. per gallon of water applied hot with a mop or sprayer. Allow several minutes dwell time. Scrub with a brush or floor scrubbing machine. Rinse with clean water.

Machinery & Equipment 5 oz. per gallon of water applied with a cloth or spray. Allow several minutes dwell time. Wipe with a clean damp cloth or spray rinse with clean water.

Painted surfaces, walls, brick, tile, cement 4-8 oz. per gallon of water, depending on severity of soil, applied with a cloth, brush or spray. Always start at the bottom and work up. On cement and brick walls, **Powermate** may be used through steam equipment or pressure washer with instant success. Rinse with clear water or wipe with a damp clean cloth.

POWERMATE

LIQUID CLEANING COMPOUND

PHYSICAL PROPERTIES

Appearance	Pale green liquid
Odor	Mild
pH	12.5-13
Freezing Point	About 32°F
Boiling Point	About 212°F
Flash Point (TCC)	Not applicable
Relative Density	1.07
Auto-Ignition Temperature	Not applicable
Water Solubility	Complete
Viscosity	Less than 5 CP at room temperature

INCOMPATIBILITY

Strong acids.

WAREHOUSING PRECAUTIONS

Store locked up. Keep container tightly closed when not in use.
Do not store in direct sunlight.
Avoid storing above 120°F (49°C).

AVAILABLE SIZES

5 gallon Pail

55 gallon Drum

FIRST AID MEASURES

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a local Poison Control Center, doctor, physician or other competent medical authority for medical advice. Penetone recommends that after any eye exposure a physician be seen immediately.

If swallowed: Rinse mouth. DO NOT INDUCE VOMITING. Immediately call a poison center, doctor, physician or other competent medical authority for medical advice.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a local Poison Control Center, physician, or other competent medical authority for medical advice.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. A mild soap may be used to wash skin. Wash contaminated clothing before reuse. Immediately call a local Poison Control Center, doctor, physician or other competent medical authority for medical advice.

PERSONAL PROTECTION Security equipment



WHMIS



IMPORTANT: Before using **POWERMATE**, always be sure to read and follow precautions and directions for use appearing on the product container label and on the safety data sheet (S.D.S).



CLIFTON

125 Kingsland Avenue
Clifton, NJ 07014
Tel.: 201-567-3000
Toll free: 1-800-631-1652

MONTREAL

10,900 Secant Street
Anjou, QC H1J 1S5
Tel.: 514-355-4660
Toll free: 1-800-361-8927

EDMONTON

11411-160 Street
Edmonton, Alberta T5M 3T7
Tel.: 780-454-3919
Toll free: 1-866-454-3919

United States
www.penetone.com

Canada
www.westpenetone.com