

Penetone® Corporation, 125 Kingsland Ave., Clifton, NJ 07014

PRESSHELPER #7HF

Page: 1 of 8

Date Prepared: September 25, 2019

SDS No.: 4755

SECTION 1: IDENTIFICATION

Product name: PRESSHELPER #7HF

Recommended use: Ink, resin, and coating cleaner

Physcial Description: Clear water white liquid with mild citrus odor

Generic Ingredients: Hydrocarbon solvents, glycol ether, surfactant, d-limonene **Manufacturer:**Business Contact:

Penetone Corporation

Customer Service

125 Kingsland Ave. 800-631-1652 x2602 or 2272

Clifton, NJ 07014 Product Safety

800-631-1652 or 201-567-3000 800-631-1652 x2211 or 2257

Emergency Phone Numbers: PENETONE 201-567-3000 CHEMTREC 800-424-9300

SECTION 2: HAZARDS IDENTIFICATION

GHS CLASSIFICATION:

Health:

Eye irritation: 2A

Skin irritation: 2

Specific target organ toxicity - single exposure: 3

Skin sensitization: 1

Physical:

Aspiration hazard: 1 Flammable liquid: 4

DANGER!

May Be Fatal If Swallowed and Enters Airways. Causes Eye and Skin Irritation. May Cause an Allergic Skin Reaction. May Cause Drowsiness or Dizziness.

Combustible Liquid.





Precautionary Statements:

Prevention:

Keep away from flames and hot surfaces.--No smoking.

Wear protective gloves, eye protection, and face protection. Wash hands and exposed skin thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

Avoid breathing fumes, vapors or mists if inhalable mists occur during use. Use only outdoors or in a well-ventilated area.

Response:

In case of fire: Use dry chemical, carbon dioxide, water spray, water fog, or foam. Do not use solid water stream as this may spread the fire.

If swallowed: Immediately call a poison center, doctor, emergency room, or 911. Do NOT induce vomiting.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. A mild soap may be used. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center, doctor, emergency room or 911 if you feel unwell.

Storage.

Store locked up. Store in a well ventilated place. Keep container tightly closed. Keep cool.

Disposal:

Dispose of contents/container in accordance with local, regional, and national regulations (see Sections 13 and 15 of SDS for disposal and reporting requirements).



Penetone® Corporation, 125 Kingsland Ave., Clifton, NJ 07014

PRESSHELPER #7HF

Page: 2 of 8

Date Prepared: September 25, 2019

SDS No.: 4755

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Concentration Wt% (1)
Aliphatic petroleum naphtha	64742-47-8	75-90
Dipropylene glycol methyl ether	34590-94-8	10-25
d-Limonene	5989-27-5	1-10
Ethoxylated nonylphenol	127087-87-0	1-10

⁽¹⁾ Exact percentages being withheld under trade secret provision of OHSA HCS 1910.1200(i)

SECTION 4: FIRST-AID MEASURES

General Description of Symptoms & First-Aid Measures

Most likely work-place exposure routes will be skin contact or inhalation.

For *skin contact*, typically no immediate effects will be observed. Slight reddening or minor irritation could develop some time after exposure if product is not quickly washed off. For sensitive individuals, a rash may appear.

Inhalation exposure may produce varied effects, particularly if exposure occurs above the recommended workplace exposure limits (see SECTION 8). Typical symptoms would include headaches, dizziness, and drowsiness. In extreme cases, unconsciousness and other central nervous effects may occur.

Eyes

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists or develops: Get medical advice or attention. Penetone recommends that after any eye exposure a physician be seen immediately.

Ingestion

If swallowed: Immediately call a poison center, doctor, physician or other competent medical authority. Rinse mouth. Product presents an aspiration hazard. DO NOT INDUCE VOMITING.

Inhalation

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center, doctor, physician or other competent medical authority if you feel unwell.

Skir

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. A mild soap may be used to wash skin. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice or attention.

Special Treatment / Other

None.

SECTION 5: FIRE FIGHTING MEASURES

Flammable Properties

Classification: 4
Flash Point: 168°F TCC

Autoignition Temperature: not determined

Lower Flammable Limit: not determined Upper Flammable Limit: not determined

Specific Hazards

Combustible liquid. Can form flammable mixtures at or above the flash point.



Penetone® Corporation, 125 Kingsland Ave., Clifton, NJ 07014

PRESSHELPER #7HF

Page: 3 of 8

Date Prepared: September 25, 2019

SDS No.: 4755

Extinguishing Media

Suitable: SMALL FIRE: Use dry chemical, carbon dioxide (CO₂), water spray or regular foam. LARGE FIRE: water spray, water fog, or foam.

Unsuitable: Do not use solid water stream as this may spread fire.

Protection & Precautions for Firefighters

Protective Equipment & Clothing: Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters protective clothing will only provide limited protection.

Fire Fighting Guidance: Cool containers with flooding quantities of water until well after fire is out. Move containers from fire area if you can do it safely. Dike fire control water for later disposal; do not scatter material. Containers can expand and explode under fire conditions due to vapor buildup. Always stay away from containers engulfed in fire.

Hazardous Combustion Products: Smoke, fumes, and oxides of carbon.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Land Spill

Eliminate sources of ignition. Do not touch or walk through spilled material. Stop leak if you can do it safely. For large spills, dike and pump into properly labeled containers for reclamation or disposal. For small spill, soak up with absorbent material and place in properly labeled containers for disposal.

Water Spill

Product is a hydrocarbon, lighter than water, and forms weak emulsion with water. Product will float. Avoid agitation to minimize emulsion formation. Remove product from water surface by skimming or with suitable absorbents. Put into properly labeled containers for reclamation or disposal. If allowed by local environmental regulatory agencies, you may use a suitable dispersant. Check with local environmental regulatory agencies for reporting requirements.

See SECTION 8 for EXPOSURE CONTROLS and PERSONAL PROTECTION.

SECTION 7: HANDLING & STORAGE

Handling

Do not handle near heat, sparks, or flame. Material can accumulate static charges which may cause an electrical spark. When the material is handled in bulk, an electrical spark could ignite any flammable vapors from liquids or residues that may be present. Use proper bonding and/or ground procedures. Avoid contact with oxidizing agents. Use only with adequate ventilation/personal protection (SEE section 8). Avoid contact with eyes, skin and clothing. After handling, always wash hands thoroughly with soap and water. Avoid personal contact with any residue. Dispose of empty containers with care. Empty containers can contain flammable residue and explosive vapors. *Do not cut, weld, or reuse empty container.*

Storage

Store in a well-ventilated place. Keep container tightly closed. Open slowly in order to control possible pressure release. Keep cool. Store locked up. Do not store near heat, sparks, open flame, or other ignition sources. Do not store near strong oxidizing agents. Do not store in direct sunlight. Avoid storing above 120°F (49°C).

SECTION 8: EXPOSURE CONTROLS and PERSONAL PROTECTION

Engineering Controls

Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits.



Penetone® Corporation, 125 Kingsland Ave., Clifton, NJ 07014

PRESSHELPER #7HF

Page: 4 of 8

Date Prepared: September 25, 2019

SDS No.: 4755

Personal Protection

<u>Inhalation</u> A respiratory protection program that meets OSHA's 29 CFR 1910.134 or ANSI Z88.2 requirements must be followed whenever workplace conditions warrant respirator use. Use of an organic vapor mask or respirator is recommended.

<u>Skin</u> Wear chemical resistant gloves such as: rubber, nitrile, neoprene, or latex when skin contact is possible. Protective clothing including gloves, apron, sleeves, boots, head and face protection should be worn depending on how the product is used. PPE should be cleaned thoroughly after each use.

<u>Eyes</u> Penetone recommends always wearing safety glasses as a minimum in any workplace. Conditions may warrant the use of chemical goggles and possibly a face shield. Consult your standard operating procedure or safety professional for advice. Use protective eye and face devices that comply with ANSI Z87.1-1987.

Additional Remarks

Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use.

Occupational Exposure Limits

Component Name	Source	Value	Type	Notation
Aliphatic petroleum naphtha	ACGIH	1200 mg/m ³	TWA	Appendix H
	NIOSH	350 mg/m ³	TWA	
		1800 mg/m ³	С	15 minutes
	OSHA Z1	500 ppm	TWA	
Dipropylene glycol methyl ether	ACGIH	100 ppm	TWA	Skin
		150 ppm	STEL	Skin
	NIOSH	100 ppm	TWA	Skin
		150 ppm	STEL	Skin
	OSHA Z1	100 ppm	PEL	Skin
d-Limonene (1)	ACGIH	20 ppm	TWA	
	NIOSH	100 ppm	TWA	
	OSHA Z1	100 ppm	PEL	

(1) No OEL has been established for d-limonene. Value given is for turpentine which has same molecular weight and similar structure.

SECTION 9: PHYSICAL & CHEMICAL PROPERTIES

Appearance: clear water white liquid

Odor: mild citrus

Odor Threshold: not determined

pH: not applicable

Melting Point / Freezing: less than 20°F

Boiling Point / Boiling Point Range: inital about 320°F

Flash Point: 168°F TCC

Evaporation Rate: less than 1 (acetone=1)

Flammability: not applicable

Lower Flammable Limit: not determined
Upper Flammable Limit: not determined
Explosive Properties: not explosive

Vapor Pressure: less than 1 mm Hg @ 20°C (68°F)

Relative Vapor Density: not determined

Relative Density: 0.81



Penetone® Corporation, 125 Kingsland Ave., Clifton, NJ 07014

PRESSHELPER #7HF

Page: 5 of 8

Date Prepared: September 25, 2019

SDS No.: 4755

Solubility (Water): forms emulsion (rapidly separates, less than one hour)

Partition Coefficient (K_{ow}): not determined Auto-ignition temperature: not determined Decomposition temperature: not determined

Viscosity: less than 5 centipoise at room temperature

SECTION 10: STABILITY & REACTIVITY

Reactivity

Not reactive.

Chemical Stability

Stable under normal conditions.

Hazardous Reactions

No hazardous reactions or under normal storage conditions. Hazardous polymerization will not occur.

Conditions to Avoid

Product is a combustible liquid. Do not store near sources of heat, sparks, open flame, or other ignition sources.

Incompatible Materials

Strong oxidizing agents.

Hazardous Decomposition Products

Carbon monoxide and dioxide.

SECTION 11: TOXICOLOGICAL INFORMATION

Product Summary

Product is essentially non-toxic. May cause mild, short lasting discomfort to the eye. Prolonged or repeated exposure may dry the skin leading to discomfort and dermatitis. Product may cause a skin rash in sensitive people. Vapor/aerosol concentrations above recommended exposure levels may be irritating to the eyes and respiratory tract, and may cause headaches, dizziness, drowsiness, unconsciousness and other central nervous system effects.

Acute Toxicity:

Dermal: LD50 > 2,000 mg/kg rabbit **Inhalation:** no data available **Oral:** LD50 > 5,000 mg/kg rabbit

Skin Corrosion/Irritation

No data available. Product is considered mildly irritating based on component data and comparison to similar products. May dry the skin leading to discomfort and dermatitis.

Serious Eye Damage/Irritation

No data available. Product is considered mildly irritating based on component data and comparison to similar products. May cause mild, short-lasting discomfort.

Sensitization - Respiratory or Skin

d-Limonene may cause skin sensitization.

Germ Cell Mutagenicity

Not expected to be a germ cell mutagen. Based on test data for structurally similar materials.



Penetone® Corporation, 125 Kingsland Ave., Clifton, NJ 07014

PRESSHELPER #7HF

Page: 6 of 8

Date Prepared: September 25, 2019

SDS No.: 4755

Carcinogenicity

Various studies have shown that d-limonene when fed at very high levels to laboratory animals have resulted in effects on the kidneys, liver, ureter, and bladder. d-Limonene is listed by IARC as Group 3: not classifiable as to its carcinogenicity to humans and is listed by ACGIH as Group 4: not classifiable as a human carcinogen. d-Limonene is listed as an equivocal tumorigenic agent by RTECS criteria.

Reproductive Toxicicty

Not expected to be a reproductive toxicant. Based on test data for structurally similar materials.

Specific Target Organ Effects - Single Exposure

Not expected to cause organ damage from a single exposure.

Specific Target Organ Effects - Repeated or Prolonged Exposure

Not expected to cause organ damage from prolonged or repeated exposure. Based on test data for structurally similar materials. d-Limonene: Repeated dose toxicity: mouse (male/female): NOEL - 1,650 mg/kg; LOEL - 3,300 mg/kg

Aspiration Hazard

Based upon available data and comparison to similar materials, if swallowed, may pose a lung aspiration hazard during vomiting. Lung aspiration may result in chemical pneumonitis, pulmonary edema, and damage to lung tissue or death.

SECTION 12: ECOLOGICAL INFORMATION

Product Summary

Product expected to be harmful toxic to aquatic organisms. (Acute aquatic toxicity category 3 by European Union classification).

Ecotoxicity

LC50/EC50/IC50 10-100 mg/l (estimated using additivity formula).

Persistence and Degradability

Expected to be readily biodegradable. Transformation due to hydrolysis and photolysis not expected to be significant. Expected to degrade rapidly in air.

Bioaccumulative Potential

Due to biodegradability, expected to have low bioaccumulative potential.

Mobility in soil

Expected to adsorb onto soil

Other Adverse Effects

None known.

SECTION 13: DISPOSAL CONSIDERATIONS

Product is a nonhazardous waste under RCRA definitions. Dispose of contents/container in accordance with all applicable federal, state, and local regulations.

<u>**Mote:**</u> Contaminated product, soil, water, container residues and spill cleanup materials may be hazardous wastes. Appropriate hazardous waste designation is the responsibility of the user.



Penetone® Corporation, 125 Kingsland Ave., Clifton, NJ 07014

PRESSHELPER #7HF

Page: 7 of 8

Date Prepared: September 25, 2019

SDS No.: 4755

SECTION 14: TRANSPORT INFORMATION

ID No.: Not applicable, nonhazardous (non-regulated) material

Proper Shipping Name: Not applicable
Hazard Class: Not applicable
Packing Group: Not applicable

Label:NoneMarine Pollutant:NoRQ:NoneSpecial Precautions:None

SECTION 15: REGULATORY INFORMATION

TSCA

The ingredients in this product are listed on the TSCA inventory.

RCRA HAZARD CLASS

Product is a nonhazardous waste.

SARA 311/312 REPORTABLE HAZARD CATEGORIES: Immediate (Acute) Health Fire

REPORTING REQUIREMENTS (all quantities in pounds)

Component	CAS / 313 Code	Section 302 (EHS) TPQ	Section 304 EHS RQ	CERCLA RQ	Section 313	CAA 112(r) TQ	CWA / OPA
no components subject to reporting requirements							

NEW JERSEY RIGHT-TO-KNOW INFORMATION

This product contains aliphatic petroleum naphtha (CAS# 64742-47-8), dipropylene glycol methyl ether (CAS 34590-94-8), d-limonene (CAS 5989-77-5), and ethoxylated nonylphenol (CAS 127087-87-0).

CALIFORNIA PROPOSITION 65 INFORMATION

This product does not contain any chemicals recognized by the state of California to cause cancer and/or birth defects or reproductive harm.

SCAQMD INFORMATION

Is there a photochemically reactive material present? Yes

What is the % by volume of photochemically reactive material? Less than 5

What is the VOC content? 780g/l

What is the vapor pressure of VOC's? Less than 1 mm Hg @ 20°C (68°F)

SECTION 16: OTHER INFORMATION

REVISION SUMMARY
Change in Section 1
Supersequence Superse

HAZARD RATING SYSTEMS:

	HMIS	NFPA	KEY
HEALTH	1	1	4 = Severe
FLAMMABILITY	2	2	3 = Serious
REACTIVITY	0	0	2 = Moderate



Penetone® Corporation, 125 Kingsland Ave., Clifton, NJ 07014

PRESSHELPER #7HF

Page: 8 of 8

Date Prepared: September 25, 2019

SDS No.: 4755

В

1 = Slight 0 = Minimal

FOR ADDITIONAL PRODUCT INFORMATION, CONTACT YOUR SALES ENGINEER FOR ADDITIONAL HEALTH/SAFETY INFORMATION, CALL 201-567-3000

THE INFORMATION PRESENTED HEREIN HAS BEEN COMPILED FROM SOURCES CONSIDERED TO BE DEPENDABLE AND ACCURATE TO THE BEST OF PENETONE'S KNOWLEDGE. THE INFORMATION RELATES TO THIS SPECIFIC MATERIAL. IT MAY NOT BE VALID FOR THIS MATERIAL IF USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY ONESELF AS TO THE SUITABILITY AND COMPLETENESS OF THIS INFORMATION FOR HIS OWN PARTICULAR USE.