

CITRIKLEEN DEGREASERS



CITRIKLEEN B29 is a low-foaming, heavy duty cleaner and degreaser designed for cleaning applications requiring fast and efficient rinsing or in areas where foam production can lead to clogged equipment or pump cavitation. It is generally effective in a variety of hard surface cleaning tasks that are sensitive or hindered by continuous foam production.

FEATURES AND BENEFITS

- Low foaming
- Utilizes the solvency and sustainability of *d-limonene*
- Non-flammable
- Non-corrosive
- Water emulsifiable
- Highly effective and versatile solvency
- Rinses effectively and quickly leaving no residue
- Effective alternative to wholly solvent-based cleaners and degreasers
- May be used in re-circulating wash-bay systems
- Compatible with virtually all washable hard surfaces
- Also effective for a variety of manual tasks including shop cleaning and dip tank applications

DIRECTIONS FOR USE

Soils to be removed	Bituminous residues, tar, greases, used oils or lubricants, etc.
Use procedure	Use CITRIKLEEN B29 as directed. May be used manually or with adequate high-pressure systems. Scour or brush stubborn deposits.
Concentration	Most effective when used undiluted. May be diluted 1:4 to 1:20 with water for immediate use in high-pressure systems.
Dwell time / Operation time	Allow to dwell 3 to 5 minutes before final rinsing.
Mechanical action	Scrubbing and rinsing recommended for removing stubborn deposits.
Rinsing	Allow product to dwell before rinsing. High-pressure, hot water is recommended.

CITRIKLEEN® B29

LOW-FOAMING, HEAVY-DUTY CLEANER & DEGREASER

PHYSICAL PROPERTIES

Appearance	Yellow liquid
Odour	Citrus/pine
Specific Gravity @ 20°C	0.940-0.950
Viscosity	Thin
pH	7.0-8.0
Flash Point (TCC)	52°C
Boiling Point	Approx. 100°C
Freezing Point	Not available
Foaming Tendency	Low
Water Solubility	Emulsifies
Autoignition temperature	Not determined
Rinsability	Excellent

INCOMPATIBILITY

Strong oxidizing materials

WAREHOUSING PRECAUTIONS

Keep container closed when not in use
Store away from heat sources and flames

AVAILABLE SIZES

		
20L / 5,28Gal.	205L / 54,16Gal	1000L / 264,17Gal.

FIRST AID MEASURES

EYE CONTACT

Wash with plenty of water for 15 minutes. Consult physician if irritation develops or persists.

SKIN CONTACT

Wash with plenty of water for 15 minutes. Consult physician if irritation develops or persists.

INHALATION

Give fresh air or artificial respiration. Consult physician.

INGESTION

Do not induce vomiting. Drink plenty of water and contact physician.

HEALTH

1

FLAMMABILITY

2

REACTIVITY

0

LEGEND

0 = MINIMAL RISK
1 = SLIGHT RISK
2 = MODERATE RISK
3 = SERIOUS RISK
4 = SEVERE RISK

PERSONAL PROTECTION Security equipment



WHMIS



IMPORTANT: Before using CITRIKLEEN B29, always be sure to read and follow precautions and directions for use appearing on the product container label and on the material safety data sheet (m.s.d.s.).



CLIFTON
125 Kingsland Avenue
Clifton, NJ 07014
Tel.: 201-567-3000
Toll free: 1-800-631-1652

MONTREAL
10,900 rue Secant
Anjou, Quebec H1J 1S5
Tel.: 514-355-4660
Toll free : 1-800-361-8927

EDMONTON
11411-160 Street
Edmonton, Alberta T5M 3T7
Tel.: 780-454-3919
Toll free: 1-866-454-3919

United States
www.penetone.com

Canada
www.westpenetone.com