

## SOLVENT DEGREASERS



**PENMUL R950T** is a water emulsifiable solvent designed for heavy tasks. It will effectively dissolve difficult to remove deposits such as tar, asphalt, heavy petroleum, and carbonized deposits from a variety of surfaces.

## FEATURES AND BENEFITS

- High flash point
- Relatively mild odour
- Powerful and fast acting
- **PENMUL R950T** may be rinsed with water, which is exceptional for a product of this type.
- Very safe product in most cases since its flash point is 63°C (145,4°F).

## DIRECTIONS FOR USE

## Equipment to be cleaned

Diesel or gas motors, production machinery, trucks or tankers, printing presses, floors soiled with used lubricating oils and grease, burner tips.

## Soils to be removed

Highly stubborn deposits such as lubricating oils and greases, deposits located on diesel or gas motors, carbon from diesel motor exhaust pipes, ink, tar, asphalt, latex, certain adhesives, etc.

## Use procedure

For very thick deposits, manually remove as much as possible first and then apply **PENMUL R950T** as is or diluted with water. Allow to dwell 5 to 30 minutes and wipe with a cloth or rinse with high-pressure water.

## Concentration

As is or diluted up to 1:10 with water, according to amount of soil.

## Use temperature

Ambient

## Dwell time / Operation time

5 to 30 minutes, according to the amount of soil.

## Mechanical action

It is generally recommended to scrub or rinse with high-pressure water.

## Rinsing

Hot or cold water.

# PENMUL R950T

## HEAVY-DUTY EMULSIFIABLE SOLVENT

### PHYSICAL PROPERTIES

Appearance	Clear Liquid
Odour	Aromatic solvent
Specific Gravity @ 20°C	0.90
Viscosity	Thin
pH	Not applicable
Flash Point (TCC)	63°C (145,4°F)
Boiling Point	180°C (356°F)
Freezing Point	< -40°C (-40°F)
Foaming Tendency	Low
Concentration Monitoring Techniques	Refractive index
Rinsability	Good
Water Solubility	Emulsifies
Phosphorus	None
Auto ignition temperature	443°C (829,4°F)
Chlorine	None

### INCOMPATIBILITY

Strong oxidizers

### WAREHOUSING PRECAUTIONS

Store away from heat sources and flames

### AVAILABLE SIZES



20L / 5,28Gal.    205L / 54,16Gal.    1000L / 264,17Gal.

### FIRST AID MEASURES

#### EYE CONTACT

Rinse with plenty of water for 15 minutes. Consult physician if irritation develops or persists.

#### SKIN CONTACT

Wash with soap and water. Consult physician if irritation develops or persists.

#### INHALATION

Give fresh air or artificial respiration. Consult physician.

#### INGESTION

Do not induce vomiting. Consult physician immediately.

### HEALTH

2

### FLAMMABILITY

1

### REACTIVITY

1

### PERSONAL PROTECTION Security equipment



#### LEGEND

0 = MINIMAL RISK  
 1 = SLIGHT RISK  
 2 = MODERATE RISK  
 3 = SERIOUS RISK  
 4 = SEVERE RISK



**IMPORTANT:** Before using PENMUL R950T, always be sure to read and follow precautions and directions for use appearing on the product container label and on the material safety data sheet (m.s.d.s.).

#### CARLSTADT

700 Gotham Parkway  
 Carlstadt, New Jersey 07072  
 Tel.: 201-567-3000  
 Toll free : 1-800-631-1652

#### MONTREAL

10,900 rue Secant  
 Anjou, Quebec H1J 1S5  
 Tel.: 514-355-4660  
 Toll free : 1-800-361-8927

#### EDMONTON

11411-160 Street  
 Edmonton, Alberta T5M 3T7  
 Tel.: 780-454-3919  
 Toll free: 1-866-454-3919

#### United States

[www.penetone.com](http://www.penetone.com)

#### Canada

[www.westpenetone.com](http://www.westpenetone.com)