

SOLVENT DEGREASERS



RAMSOL BCX is a heavy duty solvent blend designed for chemical circulation procedures where the removal of asphaltenes and resins is required from lines and vessels. It can be emulsified in water to a low or high pH to customize foulant removal.

FEATURES AND BENEFITS

- Disperses hydrocarbon sludge and foulant accumulation upon application and rinsing
- Powerful and fast acting
- Safe on all hard metal surfaces
- Effective and efficient replacement for hot diesel cleaning

DIRECTIONS FOR USE

Soils to be removed	Saturates & polymeric materials, bitumen, resins, heavy oils, asphaltenes, etc.
Use procedure	May be used in combination with alkali, acid, and surfactant chemical cleaning or circulation procedures. Rinse procedure recommended. Consult with your local West Penetone sales representative for procedures best suited for your application.
Concentration	Most effective when used undiluted. Dilute to 2-5% v/v when used as part of a general chemical cleaning procedure requiring film removal. For removal of heavy deposition, use up to 18-25% v/v.
Use Temperature	Ambient when used at concentrate. 65°C-70°C (149°F-158°F) recommended when used as part of chemical cleaning procedure.
Dwell time / Operation time	5 to 30 minutes, according to the amount and depth of foulant. Monitoring and centrifuging of retains is recommended.

RAMSOL BCX

HEAVY-DUTY SOLVENT DEGREASER

PHYSICAL PROPERTIES

Appearance	Yellow liquid
Odour	Solvent/pine
Specific Gravity @ 20°C	0.895 - 0.900
Viscosity	Thin
pH	Not applicable
Flash Point (TCC)	46°C (114,8°F)
Boiling Point	Not determined
Freezing Point	Not determined
Foaming Tendency	Nil
Concentration Monitoring Techniques	Not determined
Rinsability	Excellent
Water Solubility	Emulsifies




INCOMPATIBILITY

Oxidizing materials
Do not use on finely coated surfaces

WAREHOUSING PRECAUTIONS

Store away from heat sources and flames

AVAILABLE SIZES

		
20L / 5,28Gal.	205L / 54,16Gal.	1000L / 264,17Gal.

FIRST AID MEASURES

EYE CONTACT

Wash with plenty of water for 15 minutes.
Consult physician if irritation develops or persists.

SKIN CONTACT

Wash with plenty of water for 15 minutes.
Consult physician if irritation develops or persists.

INHALATION

Give fresh air or artificial respiration.
Consult physician.

INGESTION

Do not induce vomiting. Drink plenty of water
and consult physician immediately.

HEALTH

2

FLAMMABILITY

2

REACTIVITY

0

LEGEND

0 = MINIMAL RISK
1 = SLIGHT RISK
2 = MODERATE RISK
3 = SERIOUS RISK
4 = SEVERE RISK

PERSONAL PROTECTION Security equipment



WHMIS



IMPORTANT: Before using RAMSOL BCX, always be sure to read and follow precautions and directions for use appearing on the product container label and on the material safety data sheet (m.s.d.s.).



CARLSTADT

700 Gotham Parkway
Carlstadt, New Jersey 7072
Tel.: 201-567-3000
Toll free : 1-800-631-1652

MONTREAL

10,900 rue Secant
Anjou, Quebec H1J 1S5
Tel.: 514-355-4660
Toll free : 1-800-361-8927

EDMONTON

11411-160 Street
Edmonton, Alberta T5M 3T7
Tel.: 780-454-3919
Toll free: 1-866-454-3919

United States
www.penetone.com

Canada
www.westpenetone.com