

Penetone® Corporation, 125 Kingsland Ave., Clifton, NJ 07014

ROC 45 Page: 1 of 7

Date Prepared: September 25, 2019

SDS No.: 9160

SECTION 1: IDENTIFICATION

Product name: ROC 45

Recommended use: Reduction of LELs and hydrocarbon fouling **Physcial Description:** Clear water white liquid with mild odor **Generic Ingredients:** Water, surfactants, and chelate

Manufacturer:Business Contact:Penetone CorporationCustomer Service

125 Kingsland Ave. 800-631-1652 x2602 or 2272

Clifton, NJ 07014 Product Safety

800-631-1652 or 201-567-3000 800-631-1652 x2211 or 2257

Emergency Phone Numbers: PENETONE 201-567-3000 CHEMTREC 800-424-9300

SECTION 2: HAZARDS IDENTIFICATION

GHS CLASSIFICATION:

Health:	Carcinogenicity: 2
Skin irritation: 2	Physical:
Eye irritation: 2A	not classified

WARNING!

Causes Skin Irritation.
Causes Serious Eye Irritation.
Suspected of Causing Cancer.





Precautionary Statements:

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Wear protective gloves, clothing, eye protection, and face protection. Wash hands and exposed skin thoroughly after handling.

Response:

If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

If exposed or concerned: Get medical advice/attention.

Storage:

Store locked up.

Disposal:

Dispose of contents/container in accordance with local, regional, and national regulations (see Sections 13 and 15 of SDS for disposal and reporting requirements).

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Concentration Wt% (1)
Water	7732-18-5	65-80
Alcohols, C9-11, ethoxylated	68439-26-3	1-10
Lauramine oxide	1643-20-5	1-10
Alcohols, C12-15, ethoxylated	68131-39-5	1-10
Coco diethanolamide	68603-42-9	1-10
Tetrasodium ethylenediamine tetraacetate	64-02-8	1-10



Penetone® Corporation, 125 Kingsland Ave., Clifton, NJ 07014

ROC 45 Page: 2 of 7

Date Prepared: September 25, 2019

SDS No.: 9160

SECTION 4: FIRST-AID MEASURES

General Description of Symptoms & First-Aid Measures

Most likely work-place exposure routes will be skin contact or inhalation.

For *skin contact*, typically no immediate effects will be observed. A slight tingling sensation might be felt some time after exposure. Slight reddening or minor irritation could also develop if product is not quickly washed off.

Inhalation exposure may produce varied effects. Typical symptoms could include coughing, sneezing, and a tingling sensation in the nose, throat, and lungs.

Eves

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists or develops: Get medical advice or attention. Penetone recommends that after any eye exposure a physician be seen immediately.

Ingestion

If swallowed: Rinse mouth. Call a poison center, doctor, physician or other competent medical authority if you feel unwell.

Inhalation

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center, doctor, physician or other competent medical authority if you feel unwell.

Skin

If on skin: Wash with plenty of water or a mild soap. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice or attention.

Special Treatment / Other

None

SECTION 5: FIRE FIGHTING MEASURES

Flammable Properties

Classification: Non-flammable Flash Point: None-to-boil

Autoignition Temperature: Not applicable

Lower Flammable Limit: Not applicable Upper Flammable Limit: Not applicable

Specific Hazards

Product is water based and presents no unusual fire hazards.

Extinguishing Media

Use extinguishing agents appropriate for controlling surrounding fire.

Unsuitable: None.

Protection & Precautions for Firefighters

Protective Equipment & Clothing: Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters protective clothing will only provide limited protection.

Fire Fighting Guidance: Cool containers with flooding quantities of water until well after fire is out. Move containers from fire area if you can do it safely. Dike fire control water for later disposal; do not scatter material. Containers can expand and explode under fire conditions due to vapor buildup. Always stay away from containers engulfed in fire.





Penetone® Corporation, 125 Kingsland Ave., Clifton, NJ 07014

ROC 45 Page: 3 of 7

Date Prepared: September 25, 2019

SDS No.: 9160

Hazardous Combustion Products: Smoke, fumes, and oxides of carbon and nitrogen when taken to dryness.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Land Spill

Stop leak if you can do it safely. For large spills, dike and pump into properly labeled containers for reclamation or disposal. For small spill, soak up with absorbent material and place in properly labeled containers for disposal.

Water Spill

This is a water based product and will completely mix/dissolve in water making recovery difficult. Product is weakly alkaline and may raise pH of waters with low buffering capacity. Check with local environmental regulatory agencies for reporting requirements.

See SECTION 8 for EXPOSURE CONTROLS and PERSONAL PROTECTION.

SECTION 7: HANDLING & STORAGE

Handling

Avoid contact with eyes, skin and clothing. After handling, always wash hands thoroughly with soap and water. Avoid personal contact with any residue. Do not cut, weld, or reuse empty container.

Storage

Keep container tightly closed when not in use. Do not store near strong acids or bases. Do not store in direct sunlight. Avoid storing above 120°F (49°C).

SECTION 8: EXPOSURE CONTROLS and PERSONAL PROTECTION

Engineering Controls

Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits.

Personal Protection

<u>Inhalation</u> A respiratory protection program that meets OSHA's 29 CFR 1910.134 or ANSI Z88.2 requirements must be followed whenever workplace conditions warrant respirator use. Use of a general purpose particulate mask or respirator with particulate filter is recommended.

<u>Skin</u> Wear chemical resistant gloves such as: rubber, nitrile, neoprene, or latex when skin contact is possible. Protective clothing including gloves, apron, sleeves, boots, head and face protection should be worn depending on how the product is used. PPE should be cleaned thoroughly after each use.

<u>Eyes</u> Penetone recommends always wearing safety glasses as a minimum in any workplace. Conditions may warrant the use of chemical goggles and possibly a face shield. Consult your standard operating procedure or safety professional for advice. Use protective eye and face devices that comply with ANSI Z87.1-1987.

Additional Remarks

Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use.

Occupational Exposure Limits

<u>Component Name</u> <u>Source</u> <u>Value</u> <u>Type</u> <u>Notation</u>

No OELs have been established for any of the components



Penetone® Corporation, 125 Kingsland Ave., Clifton, NJ 07014

ROC 45

Page: 4 of 7

Date Prepared: September 25, 2019

SDS No.: 9160

SECTION 9: PHYSICAL & CHEMICAL PROPERTIES

Appearance: clear water white liquid

Odor: mild

Odor Threshold: not determined

pH: 9-10

Melting Point / Freezing: about 32°F

Boiling Point / Boiling Point Range: about 212°F

Flash Point: none to boil

Evaporation Rate: equal to water **Flammability:** not applicable

Lower Flammable Limit: not applicable
Upper Flammable Limit: not applicable
Explosive Properties: not applicable
Vapor Pressure: equal to water

Relative Vapor Density: not applicable

Relative Density: 1.005

Solubility (Water): water soluble

Partition Coefficient (K_{ow}): not determined Auto-ignition temperature: not applicable Decomposition temperature: not determined

Viscosity: less than 5 centipoise at room temperature

SECTION 10: STABILITY & REACTIVITY

Reactivity

Product is not reactive, but if strong acids or bases are added, heat will be generated which could cause splattering.

Chemical Stability

Stable.

Hazardous Reactions

None.

Conditions to Avoid

Do not store near strong acids or bases.

Incompatible Materials

Strong acids or bases.

Hazardous Decomposition Products

Oxides of carbon and nitrogen when taken to dryness and burned.

SECTION 11: TOXICOLOGICAL INFORMATION

Product Summary

Based upon ingredient data, product is non-toxic by oral and dermal routes exposure. Based upon ingredient information, product is expected to cause skin irritation and to cause serious eye irritation.

West Penetone

SAFETY DATA SHEET

Penetone® Corporation, 125 Kingsland Ave., Clifton, NJ 07014

ROC 45 Page: 5 of 7

Date Prepared: September 25, 2019

SDS No.: 9160

Acute Toxicity:

Dermal: > 5,000 mg/kg rabbit (estimated from additivity formula)

Inhalation: no data available

Oral: > 5,000 mg/kg rat (estimated from additivity formula)

Skin Corrosion/Irritation

Causes skin irritation. Based upon component data.

Serious Eye Damage/Irritation

Causes serious eye irritation. Based upon component data.

Sensitization - Respiratory or Skin

Not expected to be a skin or respiratory sensitizer. Based upon component data.

Germ Cell Mutagenicity

No data available. Not expected to be mutagenic based upon component information.

Carcinogenicity

Coco diethanolamide is listed by IARC as Group 2B: Possibly carcinogenic to humans.

Developmental/Reproductive Toxicitty

No data available. Not expected to be a developmental or reproductive toxin based upon partial component information and comparison to structurally similar compounds.

Specific Target Organ Effects - Single Exposure

No data available.

Specific Target Organ Effects - Repeated or Prolonged Exposure

No data available.

Aspiration Hazard

Based upon components, product not expected to be aspiration hazard.

SECTION 12: ECOLOGICAL INFORMATION

Product Summary

Product is harmful to fish and aquatic invertebrates. (Acute aquatic toxicity category 3 by European Union classification).

Ecotoxicity

Fish: LC50 10-50 mg/l (estimated using additivity formula)

Invertebrates: EC50 10-50 mg/l (estimated using additivity formula)

Persistence and Degradability

The surfactants used in this product are all readily biodegradable.

Bioaccumulative Potential

Product components not considered bioaccumulative

Mobility in soil

No soil mobility data available.

Other Adverse Effects

None known.



Penetone® Corporation, 125 Kingsland Ave., Clifton, NJ 07014

ROC 45 Page: 6 of 7

Date Prepared: September 25, 2019

SDS No.: 9160

SECTION 13: DISPOSAL CONSIDERATIONS

Product is a nonhazardous waste under RCRA definitions. Dispose of contents/container in accordance with all applicable federal, state, and local regulations.

<u>Mote:</u> Contaminated product, soil, water, container residues and spill cleanup materials may be hazardous wastes. Appropriate hazardous waste designation is the responsibility of the user.

SECTION 14: TRANSPORT INFORMATION

ID No.: None

Proper Shipping Name: Nonhazardous (nonregulated) material

Hazard Class: None
Packing Group: None
Label: None
Marine Pollutant: No
RQ: None
Special Precautions: None

SECTION 15: REGULATORY INFORMATION

TSCA

The ingredients in this product are listed on the TSCA inventory.

RCRA HAZARD CLASS

Nonhazardous waste

SARA 311/312 REPORTABLE HAZARD CATEGORIES: Immediate (Acute) Health

REPORTING REQUIREMENTS (all quantities in pounds)

Сотр	oonent	CAS / 313 Code	Section 302 (EHS) TPQ	Section 304 EHS RQ	CERCLA RQ	Section 313	CAA 112(r) TQ	CWA / OPA
no component is subject to reporting requirements								

NEW JERSEY RIGHT-TO-KNOW INFORMATION

This product contains water (CAS 7732-18-5), ethoxylated C9–11 alcohols (CAS 68439-46-3), lauramine oxide (CAS 1643-20-6), ethoxylated C12-15 alcohols (CAS 68131-39-5), and coco diethanolamide (CAS# 68603-42-9).

CALIFORNIA PROPOSITION 65 INFORMATION

⚠

This product can expose you to coco diethanolamide which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

SCAQMD INFORMATION

Is there a photochemically reactive material present? No What is the % by volume of photochemically reactive material? 0 What is the VOC content? 0 g/l What is the vapor pressure of VOC's? 0



Penetone® Corporation, 125 Kingsland Ave., Clifton, NJ 07014

ROC 45 Page: 7 of 7

Date Prepared: September 25, 2019

SDS No.: 9160

SECTION 16: OTHER INFORMATION

REVISION SUMMARY
Change in Section 1
SUPERSEDES ISSUE DATE
March 17, 2017

HAZARD RATING SYSTEMS:

	HMIS	NFPA	KEY
HEALTH	1	1	4 = Severe
FLAMMABILITY	0	0	3 = Serious
REACTIVITY	0	0	2 = Moderate
	В		1 = Slight
			0 = Minimal

FOR ADDITIONAL PRODUCT INFORMATION, CONTACT YOUR SALES ENGINEER FOR ADDITIONAL HEALTH/SAFETY INFORMATION, CALL 201-567-3000

THE INFORMATION PRESENTED HEREIN HAS BEEN COMPILED FROM SOURCES CONSIDERED TO BE DEPENDABLE AND ACCURATE TO THE BEST OF PENETONE'S KNOWLEDGE. THE INFORMATION RELATES TO THIS SPECIFIC MATERIAL. IT MAY NOT BE VALID FOR THIS MATERIAL IF USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY ONESELF AS TO THE SUITABILITY AND COMPLETENESS OF THIS INFORMATION FOR HIS OWN PARTICULAR USE.