

H₂S SCAVENGERS / DEGASIFICATION



ROC 55X is a product used for liquid phase applications requiring the removal of high H₂S concentrations as well as for foulant removal and LEL reduction. **ROC 55X** can also be used for batch fluid treatments with high H₂S demands and applied year-round for various types of cleaning applications.

FEATURES AND BENEFITS

- Contains no added formaldehyde
- Kinematic viscosity data available
- Effective alternative to **ROC 40** or **ROC 45** in liquid phase applications with excessive H₂S concentrations
- Suitable for environments with temperatures as low as -49°C (-56,2°F)
- Versatile application methods

DIRECTIONS FOR USE

Use procedure

May be used with adequate foaming or high-pressure systems or by direct injection when used as part of a circulation procedure. Consult with your local West Penetone sales representative for procedures best suited for your application.

Dosage application

A minimum concentration of 5-10% v/v with water is recommended when foaming, applying by high-pressure, or as part of a prescribed volume circulation/cascade procedure. When used as part of an injection procedure apply at a maximum rate of 6-8 L/min (1,5 - 2 gal./min) into a continuous water stream.

Use temperature

Ambient to a maximum of 40°C (104°F) is recommended.

Dwell time/Operation time

Dependent on job, site and method of application. 6-10 hours is recommended when accompanied by hourly gas testing and monitoring of circulation fluid.

ROC 55X

HIGH CAPACITY DEGASIFICATION AID & SULFIDE SCAVENGER

PHYSICAL PROPERTIES

Appearance	Yellow liquid
Odour	Alcohol/amine
Specific Gravity @ 20°C	0.98-0.99
Viscosity	Not available
pH	9.5-10.5
Flash Point (TCC)	32°C (89°F)
Boiling Point	Not available
Freezing Point	-49°C (-56°F)
Foaming Tendency	High
Concentration Monitoring Techniques	Not determined
Water Solubility	Complete
Rinsability	Excellent




INCOMPATIBILITY

Acids, oxidizing agents.

WAREHOUSING PRECAUTIONS

Keep containers tightly closed away from direct sunlight in a dry, cool and well-ventilated place.

AVAILABLE SIZES

			
20L/ 5,28Gal.	205L/ 54,16Gal.	1000L/ 264,71Gal.	

FIRST AID MEASURES

EYE CONTACT

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

SKIN CONTACT

Wash with plenty of water. Call a POISON CENTER or doctor/physician if you feel unwell. If skin irritation or rash occurs, get medical advice/attention. Take off immediately all contaminated clothing and wash it before re-use.

INHALATION

If difficulties occur after mist/vapors/spray has been inhaled, remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

INGESTION

Rinse mouth. Call a POISON CENTER or doctor/physician if you feel unwell.

HEALTH

2

FLAMMABILITY

3

REACTIVITY

0

LEGEND

0 = MINIMAL RISK
1 = SLIGHT RISK
2 = MODERATE RISK
3 = SERIOUS RISK
4 = SEVERE RISK

PERSONAL PROTECTION Security equipment



WHMIS



IMPORTANT: Before using ROC 55X, always be sure to read and follow precautions and directions for use appearing on the product container label and on the safety data sheet (S.D.S).



CLIFTON

125 Kingsland Avenue
Clifton, NJ 07014
Tel.: 201-567-3000
Toll free: 1-800-631-1652

MONTREAL

10,900 rue Secant
Anjou, QC H1J 1S5
Tel.: 514-355-4660
Toll free : 1-800-361-8927

EDMONTON

11411-160 Street
Edmonton, Alberta T5M 3T7
Tel.: 780-454-3919
Toll free: 1-866-454-3919

United States
www.penetone.com

Canada
www.westpenetone.com