

GENERAL USE INDUSTRIAL PRODUCTS



WESTOP 480

WESTOP 480 is a water based corrosion inhibitor. Protects iron, steel and other ferrous alloys during immersion and in open air, even when the atmosphere is humid. Its high concentration allows **WESTOP 480** to be effective even when highly diluted.

FEATURES AND BENEFITS

- Aqueous solution
- Highly active ingredients
- Double action: cathodic and film forming protection
- Remains stable at high temperature
- Effective when parts are immersed or in open air
- Prevent rust indefinitely in water immersion
- Protects against rust long after immersion or spray
- Odourless
- Non toxic and non irritant
- Cost efficient

Add **WESTOP 480** to rinsing water (rinsing by immersion or spray). Add **WESTOP 480** to water circulating in cooling systems or tank. For non-submerged parts, simply spray **WESTOP 480** on surface to protect. Avoid rinsing.

Concentration12 to 25 ml per litre of water.Use temperatureBetween 50°C and 70°CRinsingDo not rinse.Reuse/recyclingIn a tank, cooling or rinsing system.

Use procedure

WESTOP 480

Corrosion Inhibitor

PHYSICAL PROPERTIES

Appearance	Green liquid
Odour	None
Specific Gravity @ 20°C	1.07
Viscosity	< 10 cps
рН	10
Flash Point (TCC)	None
Boiling Point	100ºC
Freezing Point	Not available
Auto Ignition Temperature	None
Foaming Tendency	Moderate
Concentration Monitoring Techniques	Refractive index
Rinsability	Not applicable
Water Solubility	Complete

INCOMPATIBILITY

Acids

WAREHOUSING PRECAUTIONS

Store away from reactive substances

FIRST AID MEASURES

EYE CONTACT Wash with plenty of water for 15 minutes. Consult physician if irritation develops or persists. **SKIN CONTACT** Wash with soap and water. Consult physician if irritation develops or persists. INHALATION No object INGESTION Do not induce vomiting. Drink plenty of water and consult physician immediately.

HEALTH	1
FLAMMABILITY	0
REACTIVITY	0
LEGEND 0 = MINIMAL RISK 1 = SLIGHT RISK 2 = MODERATE RISK 3 = SERIOUS RISK 4 = SEVERE RISK	



IMPORTANT: Before using **WESTOP 480**, always be sure to read and follow precautions and directions for use appearing on the product container label and on the safety data sheet (S.D.S).



CLIFTON

125 Kingsland Avenue Clifton, New Jersey 07014 Tel.: 201-567-3000 Toll free : 1-800-631-1652

MONTREAL

10,900 rue Secant Anjou, QC H1J 1S5 Tel.: 514-355-4660

EDMONTON

11411-160 Street Edmonton, Alberta T5M 3T7 Tel.: 780-454-3919 Toll free : 1-800-361-8927 Toll free: 1-866-454-3919

United States www.penetone.com

Canada www.westpenetone.com