



**CELL-KLEEN™ HD2**

Page: 1 of 8  
Date Prepared: August 23, 2019  
SDS No.: 1267

**SECTION 1: IDENTIFICATION**

**Product name:** CELL-KLEEN HD2  
**Recommended use:** Anilox roll cleaner  
**Physical Description:** Light brown/amber viscous liquid with slight solvent odor  
**Generic Ingredients:** Water, potassium hydroxide, glycol ethers, chelate, alcohol, thickener, and surfactant  
**Manufacturer:** Penetone Corporation  
 125 Kingsland Ave.  
 Clifton, NJ 07014  
 800-631-1652 or 201-567-3000  
**Business Contact:** Customer Service  
 800-631-1652 x2300 or 2272  
 Product Safety  
 800-631-1652 x2211 or 2257

**Emergency Phone Numbers:** PENETONE 201-567-3000 CHEMTREC 800-424-9300

**SECTION 2: HAZARDS IDENTIFICATION**

**GHS CLASSIFICATION:**

<p><b>Health:</b> Skin corrosion: 1B Eye damage: 1 Acute toxicity - oral: 4</p>	<p>Specific target organ toxicity - single exposure: 1  <b>Physical:</b> Corrosive to metals - 1</p>
---	--

**DANGER!**

Causes Severe Skin Burns and Eye Damage.  
 Harmful If Swallowed.  
 Causes Damage to Organs (Gastrointestinal System and Respiratory System If Swallowed)  
 May Be Corrosive to Metals.



<b>Precautionary Statements:</b>	
<p><u>Prevention:</u> Do not breathe mists if inhalable mists occur during use. Wear protective gloves, clothing, eye protection, and face protection. Wash hands and exposed skin thoroughly after handling. Keep only in original container</p> <p><u>Response:</u> <i>If swallowed:</i> Rinse mouth. Do NOT induce vomiting. <i>If on skin or hair:</i> Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse. <i>If in eyes:</i> Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p>	<p><i>If inhaled:</i> Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center, doctor, emergency room, or 911. Absorb spillage to prevent material damage.</p> <p><u>Storage:</u> Store locked up. Store in corrosive resistant container, plastic (HDPE) is recommended, or container with a resistant inner liner.</p> <p><u>Disposal:</u> Dispose of contents/container in accordance with local, regional, and national regulations (see Sections 13 and 15 of SDS for disposal and reporting requirements).</p>

**SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS**

Chemical Name	CAS#	Concentration Wt% (1)
Water	7732-18-5	60-80
Potassium hydroxide	1310-58-3	15-25
Sodium glucoheptonate	31138-65-5	1-10
Polyacrylate	9003-01-4	1-10



---

**CELL-KLEEN™ HD2**

Page: 2 of 8  
Date Prepared: August 23, 2019  
SDS No.: 1267

---

Tripropylene glycol methyl ether	20374-33-8	1-10
Ethylene glycol butyl ether	111-76-2	1-10
Methyl alcohol	67-56-1	1-10

(1) Exact percentages being withheld under trade secret provision of OSHA HCS 1910.1200(I)

---

**SECTION 4: FIRST-AID MEASURES**

**General Description of Symptoms & First-Aid Measures**

This product contains potassium hydroxide and is corrosive. It can cause serious burns and extensive tissue destruction if it is not quickly removed. Most likely work-place exposure route will be *skin contact*. This product has a high viscosity which may make it difficult to remove from exposed tissues.

For *skin contact*, a tingling or burning sensation might be felt shortly after exposure. Slight reddening or minor irritation could also develop if the product is not quickly washed off, followed by more severe damage, such as blistering.

*Inhalation* exposure may produce varied effects, particularly if exposure occurs above the recommended workplace exposure limits (see SECTION 8). Typical symptoms could include coughing, sneezing, and a tingling or burning sensation in the nose, throat, and lungs. Because of the product's high viscosity, it is unlikely that respirable droplets could be produced. However, such droplets if produced and inhaled would be corrosive to the respiratory tract, especially the upper respiratory tract (nose and throat).

For *eye contact*, a tingling or burning sensation may almost be immediately felt. Immediate action is required to prevent serious eye damage, such as eye lid burns, conjunctivitis, corneal edema, corneal burn, damage to the internal contents of the eye, permanent visual defects, and blindness and/or loss of the eye.

*Ingestion* of the product may cause an almost immediate tingling or burning sensation followed by more severe pain. Irritation, swelling and perforation of the upper and lower gastrointestinal tissues may occur if immediate action is not taken. Permanent scarring may occur.

**Eyes** If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center, doctor, physician or other competent medical authority for medical advice. Penetone recommends that after any eye exposure a physician be seen immediately.

**Ingestion** If swallowed: Rinse mouth. DO NOT INDUCE VOMITING. Immediately call a poison center, doctor, physician or other competent medical authority for medical advice.

**Inhalation** If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a local Poison Control Center, physician, or other competent medical authority for medical advice.

**Skin** If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. A mild soap may be used to wash skin. Wash contaminated clothing before reuse. Immediately call a local Poison Control Center, doctor, physician or other competent medical authority for medical advice.

**Special Treatment / Other**

None

---

**SECTION 5: FIRE FIGHTING MEASURES**

**Flammable Properties**

**Classification:** Non-flammable

**Flash Point:** None-to-boil

**Autoignition Temperature:** Not determined

**Lower Flammable Limit:** Not applicable **Upper Flammable Limit:** Not applicable

**Specific Hazards**



---

**CELL-KLEEN™ HD2**

Page: 3 of 8  
Date Prepared: August 23, 2019  
SDS No.: 1267

---

Product is water based and presents no unusual fire hazards. Product may react with chemically reactive metals such as aluminum, zinc, magnesium, copper, etc. to release hydrogen gas which can form explosive mixtures in air.

**Extinguishing Media**

Use extinguishing agents appropriate for controlling surrounding fire.

**Unsuitable:** None.

**Protection & Precautions for Firefighters**

**Protective Equipment & Clothing:** Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters protective clothing will only provide limited protection.

**Fire Fighting Guidance:** Cool containers with flooding quantities of water until well after fire is out. Move containers from fire area if you can do it safely. Dike fire control water for later disposal; do not scatter material. Containers can expand and explode under fire conditions due to vapor buildup. Always stay away from containers engulfed in fire.

**Hazardous Combustion Products:** Smoke, fumes, and oxides of carbon, nitrogen, and sulfur when taken to dryness.

---

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

---

**Land Spill**

Absorb spillage to prevent material damage. Stop leak if you can do so safely. For large spills, dike and pump into properly labeled containers for reclamation or disposal. For small spill, soak up with absorbent material and place in properly labeled containers for disposal. Neutralize residue with dilute acid and follow with a liberal covering of sodium bicarbonate or other acceptable drying agent.

**Water Spill**

This is a water based product and will completely mix/dissolve in water. Product is very viscous. Product is much denser than water and will sink. Product viscosity and density may make recovery difficult. This product is caustic and will raise the pH of surface waters. Check with local environmental regulatory agencies for reporting requirements.

**See SECTION 8 for EXPOSURE CONTROLS and PERSONAL PROTECTION.**

---

**SECTION 7: HANDLING & STORAGE**

---

**Handling**

Avoid contact with eyes, skin and clothing. After handling, always wash hands thoroughly with soap and water. Avoid personal contact with any residue. Do not cut, weld, or reuse empty container.

**Storage**

Store locked up. Store in corrosive resistant container. Plastic is recommended. If storing in a metal container, it must be NON-ALUMINUM with a resistant inner liner (NOTE: flammable hydrogen gas may be generated if aluminum container and/or aluminum fittings are used). If secondary containers are used, plastic is recommended. Keep container tightly closed when not in use. Do not store near strong bases. Do not store in direct sunlight. Avoid storing above 120°F (49°C).

---

**SECTION 8: EXPOSURE CONTROLS and PERSONAL PROTECTION**

---

**Engineering Controls**

Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits.



# SAFETY DATA SHEET

Penetone® Corporation, 125 Kingsland Ave., Clifton, NJ 07014

## CELL-KLEEN™ HD2

Page: 4 of 8

Date Prepared: August 23, 2019

SDS No.: 1267

### Personal Protection

**Inhalation** A respiratory protection program that meets OSHA's 29 CFR 1910.134 or ANSI Z88.2 requirements must be followed whenever workplace conditions warrant respirator use. Use of an organic vapor mask or respirator is recommended.

**Skin** Wear chemical resistant gloves such as: rubber, nitrile, neoprene, or latex when skin contact is possible. Protective clothing including gloves, apron, sleeves, boots, head and face protection should be worn depending on how the product is used. PPE should be cleaned thoroughly after each use.

**Eyes** Penetone recommends always wearing safety glasses as a minimum in any workplace. Conditions may warrant the use of chemical goggles and possibly a face shield. Consult your standard operating procedure or safety professional for advice. Use protective eye and face devices that comply with ANSI Z87.1-1987.

### Additional Remarks

Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use.

### Occupational Exposure Limits

<u>Component Name</u>	<u>Source</u>	<u>Value</u>	<u>Type</u>	<u>Notation</u>
Potassium hydroxide	ACGIH	2 mg/m <sup>3</sup>	Ceiling	
	NIOSH	2 mg/m <sup>3</sup>	Ceiling	
Ethylene glycol butyl ether	ACGIH	20 ppm	TWA	A3, BEI
	NIOSH	5 ppm	TWA	skin
Methyl alcohol	OSHA Z1	50 ppm	TWA	skin
	ACGIH	200 ppm	TWA	skin, BEI
		250 ppm	STEL	skin, BEI
	NIOSH	200 ppm	TWA	skin
		250 ppm	STEL	skin
	OSHA Z1	200 ppm	TWA	

## SECTION 9: PHYSICAL & CHEMICAL PROPERTIES

**Appearance:** viscous brown/amber liquid

**Odor:** mild solvent

**Odor Threshold:** not determined

**pH:** >13

**Melting Point / Freezing:** about 25°F

**Boiling Point / Boiling Point Range:** about 220°F

**Flash Point:** above 200°F

**Evaporation Rate:** equal to water

**Flammability:** not applicable

**Lower Flammable Limit:** not applicable

**Upper Flammable Limit:** not applicable

**Explosive Properties:** not applicable

**Vapor Pressure:** equal to water

**Relative Vapor Density:** equal to water

**Relative Density:** 1.24

**Solubility (Water):** soluble

**Partition Coefficient (K<sub>ow</sub>):** not determined

**Auto-ignition temperature:** not determined

**Decomposition temperature:** not determined

**Viscosity:** about 30 poise



---

**CELL-KLEEN™ HD2**

Page: 5 of 8  
Date Prepared: August 23, 2019  
SDS No.: 1267

---

---

**SECTION 10: STABILITY & REACTIVITY**

---

**Reactivity**

Product will react with acids, giving off heat.

**Chemical Stability**

Stable.

**Hazardous Reactions**

Mixing with acids will give off heat and may cause splattering. Will react with some metals (see below) forming flammable hydrogen gas. Carbon monoxide gas may form upon contact with reducing sugars, food and beverage products in enclosed spaces.

**Conditions to Avoid**

Corrosive liquid. Do not store near strong acids.

**Incompatible Materials**

Strong acids. Soft metals such as aluminum, brass, bronze, copper, lead, tin, zinc or other alkali sensitive metals or alloys.

**Hazardous Decomposition Products**

Oxides of carbon, nitrogen and sulfur when taken to dryness and burned.

---

**SECTION 11: TOXICOLOGICAL INFORMATION**

---

**Product Summary**

This product contains potassium hydroxide and is corrosive. It can cause serious burns and extensive tissue destruction if it is not quickly removed.

**Acute Toxicity:**

**Dermal:** No data available

**Inhalation:** No data available. Corrosive. Because of the product's high viscosity, it is unlikely that respirable droplets could be produced. However, such droplets if produced and inhaled could be corrosive to the respiratory tract, and could cause severe irritation of the respiratory tract with coughing, choking, pain and possibly burns of the mucous membranes.

**Oral:** LD50 about 1,300 mg/kg rat (estimated using additivity formula). Toxic if swallowed. Corrosive. May cause severe mucous membrane burns and gastrointestinal burns.

**Skin Corrosion/Irritation**

Corrosive. Causes severe skin burns. Prolonged or repeat skin exposures can result in dermatitis.

**Serious Eye Damage/Irritation**

Corrosive. Causes serious eye damage which can result in severe irritation, pain and burns, and permanent damage including blindness.

**Sensitization - Respiratory or Skin**

Based upon component data, not expected to be a skin sensitizer.

**Germ Cell Mutagenicity**

No data available.

**Carcinogenicity**

Ethylene glycol butyl ether is listed by ACGIH as Group A3: confirmed animal carcinogen with unknown relevance to humans.



---

**CELL-KLEEN™ HD2**

Page: 6 of 8  
Date Prepared: August 23, 2019  
SDS No.: 1267

---

**Developmental/Reproductive Toxicity**

Ethylene glycol butyl ether has been toxic to the fetus in lab animals at doses toxic to the mother. Effects on reproduction have been seen only at doses that produced significant toxicity to the parent animals.

**Specific Target Organ Effects - Single Exposure**

No data available.

**Specific Target Organ Effects - Repeated or Prolonged Exposure**

Ethylene glycol butyl ether has caused effects on the blood (hemolysis) and kidney and liver effects in lab animals. Small but statistically significant increases in tumors were observed in mice but not rats. These effects are not believed to be relevant to humans.

**Aspiration Hazard**

Although potassium hydroxide poses an aspiration hazard, because of this product's high viscosity, product not expected to be an aspiration hazard.

---

**SECTION 12: ECOLOGICAL INFORMATION**

---

**Product Summary**

This material is caustic and will raise the pH of surface waters. Product should be considered nontoxic to aquatic organisms.

**Ecotoxicity**

Freshwater Fish: LC50 100-500 mg/l (estimated using additivity formula)  
Invertebrates: EC50 100-500 mg/l (estimated using additivity formula)  
Algae: ErC50 100-500 mg/l (estimated using additivity formula)

**Persistence and Degradability**

Potassium hydroxide will dissociate into its ionic form in the aquatic environment. Natural carbon dioxide will slowly neutralize it. The organic materials in this product are all readily biodegradable.

**Bioaccumulative Potential**

Bioaccumulation potential of the materials used in this product are low.

**Mobility in soil**

Mobility is high.

**Other Adverse Effects**

Potassium hydroxide has exhibited slight toxicity to terrestrial organisms.

---

**SECTION 13: DISPOSAL CONSIDERATIONS**

---

Product is a D002 Corrosive Hazardous Waste under RCRA definitions. Dispose of contents/container in accordance with all applicable federal, state, and local regulations.

**Note:** Contaminated product, soil, water, container residues and spill cleanup materials may be hazardous wastes. Appropriate hazardous waste designation is the responsibility of the user.

---

**SECTION 14: TRANSPORT INFORMATION**

---

**ID No.:** UN1814  
**Proper Shipping Name:** POTASSIUM HYDROXIDE, solution  
**Hazard Class:** 8  
**Packing Group:** II



**CELL-KLEEN™ HD2**

Page: 7 of 8  
 Date Prepared: August 23, 2019  
 SDS No.: 1267

**Label:** 8  
**Marine Pollutant:** No  
**RQ:** 1,000 lbs for potassium hydroxide CAS# 1310-58-3 or about 5,000 lbs (about 485 gallons) of product  
 1,000 lbs for methyl alcohol CAS# 67-56-1 or about 50,000 lbs (about 4,800 gallons) of product  
**Special Precautions:** None

**SECTION 15: REGULATORY INFORMATION**

**TSCA**  
 The ingredients in this product are listed on the TSCA inventory.

**RCRA HAZARD CLASS**  
 D002 - Corrosive hazardous waste

**SARA 311/312 REPORTABLE HAZARD CATEGORIES:** Immediate (Acute) Health

**REPORTING REQUIREMENTS** (all quantities in pounds)

Component	CAS / 313 Code	Section 302 (EHS) TPQ	Section 304 EHS RQ	CERCLA RQ (1)	Section 313	CAA 112(r) TQ	CWA / OPA
Potassium hydroxide	1310-58-3			1,000			
product RQ for component				5,000 450 gal			
Methyl alcohol	67-56-1			5,000	313		
product RQ for component				350,000 34,000 gal			
Ethylene glycol butyl ether	N230			(2)	313		
(1) Releases exceeding the RQ just be reported to the National Response Center, 800-424-8802 and may be subject to state and local reporting. (2) CERCLA hazardous substance with no assigned RQ							

**NEW JERSEY RIGHT-TO-KNOW INFORMATION**

This product contains water (CAS# 7732-18-5), potassium hydroxide (CAS# 1310-58-3), sodium glucoheptonate (CAS# 31138-65-5), starch (CAS# 9005-25-8), tripropylene glycol monomethyl ether (CAS# 20374-33-8), ethylene glycol butyl ether (CAS# 111-76-2), and methyl alcohol (CAS# 67-56-1).

**CALIFORNIA PROPOSITION 65 INFORMATION**

This product does not contain any chemicals recognized by the state of California to cause cancer and/or birth defects or reproductive harm.

**SCAQMD INFORMATION**

Is there a photochemically reactive material present? No  
 What is the % by volume of photochemically reactive material? 0  
 What is the VOC content? About 80 g/l  
 What is the vapor pressure of VOC's? Less than 2 mm Hg @ 20°C



# SAFETY DATA SHEET

Penetone® Corporation, 125 Kingsland Ave., Clifton, NJ 07014

**CELL-KLEEN™ HD2**

Page: 8 of 8  
Date Prepared: August 23, 2019  
SDS No.: 1267

## SECTION 16: OTHER INFORMATION

### REVISION SUMMARY

Change in header and section 1

### SUPERSEDES ISSUE DATE

January 18, 2015

### HAZARD RATING SYSTEMS:

	<u>HMIS</u>	<u>NFPA</u>
HEALTH	3	3
FLAMMABILITY	0	0
REACTIVITY	0	0
	B	

KEY  
4 = Severe  
3 = Serious  
2 = Moderate  
1 = Slight  
0 = Minimal

FOR ADDITIONAL PRODUCT INFORMATION, CONTACT YOUR SALES ENGINEER  
FOR ADDITIONAL HEALTH/SAFETY INFORMATION, CALL 201-567-3000

THE INFORMATION PRESENTED HEREIN HAS BEEN COMPILED FROM SOURCES CONSIDERED TO BE DEPENDABLE AND ACCURATE TO THE BEST OF PENETONE'S KNOWLEDGE. THE INFORMATION RELATES TO THIS SPECIFIC MATERIAL. IT MAY NOT BE VALID FOR THIS MATERIAL IF USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY ONESELF AS TO THE SUITABILITY AND COMPLETENESS OF THIS INFORMATION FOR HIS OWN PARTICULAR USE.