



SAFETY DATA SHEET

Penetone® Corporation, 375 Murray Hill Parkway, East Rutherford, NJ 07073

NAVEE™ 42

Page: 1 of 8

Date Prepared: October 21, 2024

SDS No.: 6770

SECTION 1: IDENTIFICATION

Product name: NAVEE 42

Recommended use: Degreaser

Physical Description: Clear amber liquid with aromatic odor

Generic Ingredients: Aromatic hydrocarbons, water, surfactants, coupling agents, inorganic builders

Manufacturer:

Penetone Corporation

375 Murray Hill Parkway

East Rutherford, NJ 07073

800-631-1652 or 201-567-3000

Business Contact:

Customer Service

800-631-1652 x2272

Product Safety

800-631-1652 x2257

Emergency Phone Numbers: PENETONE 201-567-3000 CHEMTREC 800-424-9300

SECTION 2: HAZARDS IDENTIFICATION

GHS CLASSIFICATION:

Health:

Skin corrosion: 1C

Eye damage: 1

Specific target organ toxicity - single exposure: 3

Aspiration hazard: 1

Physical:

not classified

DANGER!

Causes Severe Skin Burns and Eye Damage.

May Cause Drowsiness or Dizziness.

May Be Fatal If Swallowed and Enters Airways.



Precautionary Statements:

Prevention:

Avoid breathing fumes or vapors. Do not breath mists if inhalable mists occur during use. Use only outdoors or in a well-ventilated area.

Wear protective gloves, eye protection, and face protection. Wash hands and exposed skin thoroughly after handling.

Keep container tightly closed. Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Response:

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. A mild soap may be used. Wash

contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center, doctor, emergency room or 911 if you feel unwell.

If swallowed: Rinse mouth. Do NOT induce vomiting. Immediately call a poison center, doctor, emergency room, or 911.

Storage:

Store locked up. Store in a well-ventilated place. Keep cool. Keep container tightly closed.

Disposal:

Dispose of contents/container in accordance with local, regional, and national regulations (see Sections 13 and 15 of SDS for disposal and reporting requirements).

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Concentration Wt% (1)
Aromatic petroleum naphtha	64741-67-9	25-50
Water	7732-18-5	25-50
Potassium fatty acid soap	61790-44-1	1-10



SAFETY DATA SHEET

Penetone® Corporation, 375 Murray Hill Parkway, East Rutherford, NJ 07073

NAVEE™ 42

Page: 2 of 8

Date Prepared: October 21, 2024

SDS No.: 6770

Ethoxylated nonylphenol	127087-87-0	1-10
Dipropylene glycol	25265-71-8	1-10
Pine oil	8002-09-3	1-10
Sodium silicate	1344-09-8	<1
Potassium dodecylbenzene sulfonate	27177-77-1	1-10
Tetrasodium pyrophosphate	7722-88-5	<1
Tripotassium phosphate	7778-53-2	<1

(1) Exact percentages being withheld under trade secret provision of OHSA HCS 1910.1200(i)

SECTION 4: FIRST-AID MEASURES

General Description of Symptoms & First-Aid Measures

Most likely work-place exposure routes will be *skin contact* or *inhalation*.

For *skin contact*, typically no immediate effects will be observed. Reddening, irritation, or a burning sensation could develop some time after exposure if product is not quickly washed off.

Inhalation exposure may produce varied effects depending on whether vapor or mist/spray is inhaled (see SECTION 8 for recommended workplace exposure limits). For vapor, typical symptoms would include headaches, dizziness, and drowsiness. In extreme cases, unconsciousness and other central nervous effects may occur. For mist/spray, typical symptoms could include coughing, sneezing, and a tingling or burning sensation in the nose, throat, and lungs.

Eyes

If in eyes: Rinse cautiously with water for several minutes. If contact lenses present, remove them if easy to do. Continue rinsing for several minutes. Immediately call a poison center, doctor, physician or other competent medical authority for medical advice. Penetone recommends that after any eye exposure and initial treatment a physician be seen immediately.

Ingestion

If swallowed: Rinse mouth. Immediately call a poison center, doctor, physician or other competent medical authority. Product presents an aspiration hazard. DO NOT INDUCE VOMITING.

Inhalation

If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center, doctor, physician or other competent medical authority for medical advice.

Skin

If on skin: Take off immediately all contaminated clothing. Rinse skin with water or shower. A mild soap may be used. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice or attention.

Special Treatment / Other

None

SECTION 5: FIRE FIGHTING MEASURES

Flammable Properties

Classification: not classified

Flash Point: none to boil

Autoignition Temperature: not determined

Lower Flammable Limit: not determined **Upper Flammable Limit:** not determined

Specific Hazards

Contains combustible solvent. Although no flash point up to 200°F, combustible vapors may be given off above this



SAFETY DATA SHEET

Penetone® Corporation, 375 Murray Hill Parkway, East Rutherford, NJ 07073

NAVEE™ 42

Page: 3 of 8

Date Prepared: October 21, 2024

SDS No.: 6770

temperature. The product is water based and water dilutable and will self extinguish with addition of water.

Extinguishing Media

Suitable: SMALL FIRE: Use dry chemical, carbon dioxide (CO₂), water spray or regular foam. LARGE FIRE: water spray, water fog, or foam.

Unsuitable: Do not use solid water stream as this may spread fire.

Protection & Precautions for Firefighters

Protective Equipment & Clothing: Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters protective clothing will only provide limited protection.

Fire Fighting Guidance: Cool containers with flooding quantities of water until well after fire is out. Move containers from fire area if you can do it safely. Dike fire control water for later disposal; do not scatter material. Containers can expand and explode under fire conditions due to vapor buildup. Always stay away from containers engulfed in fire.

Hazardous Combustion Products: Smoke, fumes, and oxides of carbon, sulfur, and phosphorus, particularly when taken to dryness.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Land Spill

Eliminate sources of ignition. Do not touch or walk through spilled material. Stop leak if you can do it safely. For large spills, dike and pump into properly labeled containers for reclamation or disposal. For small spill, soak up with absorbent material and place in properly labeled containers for disposal.

Water Spill

Product forms emulsion with water which may make cleanup difficult. Avoid agitation to minimize emulsion formation. Remove product from water surface by skimming or with suitable absorbents. Put into properly labeled containers for reclamation or disposal. If allowed by local environmental regulatory agencies, you may use a suitable dispersant. Check with local environmental regulatory agencies for reporting requirements.

See SECTION 8 for EXPOSURE CONTROLS and PERSONAL PROTECTION.

SECTION 7: HANDLING & STORAGE

Handling

Do not handle near heat, sparks, or flame. Avoid contact with oxidizing agents. Use only with adequate ventilation/personal protection (SEE section 8). Avoid contact with eyes, skin and clothing. After handling, always wash hands thoroughly with soap and water. Avoid personal contact with any residue. Dispose of empty containers with care. Empty containers can contain flammable residue and explosive vapors. **Do not cut, weld, or reuse empty container.**

Storage

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Do not store near heat, sparks, open flame, or other ignition sources. Do not store near strong oxidizing agents. Do not store in direct sunlight. Avoid storing above 120°F (49°C).

SECTION 8: EXPOSURE CONTROLS and PERSONAL PROTECTION

Engineering Controls

Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits.



SAFETY DATA SHEET

Penetone® Corporation, 375 Murray Hill Parkway, East Rutherford, NJ 07073

NAVEE™ 42

Page: 4 of 8

Date Prepared: October 21, 2024

SDS No.: 6770

Personal Protection

Inhalation A respiratory protection program that meets OSHA's 29 CFR 1910.134 or ANSI Z88.2 requirements must be followed whenever workplace conditions warrant respirator use. Use of an organic vapor mask or respirator is recommended.

Skin Wear chemical resistant gloves such as: rubber, nitrile, neoprene, or latex when skin contact is possible. Protective clothing including gloves, apron, sleeves, boots, head and face protection should be worn depending on how the product is used. PPE should be cleaned thoroughly after each use.

Eyes Penetone recommends always wearing safety glasses as a minimum in any workplace. Conditions may warrant the use of chemical goggles and possibly a face shield. Consult your standard operating procedure or safety professional for advice. Use protective eye and face devices that comply with ANSI Z87.1-1987.

Additional Remarks

Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use.

Occupational Exposure Limits

Component Name	Source	Value	Type	Notation
Aromatic petroleum naphtha	ACGIH	100 mg/m ³	TWA	Appendix H
	NIOSH	350 mg/m ³	TWA	
		1800 mg/m ³	Ceiling	

SECTION 9: PHYSICAL & CHEMICAL PROPERTIES

Appearance: clear amber liquid

Odor: aromatic

Odor Threshold: not determined

pH: 12

Melting Point / Freezing: about 30°F

Boiling Point / Boiling Point Range: about 212°F

Flash Point: none to boil

Evaporation Rate: equal to water

Flammability: not applicable

Lower Flammable Limit: not determined

Upper Flammable Limit: not determined

Explosive Properties: not applicable

Vapor Pressure: equal to water

Relative Vapor Density: equal to water

Relative Density: 1.04

Solubility (Water): forms emulsion (stable for one to 12 hours)

Partition Coefficient (K_{ow}): not determined

Auto-ignition temperature: not determined

Decomposition temperature: not determined

Viscosity: 10 to 30 centipoise at room temperature



SAFETY DATA SHEET

Penetone® Corporation, 375 Murray Hill Parkway, East Rutherford, NJ 07073

NAVEE™ 42

Page: 5 of 8

Date Prepared: October 21, 2024

SDS No.: 6770

SECTION 10: STABILITY & REACTIVITY

Reactivity

Not reactive.

Chemical Stability

Stable.

Hazardous Reactions

None known.

Conditions to Avoid

Contains combustible liquid. Do not store near sources of heat, sparks, open flame, or other ignition sources.

Incompatible Materials

Strong oxidizing agents. Strong acids.

Hazardous Decomposition Products

Smoke, fumes, and oxides of carbon, sulfur, and phosphorus, particularly when taken to dryness.

SECTION 11: TOXICOLOGICAL INFORMATION

Product Summary

Product is corrosive to skin, eyes, and other tissues, including oral and gastrointestinal. Mists can be corrosive to the eyes and respiratory tract. Ingestion may result in damage to the mouth, tongue, throat, and esophagus. Vapor/aerosol concentrations above recommended exposure levels may be irritating to the eyes and respiratory tract, and may cause headaches, dizziness, drowsiness, unconsciousness and other central nervous system effects.

Acute Toxicity:

Dermal: Rabbits, LD50 > 2,000 mg/kg (estimated using additivity formula)

Inhalation: no data available

Oral: Rats, LD50 > 2,000 mg/kg (estimated using additivity formula)

Skin Corrosion/Irritation

Based upon component data and product pH, product as a whole may be corrosive to the skin.

Serious Eye Damage/Irritation

Based upon component data and product pH, product as a whole may be corrosive to the eyes and potentially cause serious eye damage.

Sensitization - Respiratory or Skin

Based upon component data, not expected to be a skin sensitizer.

Germ Cell Mutagenicity

Based upon component data, not expected to cause germ cell mutagenicity.

Carcinogenicity

No material in this product is listed by IARC, NTP, or OSHA as a carcinogen.

Reproductive Toxicity

No data available.

The nonionic surfactant used in this product has produced effects in the fetus only at levels that were toxic to the parent animals.



SAFETY DATA SHEET

Penetone® Corporation, 375 Murray Hill Parkway, East Rutherford, NJ 07073

NAVEE™ 42

Page: 6 of 8

Date Prepared: October 21, 2024

SDS No.: 6770

Specific Target Organ Effects - Single Exposure

No data available.

Specific Target Organ Effects - Repeated or Prolonged Exposure

No data available.

The aromatic hydrocarbon caused kidney effects in male rats which are not considered relevant to humans.

Inorganic phosphates have been extensively studied because of their use as food additives. Very high oral doses (1% in the diet) have produced toxic effects on the kidneys and parathyroid glands.

In three month study, rats fed 200, 600, and 1800 ppm sodium silicate, changes were reported in the blood chemistry of some animals, but no specific organ effects were observed. In a 4 week 2.4g/kg/day oral feeding study, kidney effects were seen in dogs but no observed effects seen in rats. 600 and 1200 ppm sodium silicate in drinking water of rats decreased number of births and survival to weaning. Frequent ingestion over extended periods of time of gram quantities of sodium silicate are associated with kidney stone formation and other siliceous urinary calculi in humans.

Aspiration Hazard

Based upon available data and comparison to similar materials, if swallowed, may pose a lung aspiration hazard during vomiting. Lung aspiration may result in chemical pneumonitis, pulmonary edema, and damage to lung tissue or death.

SECTION 12: ECOLOGICAL INFORMATION

Product Summary

Product is expected to be toxic to fish, aquatic invertebrates, algae, and microorganisms. (Acute aquatic toxicity category 2 by European Union classification).

Ecotoxicity

LC/EC/IC 1-10 mg/l (estimated using additivity formula)

Persistence and Degradability

Product components range in biodegradability from not readily to readily biodegradable..

Bioaccumulative Potential

No data available for the product. Aromatic solvent used in this product has the potential to bioaccumulate.

Mobility in soil

No data available for the product. Product is a complex mixture. Components will partition into water and soil phases depending on inherent solubility of component in water.

Other Adverse Effects

None known

SECTION 13: DISPOSAL CONSIDERATIONS

Product is a D002 Corrosive Hazardous Waste under RCRA definitions. Dispose of contents/container in accordance with all applicable federal, state, and local regulations.

Note: Contaminated product, soil, water, container residues and spill cleanup materials may be hazardous wastes. Appropriate hazardous waste designation is the responsibility of the user.



SAFETY DATA SHEET

Penetone® Corporation, 375 Murray Hill Parkway, East Rutherford, NJ 07073

NAVEE™ 42

Page: 7 of 8

Date Prepared: October 21, 2024

SDS No.: 6770

SECTION 14: TRANSPORT INFORMATION

ID No.: UN3266
Proper Shipping Name: CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S., (contains sodium silicate)
Hazard Class: 8
Packing Group: III
Label: CORROSIVE
Marine Pollutant: No
RQ: No
Special Precautions: none

SECTION 15: REGULATORY INFORMATION

TSCA

The ingredients in this product are listed on the TSCA inventory.

RCRA HAZARD CLASS

D002 - Corrosive hazardous waste

SARA 311/312 REPORTABLE HAZARD CATEGORIES: Immediate (Acute) Health Fire

REPORTING REQUIREMENTS (all quantities in pounds)

Component	CAS / 313 Code	Section 302 (EHS) TPQ	Section 304 EHS RQ	CERCLA RQ	Section 313	CAA 112(r) TQ	CWA / OPA
no components subject to reporting							

NEW JERSEY RIGHT-TO-KNOW INFORMATION

This product contains aromatic petroleum naphtha (CAS# 64741-67-9), water (CAS# 7732-18-5), potassium fatty acid soap (CAS# 61790-44-1), ethoxylated nonylphenol (CAS# 127087-87-0), dipropylene glycol (CAS# 25265-71-8), pine oil (CAS# 8002-09-3), sodium silicate (CAS# 1344-09-8), potassium dodecylbenzene sulfonate (CAS# 27177-77-1), tetrasodium pyrophosphate (CAS# 7722-88-5), and tripotassium phosphate (CAS# 7778-53-2).

CALIFORNIA PROPOSITION 65 INFORMATION

This product does not contain any chemicals recognized by the state of California to cause cancer and/or birth defects or reproductive harm.

SCAQMD INFORMATION

Is there a photochemically reactive material present? Yes
What is the % by volume of photochemically reactive material? About 40
What is the VOC content? About 500 g/l
What is the vapor pressure of VOC's? Less than 0.1 mm Hg @ 20°C

SECTION 16: OTHER INFORMATION

REVISION SUMMARY

Change in Header and Section 1

SUPERSEDES ISSUE DATE

September 25, 2019



SAFETY DATA SHEET

Penetone® Corporation, 375 Murray Hill Parkway, East Rutherford, NJ 07073

NAVEE™ 42

Page: 8 of 8

Date Prepared: October 21, 2024

SDS No.: 6770

HAZARD RATING SYSTEMS:

	<u>HMIS</u>	<u>NFPA</u>
HEALTH	2	2
FLAMMABILITY	1	1
REACTIVITY	0	0
	B	

KEY
4 = Severe
3 = Serious
2 = Moderate
1 = Slight
0 = Minimal

FOR ADDITIONAL PRODUCT INFORMATION, CONTACT YOUR SALES ENGINEER
FOR ADDITIONAL HEALTH/SAFETY INFORMATION, CALL 201-567-3000

THE INFORMATION PRESENTED HEREIN HAS BEEN COMPILED FROM SOURCES CONSIDERED TO BE DEPENDABLE AND ACCURATE TO THE BEST OF PENETONE'S KNOWLEDGE. THE INFORMATION RELATES TO THIS SPECIFIC MATERIAL. IT MAY NOT BE VALID FOR THIS MATERIAL IF USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY ONESELF AS TO THE SUITABILITY AND COMPLETENESS OF THIS INFORMATION FOR HIS OWN PARTICULAR USE.