

MILITARY / COMMERCIAL AVIATION



Penetone 1112A is a ready-to-use carbon remover and aircraft thrust reverser, aft sleeve and bare metal component cleaner that has passed the effects on metals section of MIL-PRF-87937C.

Designed to remove tough carbon deposits, **Penetone 1112A** will also remove enamel paints. Although designed as a ready-to-use product, **Penetone 1112A** can be used diluted.

FEATURES AND BENEFITS

- Ready to use
- Safe on most metals
- Removes carbon
- Mild odor
- High flash point (> 210°F)

Use procedures

Carbon Removal

Penetone 1112A is ready to use. Do not add solvent or water. Fill cleaning bath to a reference mark with fresh compound. Before soaking item, remove loose grease, dirt and oil with a degreasing solvent. Place objects to be cleaned in a wire basket or hang them by a wire so as to be off the bottom and completely immersed. Soak for 2 to 16 hours as needed at temperatures up to 130°F and rinse with water or solvent. Brush with a stiff brush under hot water for complete removal.

Thrust Reverser, Aft Sleeve and Bare Metal Component Cleaning

Refer to directions in Technical Order 1C-135(K)A-3-4 or other applicable technical order. Use **Penetone 1112A** as supplied to 1:20 to remove soils. Apply by coarse spray or bucket and brush, agitate with abrasive pads and follow with a water rinse.

PENETONE® 1112A

MULTI METAL SAFE CARBON REMOVING COMPOUND

PHYSICAL PROPERTIES

Appearance	Clear liquid
Odor	Glycol ether
pH	12-12.5
Freezing Point	About 25°F
Boiling Point	About 212°F
Flash Point (TCC)	None to boil
Relative Density	0.99
Auto-Ignition Temperature	Not determined
Water Solubility	Complete
Viscosity	Less than 5 CP at room temperature

INCOMPATIBILITY

Strong acids, strong oxidizers.

WAREHOUSING PRECAUTIONS

Store locked up. Keep container tightly closed when not in use.
Do not store in direct sunlight.
Avoid storing above 120°F (49°C).

APPROVALS

P-C-111DTy II, MIL-PRF-87937 Corrosion

AVAILABLE SIZES

5 gallon Pail

55 gallon Drum

FIRST AID MEASURES

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a local Poison Control Center, doctor, physician or other competent medical authority for medical advice. Penetone recommends that after any eye exposure a physician be seen immediately.

If swallowed: Rinse mouth. DO NOT INDUCE VOMITING. Immediately call a poison center, doctor, physician or other competent medical authority for medical advice.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a local Poison Control Center, physician, or other competent medical authority for medical advice.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. A mild soap may be used to wash skin. Wash contaminated clothing before reuse. Immediately call a local Poison Control Center, doctor, physician or other competent medical authority for medical advice.

PERSONAL PROTECTION Security equipment



WHMIS



IMPORTANT: Before using **PENETONE 1112A**, always be sure to read and follow precautions and directions for use appearing on the product container label and on the safety data sheet (S.D.S).



CLIFTON

125 Kingsland Avenue
Clifton, NJ 07014
Tel.: 201-567-3000
Toll free: 1-800-631-1652

MONTREAL

10,900 Secant Street
Anjou, QC H1J 1S5
Tel.: 514-355-4660
Toll free: 1-800-361-8927

EDMONTON

11411-160 Street
Edmonton, Alberta T5M 3T7
Tel.: 780-454-3919
Toll free: 1-866-454-3919

United States
www.penetone.com

Canada
www.westpenetone.com