

### GENERAL USE



**Penmul R950** is a mixture of solvent and emulsifiers intended for use in difficult industrial cleaning applications. **Penmul R950** is especially effective in loosening and dissolving asphaltic and heavy petroleum based soils and sludge accumulations.

**Penmul R950** is typically used to clean and desludge oil storage tanks, engine blocks and where asphalt is mixed, applied or pumped.

**Penmul R950** has a flashpoint above 140°F, rendering it non-hazardous for disposal.

### FEATURES AND BENEFITS

- Water rinseable
- Effective at room temperature
- Effective on asphaltic deposits
- Safe on all metals
- Works fast
- Free of chlorinates
- Safer than flammable products
- Versatile and multipurpose
- No heat required
- Increased productivity

### DIRECTIONS FOR USE

#### Use procedures

**Penmul R950** can be applied by brush or coarse spray, in a tank operation, or in a parts washing machine. When used in a tank, agitation should be provided for best results.

**Penmul R950** may be used concentrated or diluted with water, mineral spirits, kerosene or fuel oil.

#### *Application & Procedure Using Penmul R950 Concentrated:*

#### Automotive

Spray or brush on the undergear of trucks, buses, tractors, and road building equipment for removing asphalt, tar and pitch. Allow to set for a few minutes, then hose or wipe off.

#### Parts Washing

Soak until oils and grease are removed. Rinse with water or mineral spirits.

#### Note

**Penmul R950** may attack asphaltic flooring and some plastics. Pre-test on these surfaces before using. Do not use on painted surfaces.

# PENMUL R950

## HEAVY DUTY SOLVENT EMULSION DEGREASER

### PHYSICAL PROPERTIES

|                           |                                    |
|---------------------------|------------------------------------|
| Appearance                | Clear liquid                       |
| Odor                      | Aromatic                           |
| pH                        | Not applicable                     |
| Freezing Point            | Less than 20°F                     |
| Boiling Point             | 350-410°F                          |
| Flash Point               | 150°F TCC                          |
| Relative Density          | 0.90                               |
| Auto-Ignition Temperature | Not determined                     |
| Water Solubility          | Emulsifies                         |
| Viscosity                 | Less than 5 CP at room temperature |

### INCOMPATIBILITY

Strong oxidizing agents.

### WAREHOUSING PRECAUTIONS

Store in a well-ventilated place. Keep container tightly closed. Open slowly in order to control possible pressure release. Keep cool. Store locked up. Do not store near heat, sparks, open flame, or other ignition sources. Do not store in direct sunlight. Avoid storing above 120°F (49°C).

### AVAILABLE SIZES

5 gallon Pail

55 gallon Drum

### FIRST AID MEASURES

**If in eyes:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists or develops: Get medical advice or attention. Penetone recommends that after any eye exposure a physician be seen immediately.

**If swallowed:** Immediately call a poison center, doctor, physician or other competent medical authority. Rinse mouth. Product presents an aspiration hazard. DO NOT INDUCE VOMITING.

**If inhaled:** Remove person to fresh air and keep comfortable for breathing. Call a poison center, doctor, physician or other competent medical authority if you feel unwell.

**If on skin (or hair):** Take off immediately all contaminated clothing. Rinse skin with water or shower. A mild soap may be used to wash skin. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice or attention.

### PERSONAL PROTECTION Security equipment



WHMIS



**IMPORTANT:** Before using **PENMUL R950**, always be sure to read and follow precautions and directions for use appearing on the product container label and on the safety data sheet (S.D.S).



#### CLIFTON

125 Kingsland Avenue  
Clifton, NJ 07014  
Tel.: 201-567-3000  
Toll free: 1-800-631-1652

#### MONTREAL

10,900 Secant Street  
Anjou, QC H1J 1S5  
Tel.: 514-355-4660  
Toll free: 1-800-361-8927

#### EDMONTON

11411-160 Street  
Edmonton, Alberta T5M 3T7  
Tel.: 780-454-3919  
Toll free: 1-866-454-3919

United States  
[www.penetone.com](http://www.penetone.com)

Canada  
[www.westpenetone.com](http://www.westpenetone.com)