

SOLVENT DEGREASERS



ENVIROSOL is a versatile and high-performance cleaner and degreaser that utilizes the solvency and sustainability of terpene chemistry as a replacement for aromatic solvents such as xylene or toluene. It removes a multitude of soils for a variety of applications in the oilfield, manufacturing, mining, and printing industries.

FEATURES AND BENEFITS

- Free of aromatic solvents such as xylene or toluene
- Utilizes the solvency and sustainability of terpene chemistry
- Non-flammable
- Thixotropic formula available with **ENVIROGEL**
- Powerful and fast acting
- Does not freeze
- Rinses effectively leaving little to no residue
- Removes a multitude of soils including petroleum-based materials, adhesives, inks, and other water-insoluble deposits such as waxes
- Safe on all metal and painted surfaces
- For stubborn soils or applications, more robust solvency available in **ENVIROSOL PLUS**

DIRECTIONS FOR USE

Soils to be removed	Tar, grease, lubricants, adhesives, bituminous residue, heavy oils, waxes, asphaltenes, etc.
Use procedure	Use ENVIROSOL as part of a manual or low-pressure application. For very thick accumulations, physically remove excess or loose deposits before application. May also be used as an additive in dip tank applications.
Concentration	Most effective when used undiluted. May also be emulsified in water for immediate use with lighter cleaning tasks such as film removal or spot cleaning.
Dwell time / Operation time	5 to 30 minutes, according to the amount of soil.
Mechanical action	Scrubbing and wiping recommended to remove stubborn deposits.
Rinsing	Allow product to dwell before rinsing. High-pressure, hot water is recommended.

ENVIROSOL

HEAVY-DUTY SOLVENT CLEANER & DEGREASER

PHYSICAL PROPERTIES

Appearance	Yellow Liquid
Odour	Citrus/solvent
Specific Gravity @ 20°C	0.84-0.85
Viscosity	Thin
pH	Not applicable
Flash Point (TCC, COC)	48°C, 61°C (118,4°F - 141,8°F)
Boiling Point	Not determined
Freezing Point	<-40°C (-40°F)
Foaming Tendency	Nil
Rinsability	Excellent
Water Solubility	Emulsifies



INCOMPATIBILITY

Oxidizing materials
Do not use on finely coated surfaces

WAREHOUSING PRECAUTIONS

Store away from heat sources and flames

AVAILABLE SIZES

		
20L / 5,28Gal.	205L / 54,16Gal	1000L / 264,17Gal.

FIRST AID MEASURES

EYE CONTACT

Wash with plenty of water for 15 minutes.
Consult physician if irritation develops or persists.

SKIN CONTACT

Wash with plenty of water for 15 minutes.
Consult physician if irritation develops or persists.

INHALATION

Give fresh air or artificial respiration.
Consult physician.

INGESTION

Do not induce vomiting. Drink plenty of water and consult physician immediately.

HEALTH

2

FLAMMABILITY

2

REACTIVITY

1

LEGEND

0 = MINIMAL RISK
1 = SLIGHT RISK
2 = MODERATE RISK
3 = SERIOUS RISK
4 = SEVERE RISK

PERSONAL PROTECTION Security equipment



WHMIS



IMPORTANT: Before using ENVIROSOL, always be sure to read and follow precautions and directions for use appearing on the product container label and on the safety data sheet (S.D.S).



CARLSTADT

700 Gotham Parkway
Carlstadt, New Jersey 7072
Tel.: 201-567-3000
Toll free : 1-800-631-1652

MONTREAL

10,900 rue Secant
Anjou, Quebec H1J 1S5
Tel.: 514-355-4660
Toll free : 1-800-361-8927

EDMONTON

11411-160 Street
Edmonton, Alberta T5M 3T7
Tel.: 780-454-3919
Toll free: 1-866-454-3919

United States
www.penetone.com

Canada
www.westpenetone.com