

PULP AND PAPER



Pensolv LV15 is a 15% VOC specialty product specifically developed for papermachine wire and felt cleaning. **Pensolv LV15** is designed for use with continuous cleaning applications or batch cleaning for the removal of stickies. **Pensolv LV15** is highly effective in removing pitch, latex, resins, and adhesives.

Pensolv LV15 is safe on all equipment – rubber rolls, roll covers, bearing housings, and machine frame.

FEATURES AND BENEFITS

- Safe on all dewatering equipment
- 15% VOC Cleaner
- Economical
- Pleasant mild citrus odor from one of our natural ingredients
- No transfer of harsh solvent odors to the sheet. Low residue
- No need to purge from the process water system
- FDA Compliant – Contains no phenols, chlorinated, or aromatic solvents
- Improves sheet quality and extends clothing life.
- Reduces paperwork: No SARA Title III or Prop. 65 Ingredients
- Not photochemically reactive

Use procedures

Paper machine felt and wire

Use **Pensolv LV15** while the machine is running. Pump **Pensolv LV15** from the holding tank and shower onto the wire, felt, or roller using a spray bar. **Pensolv LV15** can be applied manually using a hand held sprayer. Apply by non-atomizing coarse spray directly to the wire, felt, or roller under low pressure.

General cleaning

Pensolv LV15 can be applied by non-atomizing coarse spray. Other application methods may be used, including brushing it on or dipping parts into the solvent. After application and a brief soaking period, blow surfaces dry with compressed air. No water rinse is needed.

Concentration

Pensolv LV15 is to be used full strength.

PENSOLV LV15

LOW VOC "STICKIES" REMOVAL SOLVENT

PHYSICAL PROPERTIES

Appearance	Clear liquid
Odor	Mild citrus
pH	Not applicable
Freezing Point	Less than 0°F
Boiling Point	About 315°F
Flash Point (TCC)	105°F
Relative Density	0.78
Auto-Ignition Temperature	Not determined
Water Solubility	Insoluble
Viscosity	Less than 5 CP at room temperature

INCOMPATIBILITY

Strong oxidizing agents.

WAREHOUSING PRECAUTIONS

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Do not store near heat, sparks, open flame, or other ignition sources. Do not store in direct sunlight. Avoid storing above 120°F (49°C).

AVAILABLE SIZES

55 gallon Drum

FIRST AID MEASURES

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists or develops: Get medical advice or attention. Penetone recommends that after any eye exposure a physician be seen immediately.

If swallowed: Immediately call a poison center, doctor, physician or other competent medical authority. Rinse mouth. Product presents an aspiration hazard. **DO NOT INDUCE VOMITING.**

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center, doctor, physician or other competent medical authority if you feel unwell.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. A mild soap may be used to wash skin. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice or attention.

PERSONAL PROTECTION Security equipment



WHMIS



IMPORTANT: Before using **PENSOLV LV15**, always be sure to read and follow precautions and directions for use appearing on the product container label and on the safety data sheet (S.D.S).



CLIFTON

125 Kingsland Avenue
Clifton, NJ 07014
Tel.: 201-567-3000
Toll free: 1-800-631-1652

MONTREAL

10,900 Secant Street
Anjou, QC H1J 1S5
Tel.: 514-355-4660
Toll free: 1-800-361-8927

EDMONTON

11411-160 Street
Edmonton, Alberta T5M 3T7
Tel.: 780-454-3919
Toll free: 1-866-454-3919

United States
www.penetone.com

Canada
www.westpenetone.com